


PanaSync™ E15



- Full Scan Capability
- Up Front Controls
- .27mm Dot Pitch
- 24 Hour / 7 Day Customer Support
- 48 Hour Swap / 3 Year Limited Warranty

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright ©1997 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e S p e c S h e e t

	<p>Panasonic Computer Peripheral Company Division of Panasonic Communications & Systems Company Unit of Matsushita Electric Corporation of America Display Monitors Division Headquarters 2 Panasonic Way, Secaucus, NJ 07094</p>
---	---

www.panasonic.com/alive

PanaSync™ E15 Specifications

CRT Screen Size	15" CRT (13.7"/34.8 cm Viewable Image Size) Flat-Square
Dot Pitch	0.27mm
Surface	Anti-Static/Silica-Coat
Input	
Video Signal	RGB analog (0,7 Vp-p, 7 ohms)
Sync Signal	H/V separate (TTL)
H-Sync	30-61kHz (Multi-mode)
V-Sync	50-90Hz
Modes	7 Factory Presets
Connector & Cables	
Video Input	One 15-pin Male Mini D-Sub on attached cable (4.92'/1.5 meters)
Mac Adapter	Available-Free of Charge
Power	One UL 3-pole (CEE 22 type) (4.92'/1.5 meters)
Controls	
Front Panel	Power Switch, Contrast, Brightness, H Size, H Position, V Size, V Position
Indicators	LED power indicator Green=On, Yellow=Power-saving mode
Video Bandwidth	75MHz (typical)
Resolution (HxV)	1,024 dots x 768 lines 75Hz NI FCC Class B, Max.
Operating Conditions	
Temperature	32-95°F
Humidity	5%-90% Non-condensing
Dimensions	14.65" (W) x 14.92" (H) x 16.22" (D)
Weight	31.9 lbs
Approvals	UL, C-UL=CSA, FCC Class B, DHHS, Energy Star /VESA DPMS
Power Consumption	
Supply	120V AC (60Hz)
On	100 Watts (Typical)
Standby	<30 Watts
Suspend	<30 Watts
Off	<8 Watts
Warranty	3 Years Limited Parts & Labor, 1 Year Express Exchange (see your dealer for details)
Other	Windows '95 Plug & Play 24-hour/7-day customer service 48-hour Swap Program