

EggCam™ GP-KR0011 Desktop Camera



Features

- Full Motion Video Capture (30 fps) at 320 x 240
- Capture 32-bit Still Images at 640 x 480
- Tilt and Swivel Base for Convenient Camera Positioning, Pan 360° & Tilt 30°
- Automatic Gain Control (AGC): Adjusts for proper exposure in different lighting conditions
- Adjustable Focus: Capture Subject as Close as 3.9" up to infinity
- Built In Omni Directional Microphone
- Optical Viewing Angle 45° Horizontal 33° Vertical

Package includes

- EggCam™ CCD-Based Digital Video Camera with Cables
- 6V AC Adaptor
- PCI Video Capture Card by Hauppauge™
- CU-SeeMe™ Videoconferencing Software from White Pine™
- VideoLink 324™ H.324 Videoconferencing from SmithMicro™
- Video E-Mail Software from SmithMicro™
- Easy Setup Instructions

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright ©1997 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e S p e c S h e e t

Panasonic	Panasonic Digital Imaging Company Computer Peripherals Division Unit of Matsushita Electric Corporation of America Headquarters: 2 Panasonic Way, Secaucus, NJ 07094
------------------	---

w w w . p a n a s o n i c . c o m / o f f i c e

GP-KR0011 Specifications

Lens & Pickup

Focus	Focal Length 4.6mm Focus Adjustment - 3.9" to infinity
--------------	---

Pick Up System	CCD 270,000 Pixel Elements (542 Horizontal x 496 Vertical)
-----------------------	--

Iris	Automatic Gain Control (AGC) and Electric Light Control (ELC) adjusts for proper exposure in different lighting conditions
-------------	--

Recommended Illumination	40 Lux to 10,000 Lux (Optimum)
---------------------------------	--------------------------------

Image Device	1/4 inch CCD
---------------------	--------------

Video

Output Signal	NTSC Television Standard
----------------------	--------------------------

Video Capture	Board PCI Bus Master Video Capture Card, Brooktree™ Video Encoder, Composite Video Input for EggCam™, S-Video Input for other Video Source (VCR, Laserdisk, etc.) and AC connection to power camera
----------------------	---

Video Output Impedance	75 ohms
-------------------------------	---------

Signal to Noise	40 db (AGC Off Equivalence)
------------------------	-----------------------------

Horiz. Resolution	330 TV Lines Minimum, Center
--------------------------	------------------------------

White Balance	Automatic
----------------------	-----------

Built in Microphone	Omnidirectional microphone connects to your computer's sound board
----------------------------	--

General Specifications

Weight	0.13 Lbs. (60 Grams)
---------------	----------------------

Size	3.2"H x 1.6"W x 1.8"D (approximate)
-------------	-------------------------------------

Power	DC 6V (160mA), use included adaptor or AC connection on capture card
--------------	--

Operating System	Windows 95™, 98 and NT 4.0
-------------------------	----------------------------

System Requirements	Pentium™ 90 MHz (or equivalent) with open PCI System Slot (version 2.1 or higher) Windows 95 Operating System, Sound Board CD-ROM Drive (for Software installation) Graphics Card that supports Windows 95, Direct Draw, and Video Overlay**, 2MB Video Memory is Recommended
----------------------------	---