

KV-SS50EX/55EX Scanner



The Panasonic KV-SS50EX Scanner and the KV-SS55EX Duplex Scanner are high performance 40 ppm scanners designed for efficient and convenient storage of your documents. These scanners are designed for a multitude of imaging applications such as invoices, checks, business cards, irregular sized documents... even wrinkled documents. With superb high-speed paper handling and a compact footprint, a Panasonic Scanner is an extremely attractive solution for a wide variety of document imaging applications.

- Panasonic Image Enhancement Technology featuring *White Level Follow, Automatic Separation & Noise Reduction*
- Pixel Translations ISIS compatible, TWAIN Support
- High-speed simplex scanning at up to 40 ppm (letter size, 200 dpi)
- Duplex scanning capabilities
- 100 page automatic document feeder
- Up to 300 dpi scanning resolutions

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright ©1998 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e S p e c S h e e t

Panasonic

Panasonic Corporate Systems Sales Company
Division of Panasonic Communications & Systems Company
Unit of Matsushita Electric Corporation of America
Imaging Products Group
Headquarters: 2 Panasonic Way, Secaucus, NJ 07094

w w w . p a n a s o n i c . c o m / a l i v e

KV-SS50EX/SS55EX Specifications

Scanning Face	KV-SS50EX- Simplex Scanning (single-sided) KV-SS55EX- Duplex Scanning (front/back sides)
Scanning Method	CCD Image sensor & contact image sensor
Scanning Speed	52 pages/minute at 150 dots/inch 40 pages/minute at 200 dots/inch 27 pages/minute at 300 dots/inch
Duplex Mode	3.0 sec/sheet
Scanning Resolution	150-300 dpi
Tonal Gradation	Binary mode: 64-step gradation (dither mode), 64-step gradation (error diffusion) mode, Grayscale (4 bit/8 bit)
Paper Size	2.2" x 3.6" to 8.5" x 14" (legal)
Paper Thickness	Single paper feed: 2.0 to 7.9 mil Continuous paper feed: 2.4 to 5.9 mil (1 mil = 1/1000 inch)
Paper Weight	Single paper feed: 11 to 34 lbs; Continuous Paper feed: 13 to 27 lbs.
External Dimensions	15.3" H x 22.3" W x 17.7" D
Weight	31 lbs.
Power Requirement	120V +/- 12 VAC, 60 Hz Power Consumption 1.3A maximum (scanning); 0.5A (standby)
Operating Environment	59°F to 86°F; 30% to 80% RH
Storage Environment	32°F to 95°F; 10% to 80% RH
Accessories	Document tray, exit tray, exit tray sheet, power cord, ISIS & TWAIN Drivers, operation manual and installation manual, repacking instructions