

KX-P7510 Black & White Workgroup Laser Printer



- **17 ppm Workgroup Printer**
- **Auto Duplex – Standard**
- **10/100 Base-TX Ethernet – Standard**
- **1200 dpi Class Printing**
- **500 Sheet Universal Cassette – Standard**
- **20 MB RAM – Standard
Up to 132 MB**

Microsoft, Windows and Windows NT are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.
 PostScript is a trademark of Adobe Systems Incorporated.
 ENERGY STAR is a U.S. registered mark.
 PowerPage is a registered trademark of Electronics for Imaging, Inc.
 All other acknowledgements are trademarks or registered trademarks of their respective holders.
 As an ENERGY STAR Partner, Panasonic has determined that this Product meets the ENERGY STAR guidelines for energy efficiency.
 This product may be subject to export control regulations.
 Panasonic is a brand name of Matsushita Electric.

Panasonic Document Imaging Company
 A Division of Matsushita Electric Company of America
 2 Panasonic Way, Secaucus, NJ 07094

KX-P7510 Specifications

Print Method	Semiconductor Laser and Electrophotography	
Print Speed	17 ppm (Letter), 16 ppm (A4)	
Print Resolution	600 x 600 dpi, 1200 dpi class with Optimum Resolution Technology	
Emulation	PCL 6 Standard, Optional PostScript Level 2	
RAM Memory	20 MB Standard, Up to 132 MB	
Processor	Power PC 603e-100 MHz	
Resident Fonts	45 Scalable fonts, 1 Bitmap	
Optional Fonts	35 Type 1 for PostScript option	
Interface	IEEE 1284 bi-directional parallel	
Network	10/100 Base-TX	
Optional Interface	Interface Card (LocalTalk/RS-232C) Interface Kit (IrDA/RS-232C)	
Paper Input	500 Sheets: Standard Tray 100 Sheets: Multi-Purpose Tray 500 Sheets: Optional 2nd Tray	
Paper Output	250 Sheets Face Down	
Paper Handling	Standard Tray:	Letter, A4, Legal, B5, Executive, Folio Paper, Transparency, Cardstock, Label, Envelope
	MPT:	Letter, A4, Legal, B5, Executive, Folio
	Optional 2nd Tray:	Letter, A4, Legal, B5, Executive, Folio
Paper Weight	Plain Paper 16 to 24 lbs. (60 to 90 g/m ²): Standard Tray 16 to 43 lbs. (60 to 161 g/m ²): MPT 16 to 24 lbs. (60 to 90 g/m ²): Optional 2nd Tray Envelope 16 to 24 lbs. (60 to 90 g/m ²): MPT 16 to 20 lbs. (60 to 75 g/m ²): Optional 2nd Tray	
Duplex	Standard (20 to 24 lbs. (75 to 90 g/m ²))	
Noise Level	50 dB (A): Printing	36 dB (A): Standby
Power Consumption	Average: 340 W : Printing / 25 W : Standby	
Environment	Operating: 50 to 90.5°F (20 to 80 % RH) Storage: 32 to 95°F (10 to 90 % RH)	
Dimension	16.8" x 17.0" x 11.9" (W x D x H) (427mm x 432mm x 301mm)	
Weight	Approx. 37.4 lbs. (17 Kg)	

System Requirements

For Windows computer:	95, Windows 98 and Windows NT
- An IBM PC or compatible computer with 486 processor or higher	- 20 MB available hard-disk space
- Windows 3.1, 3.11 ^{*2} , Windows 95, Windows 98, Windows NT 4.0 ^{*3,4} or Windows® 2000	- CD-ROM drive
- Appropriate interface cables for your network or printer connection	For Macintosh computer:
- 8 MB of RAM for Windows 3.1, 3.11 (16 MB recommended for some applications) or 16 MB for Windows	- Mac OS 7.5x, 7.6x, 8.x, 9.0
	- Appropriate interface cables for your network and printer connection
	- CD-ROM drive
	- Network Card for Ethernet or LocalTalk/RS-232C interface card
	- Upgrade SIMM

*2 Microsoft, Windows Operating system Version 3.1 or 3.11 (hereafter Windows 3.1, 3.11)

*3 Microsoft® Windows NT® operating system Version 4.0 (hereafter Windows NT 4.0)

*4 Service Pack 3 or later version is required

Consumables & Accessories

Toner Cartridge	KX-PEP7 (8000 pages at 5%)
Interface Kit	KX-PNB6 (IrDA/RS-232C)
2nd Feeder	KX-PMF2 (500 Sheets)
Interface Card	KX-PNB4 (LocalTalk/RS-232C)
Upgrade SIMM*	KX-PPSU4 (Upgrade to PostScript)

*Upgrade SIMM Contains the PowerPage(R) Level2J Interpreter from Electronics for Imaging, Inc.

Panasonic
 Document Imaging Company
 Visit us at www.panasonic.com/printers

