


# PanaSync/Pro™ P17



- On-Screen Adjustment Menu
- 1,600 x 1,280 Maximum Resolution NI
- TCO '92 / MPR II Certified
- .25mm Dot Pitch
- NEW AGRAS™ Coating
- 48 Hour Swap / 3 Year Limited Warranty

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright © 1997 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e   S p e c   S h e e t

	<p>Panasonic Computer Peripheral Company          Division of Panasonic Communications &amp; Systems Company          Unit of Matsushita Electric Corporation of America          Display Monitors Division          Headquarters 2 Panasonic Way, Secaucus, NJ 07094</p>
--	---

www.panasonic.com/alive

## PanaSync/Pro™ P17 Specifications

CRT Screen Size	17" CRT (16.0"/40.6 cm Viewable Image Size) Flat-Square
Dot Pitch	0.25mm
Surface	NEW AGRAS™ COAT
Viewable Display Area (HxV)	
Factory Preset	11.81" x 8.86", 14.8" diagonal
Full Scan	12.80" x 9.61", 16.0" diagonal (typical)
Input	
Video Signal	RGB analog (0.7 Vp-p, 1.0 Vp-p with sync on green, 75 ohms)
Sync Signal	H/V separate (TTL), H/V Combined, or Sync on Green
H-Sync	30-86kHz
V-Sync	50-160Hz
Modes	1 Factory Preset, 7 Reservations, 13 User Memories
Connector & Cables	
Video Input	One 15-pin Male Mini D-Sub to 15-pin Male Mini D-Sub (4.92'/1.5 meters), 5 Female BNC Connectors
Mac Adapter	Available-Free of Charge
Power	One UL 3-pole (CEE 22 type) (5.91'/1.8 meters)
Controls	
Front Panel	1 (menu) key, Left key, Right key, 2 (select) key, Power Switch (On/Off)
Indicators	LED power indicator Green=On, Yellow=Power-saving mode
On-Screen Menu	Contrast, Brightness, Degauss, Recall (Factory Setting), H Position, H Size, V Position, V Size, V Pincushion, Trapezoid, Parallelogram, Rotation, Color Temperature (9,300K/6,550K/User Color), Display Frequency, Video Level (0.7/1.0 Vp-p), Input Select, H. Moire, V. Moire, Language (German, French, English, Italian & Spanish), Monitor Self-Test (w/no Signal Input)
Video Bandwidth	135MHz (typical)
Resolution (HxV)	1,600 dots x 1,200 lines 69Hz NI FCC Class B, Max. 1,600 dots x 1,280 lines 65Hz NI FCC Class A, Max.
Operating Conditions	
Temperature	32-104°F
Humidity	5%-90% Non-condensing
Dimensions	16.1" (W) x 16.4" (H) x 17.5" (D)
Weight	38.5 lbs
Approvals	UL, CSA, TUV/GS, TUV/ISO9241-3, NORDIC, VCCI 2, DHHS, HWC, PTB, MPR II, FCC Class B, DOC-B, TCO '92, CE, EN-60552, Energy Star/VESA DPMS
Power Consumption	
Supply	90 to 132, 198 to 269V AC (50 or 60Hz), AutoSwitch
On	120 Watts (Typical)
Standby	<15 Watts
Suspend	<15 Watts
Off	<8 Watts
Warranty	3 Years Limited Parts & Labor, 1 Year On-Site Replacement (see your dealer for details)
Other	Windows '95 Plug & Play 24-hour/7-day customer support 48-hour Swap Program