PanaMedia™ PM15

- Built in Dome Sound Speakers
- Built in Microphone
- On-Screen Adjustment Menu
- 1,280 x 1,024 Maximum Resolution NI
- .27mm Dot Pitch
- 48 Hour Swap / 3 Year Limited Warranty

All product/brand names are trademarks or registered trademarks of their respective holders.
Specifications subject to change without notice.
Product may be subject to export control regulations.
Copyright ©1997 Matsushita Electric Corporation of America. All rights reserved.

Online Spec Sheet

Panasonic Computer Peripheral Company
Division of Panasonic Communications & Systems Company
Unit of Matsushita Electric Corporation of America
Display Monitors Division
Headquarters 2 Panasonic Way, Secaucus, NJ 07094

www.panasonic.com/alive

PanaMedia ™ PM15 Specifications

CRT Screen Size	15" CRT (14.0"/35.6 cm Viewable Image Size) Flat-Square
Dot Pitch	0.27mm
Surface	Anti-Static/Silica-Coat
Viewable Display Area (HxV)	
Factory Preset	10.24" x 7.68", 12.8" diagonal
Full Scan	11.20" x 8.40", 14.0" diagonal (typical)
Input	
Video Signal	RGB analog (0.7 Vp-p, 1.0 Vp-p with sync on green, 75 ohms)
Sync Signal	H/V separate (TTL), H/V Combined, or Sync on Green
H-Sync	30-69kHz
V-Sync	50-160Hz
Modes	1 Factory Preset, 7 Reservations, 13 User Memories
Connector & Cables	One 15-pin Male Mini D-Sub on attached cable (4.92'/1.5 meters)
Video Input	Pin Plug (RCA x 2, R & L) to 3.5 mm
Audio Input	Mini plug (Stereo) (4.92'/1.5 meters) 3.5 mm Mini plug (Stereo) to 3.5 mm
Microphone Output	Mini plug (Stereo) (4.92'/1.5 meters)
Mac Adapter	Available-Free of Charge
Power	One UL 3-pole (CEE 22 type) (4.92'/1.5 meters)
Speakers	Freq. response 100Hz to 20 kHz (typical) Audio Output 3W+3W (typical)
Microphone	Freq. response 100 Hz to 10 kHz (typical) Input sensitivity -45 dB
Controls	
Front Panel	Audio mute, Volume+, Volume-, 1 (menu) key, Left key, Right key, 2 (select) key, Power Switch (On/Off)
Indicators	LED power indicator Green=On, Yellow=Power-saving mode, Mute Indicator Yellow=On
On-Screen Menu	Contrast, Brightness, Recall (Factory Setting), H Position, H Size, V Position, V Size, V Pincushion, Trapezoid, Parallelogram, Color Temperature (9,300K /6,550K/User Color), Display Frequency, Video Level (0.7/1.0 Vp-p), Audio Volume
Video Bandwidth	86MHz (typical)
Resolution (HxV)	1,280 dots x 1,024 lines 60Hz NI FCC Class B, Max. 1,280 dots x 1,024 lines 65Hz NI FCC Class A, Max.
Operating Conditions	
Temperatur e	32-95°F
Humidity	5%-90% Non-condensing
Dimensions	14.7" (W) x 15.1" (H) x 16.0" (D)
Weight	33 lbs
Approvals	UL, C-UL=CSA, DHHS, HWC, MPR II, FCC Class B, Energy Star/VESA DPMS
Power Consumption	100 to 240V AC (50 or 60Hz)
Supply	Auto Switch
On	
Standby	<30 Watts
Suspend	<30 Watts
Off	<8 Watts
Warranty	3 Years Limited Parts & Labor, 1 Year On-Site Replacement (see your dealer for details)
Other	Headphone jack, Microphone input & output, Audio input w/connector, Windows '95 Plug & Play 24-hour/7-day customer support 48-hour Swap Program