


# PanaSync™ S110



- On-Screen Adjustment Menu
- 1,600 x 1,200 Maximum Resolution NI
- TCO '92 / MPR II Certified
- .25mm Dot Pitch
- New AGRAS™ Coating
- 48-Hour Swap / 3-Year Limited Warranty

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright © 1997 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e   S p e c   S h e e t

	<p>Panasonic Computer Peripheral Company                  Division of Panasonic Communications &amp; Systems Company                  Unit of Matsushita Electric Corporation of America                  Display Monitors Division                  Headquarters: 2 Panasonic Way, Secaucus, NJ 07094</p>
---	--

www.panasonic.com/alive

## PanaSync™ S110 Specifications

CRT Screen Size	21" CRT (20.0"/50.8cm) Viewable Image Size Flat Square
Dot Pitch	0.25mm
Surface	New AGRAS™ Coat
Viewable Display Area (HxV)	
Factory Preset	15.43" x 11.57", 19.3" diagonal
Full Scan	15.98" x 11.97", 20.0" diagonal (typical)
Input	
Video Signal	RGB analog (0.7 Vp-p, 1.0 Vp-p, with Sync-on-Green, 75 ohms)
Sync Signal	H/V separate (TTL), H/V Combined, or Sync-on-Green
H-Sync	30-95kHz
V-Sync	50-180Hz
Modes	1 Factory Preset, 7 Reservations, 13 User Memories
Connector & Cables	
Video Input	One 15-pin Male Mini D-Sub to 15-pin Male Mini D-Sub (4.92'/1.5 meters), 5 Female BNC Connectors
Mac Adapter	Available-Free of Charge
Power	One UL 3-pole (CEE 22 type) (5.91'/1.8 meters)
Controls	
Front Panel	1 key, Left key, Right key, 2 key, Power Switch (On/Off)
Indicators	LED power indicator Green=On, Yellow=Power-saving mode
On-Screen Menu	Contrast, Brightness, Degauss, Recall (Factory Setting), H. Position, H. Size, V. Position, V. Size, V. Pincushion, Side Pincushion Balance, Trapezoid, Parallelogram, Rotation, Color Temperature (9,300 + 8 MPCD/7500K/6500K/5000K/User Color) Signal (H&V Display Frequency) & Input Port (A: Mini D-Sub or B: 5 BNC), Video Level (0.7/1.0 Vp-p), H. Moiré, V. Moiré, Language (English, German, French, Italian & Spanish), Monitor Self-Test (w/no Signal Input or Signal Outside Range)
Video Bandwidth	202.5MHz (Pixel Clock)
Resolution (HxV)	1,600 dots x 1,200 lines 75Hz NI FCC Class B, Max. & CISPR 22-B Max. 1,600 dots x 1,280 lines 71 Hz NI, FCC Class A Max.*
Operating Conditions	
Temperature	32-104°F
Humidity	5%-90% Non-condensing
Dimensions	19.9" (W) x 19.2" (H) x 20.4" (D)
Weight	60.61 lbs
Approvals	UL, CSA, TUV/EN60950, TUV/IEC950, TUV/GS, NORDIC, DHHS, PTB, VCCI Class B, FCC Class B, IC(DOC) Class B, CISPR 22 Class B, CE, MPR II, TCO'92, VESA DPMS/Energy Star, ISO9241-3/-8
Power Consumption	
Supply	90 to 132, 198 to 264V AC (50 or 60Hz), Automatic
On	160 Watts (Typical)
Standby	<15 Watts
Suspend	<15 Watts
Off	<4 Watts
Warranty	3 Years Limited Parts & Labor, 1 Year On-Site Replacement (see your dealer for details)
Other	Windows '95 Plug & Play 24-hour/7-day customer service 48-hour Swap Program