


# PanaSync™ S15



- On-Screen Adjustment Menu
- 1,280 x 1,024 Maximum Resolution NI
- TCO '92 / MPR II Certified
- .27mm Dot Pitch
- Reduced Glare A/S Silica Coat
- 48 Hour Swap / 3 Year Limited Warranty

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright © 1997 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e   S p e c   S h e e t

	Panasonic Computer Peripheral Company Division of Panasonic Communications & Systems Company Unit of Matsushita Electric Corporation of America Display Monitors Division Headquarters 2 Panasonic Way, Secaucus, NJ 07094
-------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

www.panasonic.com/alive

## PanaSync™ S15 Specifications

CRT Screen Size	15" CRT (13.7" /34.8 cm Viewable Image Size) Flat-Square
Dot Pitch	0.27mm
Surface	Anti-Static/Silica-Coat
Viewable Display Area (HxV)	10.24" x 7.68", 12.8"
Factory Preset	diagonal
Full Scan	10.98" x 8.23" , 13.7" diagonal (typical)
<b>Input</b>	
Video Signal	RGB analog (0,7 Vp-p, 7 ohms)
Sync Signal	H/V separate (TTL)
H-Sync	30-67kHz
V-Sync	50-120Hz
Modes	1 Factory Preset, 7 Reservations, 8 User Memories
<b>Connector &amp; Cables</b>	
Video Input	One 15-pin Male Mini D-Subon attached cable (4.92'/1.5 meters)
Mac Adapter	Available
Power	One UL 3-pole (CEE 22 type) (4.92'/1.5 meters)
<b>Controls</b>	
Front Panel	Power Switch, Contrast, Brightness, Select, Up, Down, Degauss, Power Switch (On/Off)
Indicators	LED power indicator Green=On, Yellow=Power-saving mode H Position H Size V Position V Size
Video Bandwidth	86MHz (Pixel Clock)
Resolution (HxV)	1,280 dots x 1,024 lines 60Hz NI FCC Class B, Max. 1,280 dots x 1,024 lines 63Hz NI FCC Class A, Max.
<b>Operating Conditions</b>	
Temperature	32-95°F
Humidity	5%-90% Non-condensing
Dimensions	14.6" (W) x 15.0" (H) x 16.2" (D)
Weight	29.9 lbs
Approvals	UL, CSA, TUV/GS, TUV/ISO9241-3, NORDIC, UL, C-UL=CSA, DHHS, HWC, MPR II, FCC Class B, EnergyStar/VESA DPMS
<b>Power Consumption</b>	
Supply	100 to 240V AC (50 or 60Hz), Auto Switch
On	90 Watts (Typical)
Standby	<30 Watts
Suspend	<30 Watts
Off	<5 Watts
Warranty	3 Years Limited Parts & Labor, 1 Year On-Site Replacement (see your dealer for details)
Other	Windows '95 Plug & Play, 24-hour/7-day customer service, 48-hour Swap Program