

KXL-RW10A Portable CD-R/RW Drive



This CD-R/RW drive is sure to please users on the go who need an economical storage solution. It connects quickly and easily, so it's ideal for use on the road, at home or in the office- whenever and wherever the need occurs. The ultra-compact KXL-RW10A features 4X write (max) /4X rewrite (max) /20X (max) read times and a 2 MB buffer, and runs under Windows® 95/98 and Windows NT 4.0. Upgrading to Panasonic's portable CD-R/RW drive can provide enhanced productivity and computing flexibility!

Features

- Ultra-Compact, Lightweight Drive
- Easy to set-up, easy to use
- Ideal for Notebook and Desktop PC
- All write modes are supported
- Includes easy to use CD Writing Software
- Includes CardBus and PCMCIA Interface

O n l i n e S p e c S h e e t

Panasonic®

Panasonic Document Imaging Company
Unit of Matsushita Electric Corporation of America
Multimedia Systems Division
Headquarters: 2 Panasonic Way, Secaucus, NJ 07094

www.panasonic.com/office

KXL-RW10A Specifications

Performance

Dimensions (W x H x D)	5.12" x 6.41" x 0.96" (130 x 163 x 24.3 mm)
Weight	12.7 oz. (360 g)
Interface	SCSI-2
SCSI Connector Type	50-pin High-density
Date Transfer Rate ¹	
Reading from Media ²	With Notebook Computer: CardBus Mode: 1350 KB/s (inner: 9X) to 3000 KB/s (outer: 20X) 16 Bit Mode: 1350 KB/s (inner: 9X) to 2700 KB/s (outer: 18X) With Desktop Computer: 1350 KB/s (inner: 9X) to 3000 KB/s (outer: 20X)
Writing to Media	150 KB/s (inner/outer: Normal Speed) 300 KB/s (inner/outer: 2X) 600 KB/s (inner/outer: 4X)
Access Time	150 ms typical at 1/3 stroke
Buffer Size	2 MB
Compatible Media	
Read Only	CD-DA (audio CD), VIDEO CD ³ , CD-i (movie), CD-ROM (Mode 1, Mode 2 Form 1), CD-ROM XA (Mode 2 Form 2), Photo CD ⁴ (multisession), CD Extra
Read/Write	CD-R, CD-RW
Writing Methods	Track at once, Disc at once, Session at once, Packet writing, Multisession
Error Rates	
Soft Read Errors	Less than 10 ⁻⁹
Hard Read Errors	Less than 10 ⁻¹²
Audio Performance	
Phones Out (stereo)	More than 80 dB (A Range)
Maximum Output Level	14 mW (EIAJ) (impedance 32 Ω)
Power Requirements	AC Adapter
Input	100-240VAC, 50/60 Hz
Output	DC CV 1A
Power Consumption	Drive: IIW, PC Card: OSW
Operating Environment	
Temperature	41°F - 95°F (5°C - 35°C)
Humidity	20% to 85% RH
Storage Environment	
Temperature	-4°F - 131°F (-20°C - 55°C)
Humidity	15% to 85% RH
Interface Card and Cable	
Power Source	(16 bit mode) DC 5 V, approx. 150 mA (cardbus mode) DC 3.3 V approx. 50 mA
Card Type	PCMCIA Type II
Card Dimensions	2.13" x 3.37" x 0.20" 54 x 85.6 x 5 mm
SCSI Connector	Half-pitch 50-pin (pin type)
Cable Length	Approx. 400 mm (without connector)
Data Transfer Rate	10 MB/s (MAX.)
Mass (Weight)	Approx. 180 g (6.35 oz.) (included the cable)
Warranty	2 Year Limited Parts & Labor: Mail-in Exchange (see dealer for details)
Technical Support	1-800-PANASYS (1-800-726-2797) www.panasonic.com/office/techsupport.html

¹ Performance may vary based on computer specifications.

² 10X is the maximum reading transfer rate to read from a media.

³ VIDEO CD or CD-i titles can only be viewed if the computer has software or hardware MPEG decoding capability.

⁴ Software required for viewing Photo CD titles is not included.