

KX-P4440 Laser Printer



Announcing the Panasonic® KX-P4440 laser printer with the features you need for the demanding business environment. The KX-P4440 offers a print speed of 10 pages per minute using Intel's 960 RISC microprocessor HP Laser Jet III emulation with Panasonic SatinPrint™ Technology for edge smoothing and 1MB of RAM standard, expandable to 5MB. The KX-P4440 has 8 outline fonts, 14 internal bitmapped fonts, a font card slot for optional font cards and is compatible with all HP Laser Jet downloadable bitmap fonts for a wide range of choices. And, for the user who requires multiple font styles in a document, font cards can be read into the KX-P4440's memory, while the most frequently used font card remains in the font card slots for rapid access time. The KX-P4440 has two 200 sheet input cassettes (top cassette with manual feed) for paper input flexibility and a 150 sheet face down output. All of this comes backed by a 1-year limited warranty (see your dealer for details) from Panasonic, a name you can trust.

All product/brand names are trademarks or registered trademarks of their respective holders. Specifications subject to change without notice. Product may be subject to export control regulations. Copyright ©1999 Matsushita Electric Corporation of America. All rights reserved.

O n l i n e S p e c S h e e t

Panasonic®	Panasonic Digital Imaging Company Unit of Matsushita Electric Corporation of America Computer Peripherals Division Headquarters: 2 Panasonic Way, Secaucus, NJ 07094
-------------------	---

w w w . p a n a s o n i c . c o m / o f f i c e

KX-P4440 Specifications

Printing Process	Electrophotographic semi-conductor laser
Speed	10 ppm using an Intel 960 RISC microprocessor (letter size, text mode, all originals, 5.5% image area)
Compatibility	HP LaserJet Series III, IBM Proprinter II, Diablo 630
Resolution	300 x 300 dpi
Paper Input	Two 200-sheet (using 20 lb. bond) multi-purpose cassettes (envelope, letter, legal) top cassette with manual feed
Paper Output	150 sheets face down for collated output 20 sheets face up for heavier weight paper
RAM	1MB Standard, 5MB maximum
Interfaces	Centronics parallel and RS-232C serial standard
Bitmap Fonts	Courier 10, 12, 15, and 17 upright and italic Courier 10 and 12 bold Courier 20 upright Century PS 10 upright, italic and bold <small>Note: all fonts are available in portrait and landscape orientation</small>
Scalable Fonts	CG Times upright medium CG Times upright bold CG Times italic medium CG Times bold italic Univers upright medium Univers upright bold Univers italic medium Univers bold italic
Font Card Slots	1 (located on the left side of the printer)
Duty Cycle/Life	5,000 pages per month/300,000 pages total
Warranty	Limited 1 year parts and labor
Dimensions	14.6" (W) x 16.7" (D) x 11.2" (H)
Weight	35.5 lbs.
Environmental Conditions	Operating temperature: 50-90.5°F (10-32.5°C) Storage temperature 32-95°F (0-35°C) Humidity: 20-80% relative humidity (non-condensing)
Approvals	UL and FCC class B approved