

Panasonic®

- Please read the Installation Instructions carefully before installing the unit, and the Operating Instructions before using it.
- Specifications are subject to change without prior notice.
- The contents of this catalogue are accurate as of September 2021.
- Due to printing considerations, actual colours may vary slightly from those shown.
- All graphics are provided solely for the purpose of illustrating a point.



Do not add or replace refrigerant other than the specified type. Manufacturer is not responsible for damage or deterioration in safety due to usage of other refrigerant.

Authorised Dealer



TRUNG TÂM HỖ TRỢ KHÁCH HÀNG - TƯ VẤN MIỄN PHÍ CÁC DỊCH VỤ

Hỗ Trợ Trước và Sau Mua Hàng • Tư Vấn, Hướng Dẫn Sử Dụng Sản Phẩm • Giải Quyết Các Thắc Mắc, Khiếu Nại của Khách Hàng hoặc (024) 3767 7360

Từ 8h15 - 17h30 Thứ 2 đến Chủ Nhật

www.panasonic.com/vn

www.facebook.com/PanasonicVietnam



Panasonic Heating & Cooling Solutions

Global site : aircon.panasonic.com

PRO Club : panasonicproclub.global

Panasonic HVAC Global

AC-VN-C-21

RESIDENTIAL AIR CONDITIONERS (FOR WS/ACS/KKE) 2021/2022

WAKE UP REFRESHED




AWAY FROM HOME




PRECIOUS NIGHT SLEEP



FAMILY EVENING MOMENTS



AERO ELITE INVERTER



PREMIUM INVERTER



QUALITY AIR FOR LIFE

A Better Life, A Better World

QUALITY AIR FOR LIFE



Quality air has been a prime concern of many in today's world. While we spend most of our time indoors, we often take the perception that indoor air is cleaner than the outside air.

Panasonic is committed to advance frontiers through air quality improvement with "Quality Air For Life" initiatives and bring a great range of air solutions to mitigate indoor air concerns. Quality Air For Life solutions aim to deliver comfortable, clean air and clean energy solutions through four different enabling technologies: Air Purification, Air Conditioning, Air Connectivity and Air Ventilation.

Quality Air Solutions at Home

Panasonic offers a wide range of air conditioning solutions to purify and cool indoor spaces for comfort with energy efficiency for a lesser environmental impact. Connect with the Panasonic Comfort Cloud App that keeps you in touch with your home air conditioner remotely while you're away from home.



AIR PURIFICATION
Purifies air and surfaces 24 hours a day



AIR CONNECTIVITY
Stay connected and in control anywhere, anytime



AIR CONDITIONING
Comfortable cool air for you and your family



AIR EFFICIENCY
Eco-friendly and cost saving technologies for a sustainable living

SPECIFICATIONS OF ELITE INVERTER	34	SPECIFICATIONS OF AERO ELITE INVERTER	36
SPECIFICATIONS OF PREMIUM INVERTER	38	SPECIFICATIONS OF STANDARD INVERTER WITH WI-FI	40
SPECIFICATIONS OF STANDARD INVERTER WITH nanoe™ X	42	SPECIFICATIONS OF STANDARD NON-INVERTER	44
SPECIFICATIONS OF PREMIUM INVERTER HEAT PUMP	46	SPECIFICATIONS OF STANDARD INVERTER HEAT PUMP	48
TOTAL QUALITY AIR SOLUTIONS	50	COMPLETE AIR MANAGEMENT SYSTEM	52
nanoe™ WORLD	54	TECHNICAL EXPLANATION	56
FEATURES COMPARISON & EXPLANATION	66	MODEL LINE-UP	68




24-HOUR PROTECTION

with nanoe™ X + Comfort Cloud

Your health starts with you at home from the outside world. nanoe™ X with hydroxyl radicals contained in water helps families to ensure constantly clean and safe indoor environments by inhibiting bacteria, viruses, mould and other pollutants while deodorising for clean and fresh air.

Choose Panasonic air conditioners equipped with nanoe™ X and stay connected by downloading the Panasonic Comfort Cloud App* to manage your air conditioners with one device.



Comfort Cloud App
(Air Connectivity)



*A router with Internet connection is required to connect your air conditioner with the Panasonic Comfort Cloud App. The C2-TACG1 accessory is required for ELITE INVERTER, PREMIUM INVERTER, STANDARD INVERTER with nanoe™ X and STANDARD INVERTER HEAT PUMP models. Built-in Wi-Fi is only available for AERO ELITE INVERTER, STANDARD INVERTER with Wi-Fi and PREMIUM INVERTER HEAT PUMP models.

Stay Safe Indoors with 24-Hour nanoe™ X Air Protection¹

nanoe™ X technology with the benefits of hydroxyl radicals can effectively inhibit adhered and airborne pollutants, and reduce odours. You can switch ON nanoe™ X mode with the air conditioning operation ON or OFF to actively clean your air when you are at home or operate independently when you are away from home.

nanoe™ X mode operates on low energy consumption and requires no maintenance – thanks to the titanium-made nanoe™ X device. nanoe™ X keeps you and your family safe indoors with 24-hour active air protection.



Switch nanoe™ X mode ON to inhibit pollutants and deodorise while you're away.

Provides a cleaner and comfortable space for you and your loved ones.

*Energy consumption may vary depending on models.

Smartify Your Air Conditioner Anytime, Anywhere

Take control of single or multiple air conditioning units wherever you are. Purify your home with the Panasonic Comfort Cloud App on your mobile device on-the-move.



Switch on nanoe™ X mode without cooling while away from home.

Convenience to monitor and manage the air conditioners with one mobile device.

¹The nanoe™ X mode can be run independently from cooling mode, and needs to be ON for the 24-hour air purification to function.


Activate nanoe™ X All Day Long

Making your home a safe place to be. nanoe™ X works at all hours of the day to bring you pleasant mornings and comfortable nights. Giving you a peace of mind, in the comfort of your own home.



MORNING

WAKE UP REFRESHED



Kick start the day at breakfast with quality air that refreshes and energises your morning.


Odours

Allergens

Bacteria & Viruses

NOON

AWAY FROM HOME



Control your home air conditioner remotely, with the Panasonic Comfort Cloud app to inhibit pollutants indoors, even when you are away from home.


Bacteria & Viruses

Hazardous Substances

Mould

EVENING

FAMILY EVENING MOMENTS



Return home to cooling and refreshing air as the air conditioner cools your home and nanoe™ X inhibits pollutants at the same time.


Odours

Pollen

Bacteria & Viruses

NIGHT


PRECIOUS NIGHT SLEEP




Enjoy a good night's sleep while nanoe™ X keeps your air clean and safe throughout the night. nanoe™ X also helps to moisturise skin and hair for a refreshing morning the next day.

Moisturise Hair & Skin

Bacteria & Viruses






nanoe™ X, Technology with the Benefits of Hydroxyl Radicals

Known as nature's detergent, hydroxyl radicals (also known as OH radicals) are natural reactive molecules looking to react with other elements such as hydrogen. This reaction enables hydroxyl radicals to inhibit the growth of pollutants.


Panasonic's nanoe™ X technology brings these benefits to the comfort of your home to purify surfaces, soft furnishings and the indoor environment for a pleasant and comfortable living space.

How the nanoe™ X device generates hydroxyl radicals contained in water?



Uniqueness of nanoe™ X

Huge Quantity



nanoe™ X produces 9.6 trillion hydroxyl radicals per second*. Large amounts of hydroxyl radicals contained in nanoe™ X lead to outstanding effects in inhibiting pollutants.

*nanoe X Generator Mark 2 generates 9.6 trillion hydroxyl radicals per second, nanoe X Generator Mark 1 generates 4.8 trillion hydroxyl radicals per second.

Longer Lifespan



nanoe™ X technology creates hydroxyl radicals contained in water, enhancing their lifespan from less than a second to more than 600 seconds (10 mins) to spread across long distances.

Fills Space Actively




nanoe™ X actively fills the entire room and goes beyond the filter to inhibit adhered and airborne pollutants.

Maintenance-Free



No maintenance, no replacement required. nanoe™ X is a filter-free solution using a titanium-made atomised electrode that does not require maintenance.

Effective on Fabrics and Surfaces



Sized smaller than a steam droplet, nanoe™ X penetrates deeply into cloth fabrics to inhibit and deodorise effectively.

Safe to Use



The safety of nanoe™ X has been tested in labs and institutions.

Visit our website for a list of safety data:
www.panasonic.com/global/consumer/clean/hydroxyl/technology.html




Asthma and Allergy Friendly



nanoe™ X is approved by Sensitive Choice, which helps consumers worldwide live better with asthma and allergies.

Sensitive Choice is a community service program that aims to educate people about the importance of managing their asthma and allergies. Developed by the National Asthma Council Australia in 2006, the program also encourages companies to produce products and services that are more asthma and allergy aware.

Panasonic and Sensitive Choice have partnered to introduce the nanoe™ X to the Asian market. Purifying your air 24 hours, the nanoe™ X feature can function independently or concurrently with your air conditioner. This market leading Air Sterilisation technology works towards the inhibition of bacteria, viruses, allergens, pollens and mould within your indoor environment, whilst deodorising, keeping your home or office fresh and clean. Panasonic & Sensitive Choice are committed to bring you Quality Air, for Life.




*Virus Lifespan: <https://www.businessinsider.com/coronavirus-lifespan-on-surfaces-graphic-2020-3>

Effective in Inhibiting Novel Coronavirus

COVID-19 pandemic triggered by the Novel Coronavirus (SARS-CoV-2) has brought social distancing and constant sanitisation as the new normal in our daily lives. nanoe™ X enables you to engage in more proactive activities through active purification to inhibit coronavirus around the clock.

Inhibiting SARS-CoV-2 with nanoe™ X

nanoe™ X with hydroxyl radicals contained in water denatures the envelope's lipids and protein of viruses and inhibits it.




The Power of nanoe™ X

Featuring a long lasting lifespan and huge amounts of hydroxyl radicals contained in water, nanoe™ X has the ability to travel for widespread coverage, especially in large spaces of 54m³ to inhibit airborne and surface pollutants throughout the area.

nanoe™ X Concentration Simulation

nanoe™ X concentration has been simulated in a 54m³ (4m x 5m x 2.7m) room to fill for a duration of 30 mins. The bluer the colour, the higher the nanoe™ X concentration.



*Photograph is for illustrative purposes.



Overview


The objective of this test was to determine if nanoe™ X inhibits the activity of the SARS-CoV-2 virus. Gauze saturated with SARS-CoV-2 virus solution was exposed to a generator of nanoe™ X from a distance of 15cm in a 45L box for 2 hours. Over 99.99% of the activity of the SARS-CoV-2 virus was inhibited.

Details

- (1) Testing organisation: TEXCELL (France)
- (2) Test subject: novel coronavirus (SARS-CoV-2)
- (3) Test volume: 45L enclosed box (400 mm x 350 mm x 350 mm)
- (4) Exposure time: 2 hours
- (5) Exposure distance: 15cm

Test of a generator of nanoe™ X

Test results: SARS-CoV-2



Notes: [1] The virus infectious titer was measured and used to calculate the inhibition rate. [2] This verification was designed to generate basic research data on the effects of nanoe™ X on the novel coronavirus in laboratory conditions. It was not designed to evaluate product performance.



Overview


The objective of this test was to determine if nanoe™ X inhibits the activity of the SARS-CoV-2 virus. Gauze saturated with SARS-CoV-2 virus solution was exposed to an air conditioner with nanoe™ X from a distance of 0.7 m in a 6.7 m³ room for 8 hours. Over 91% of the activity of the SARS-CoV-2 virus was inhibited.

Details

- (1) Testing organisation: Texcell (France)
- (2) Test subject: novel coronavirus (SARS-CoV-2)
- (3) Test volume: 6.7 m³ room (1.7 m x 1.8 m x 2.2 m)
- (4) Exposure time: 8 hours

Test of an air conditioner with nanoe™ X

Test results: SARS-CoV-2



Notes: [1] The virus infectious titer was measured and used to calculate the inhibition rate. [2] This verification was designed to generate basic research data on the effects of nanoe™ X on the novel coronavirus in laboratory conditions. Actual effects will vary depending on the environment and usage of the product.



The Development of nanoe™ X Generators

Enhancing the effectiveness of hydroxyl radicals contained in water through every new and improved nanoe™ X generator.




Generator	Mark 1	Mark 2 NEW
	4.8 trillion hydroxyl radicals/sec	9.6 trillion hydroxyl radicals/sec
Ion particle structure		




7 Effects of nanoe™ X

nanoe™ X technology effectively inhibits 5 types of pollutants, deodorises and moisturises with the benefits of hydroxyl radicals contained in water.




Deodorises Various Types of Odours


nanoe™ X reduces strong, adhesive odours¹ by deeply penetrating into fabrics, resulting in lasting freshness in your living space.




How nanoe™ X Reduces Odour



nanoe™ X reaches odour in fabric




Hydroxyl radicals break down odour-causing substances




Odour is eliminated

Inhibits 5 Types of Pollutants


nanoe™ X inhibits airborne and adhered pollutants², providing better air quality for your loved ones.



How nanoe™ X Inhibits Pollutants



nanoe™ X reaches pollutants in fabrics



Hydroxyl radicals take hydrogen away from pollutants



Hydroxyl radicals transform hydrogen to inhibit the activity of pollutants


¹Please refer to page 55 ²Please refer to page 56



Moisturises Skin and Hair

nanoe™ X water particles help to achieve proper moisture balance, resulting in smooth, hydrated skin and hair³.

Without nanoe™ X




Without nanoe™ X




How nanoe™ X works

Maintain skin moisture




[Initially] nanoe™ X combines with natural sebum to coat the skin.



[28 days later] Leads to smooth, well hydrated skin.

Maintain straighter, smoother hair



³Please refer to page 61

nanoe-G


Effective in removing 99% of dust particles⁴, nanoe-G releases negative ions to capture dust particles sized as small as PM2.5, carrying them back to the filter to provide a clean and pristine living space.

Dust Removal (PM2.5)




What is PM2.5?


PM or "Particulate Matter" comprises of tiny particles and liquid droplets. Measuring less than 2.5 micrometers (PM2.5), these particles pose health risks as they can enter our lungs easily. PM2.5 can be found airborne, including dust, dirt, smog and water droplets.




How nanoe-G works



nanoe-G ion generator releases negative ions.



Negative ions attach to dust particles.



These particles are being carried back and trapped at the filter.

⁴Please refer to page 63



Manage at Ease Using Panasonic Comfort Cloud App

Bringing simplicity and convenience to your fingertips, Panasonic Comfort Cloud application gives you complete control of your air conditioning units anytime, anywhere.

The Panasonic Comfort Cloud application enables your mobile device to act as a remote controller, synchronising with your air conditioner in a matter of seconds. Perfect for multiple air conditioning units in single and multiple locations.

AIR CONDITIONER WITH BUILT-IN Wi-Fi

XU/XZ SERIES

WPU SERIES

AIR CONDITIONER WITH OPTIONAL NETWORK ADAPTOR

VU/U/XPU/YZ SERIES

NEW 2021



Easy connectivity to Panasonic Comfort Cloud and removes the need to purchase and install optional network adaptor

Optional network adaptor is required

Smartify Your Air

Applicable for Residential Properties and Premises


SMART CONTROL

Control Multiple Air Conditioners in Single/Multiple Locations

Managing Air Conditioners in Single Location



Managing Air Conditioners in Multiple Locations




Monitor and control single and multiple air conditioners at one or more locations simultaneously anytime, anywhere with the Panasonic Comfort Cloud App. Switch ON or OFF all air conditioners at a single location also available at your convenience.

SMART COMFORT

Turn ON nanoe™ Mode

Switch on nanoe™ mode with cooling OFF



Switch on nanoe™ mode with cooling ON



Switching Air Conditioner Mode



Activate iAUTO-X to enjoy rapid cooling on a hot day.

Adjust Fan Speed And Air Swing



Enjoy comfortable cooling by adjusting the fan speed, air swing (up & down) or (left & right).

*Functions availability may vary depending on models.

SMART EFFICIENCY

Set Timer



Schedule nanoe™ X with cooling ON or OFF and pre-cool your house for you to enjoy clean air and comfortable cooling.

Track Energy Consumption



View energy consumption of individual units by comparing the usage patterns daily/weekly/monthly/yearly.


SMART ASSIST

Error Notifications



Identify errors by checking error notifications to inform your technician to repair your air conditioner quickly.

User Assignment & Management



Assign user profiles to control or view selected air conditioning units.

Panasonic Comfort Cloud App

Main Function Overview

Main Device Screen

- Indoor Air Temperature
- Outdoor Ambient Temperature
- Set Temperature
- Switch Between Devices
- ON/OFF Air Conditioner
- Fan Speed Adjustment
- ECO + A.I. Mode
- Operation Mode
- Setting Temperature Change
- Air Swing Adjustment
- Basic Features

- 1 Group Status**
- 2 Main Menu**
- 3 Notification**
- 4 ON/OFF nanoe & ECO**
- 5 Statistics**
- 6 Weekly Timer**

Requirements for Connecting with Panasonic Comfort Cloud App

Indoor Unit-Network
Air Conditioner equipped with built-in Wi-Fi /CZ-TACG1 optional network adaptor connected to port CN-CNT¹

Other Hardware Requirements*
Router - Internet - Smartphone
(Required 2.4GHz transmission channel)

*Purchase and subscribe separately

Compatible Device and Browsers

- iOS 9.0 or above
- Android™ 5.0 Lollipop or later

Download Free App


¹For AC models (ELITE INVERTER, PREMIUM INVERTER, STANDARD INVERTER with nanoe™ X and STANDARD INVERTER HEAT PUMP), you need accessory CZ-TACG1 connected to port CN-CNT. Built-in Wi-Fi is only available for AERO ELITE INVERTER, STANDARD INVERTER with Wi-Fi and PREMIUM INVERTER HEAT PUMP models.

*Screen capture based on current Comfort Cloud app version 1.11.0



How Humidity Control Works

The new iAUTO-X with the Humidity Sensor constantly monitors and adjusts relative humidity to below 60% according to different environments with the set temperature that ensures a balanced cooling sensation throughout by reducing heat for optimal cooling.



* Comparison of iAUTO-X Mode & normal COOL mode by using 1.5HP AERO ELITE INVERTER Model

iAUTO-X Mode:
 iAUTO-X Mode, Outside temperature : 35°C/24°C
 Remote setting temperature : 25°C, with Fan Speed: Auto
 Horizontal Airflow direction : Auto
 Vertical Airflow direction : Straight

Normal Cool Mode:
 Cool Mode, Outside temperature : 35°C/24°C
 Remote setting temperature : 25°C, with Fan Speed: High
 Horizontal Airflow direction : Middle
 Vertical Airflow direction : Straight

Average Room RH is measured every 1 hour up to 4th hour (under stable condition).
 At Panasonic Amenity Room [size:16.6m²]
 The effect differs according to conditions in installation and usage.



Without the humidity sensor, relative humidity increases in the room during stable operation causing uncomfortable sleeping environments.



The humidity sensor automatically controls relative humidity below 60% to remain stable and comfortable during bedtime.


Problems Caused by High Humidity

A high relative humidity even with a low temperature may increase the risk of heat stroke. Causing discomfort and irregular sleep cycles.



Humidity Sensor Optimises An Ideal Sleeping Environment¹


Panasonic's new iAUTO-X with the Humidity Sensor constantly monitors and adjusts relative humidity levels to below 60% for an optimal sleeping environment, so you can enjoy better sleep with comfortable cooling.




Balancing Temperature and Humidity for Comfort

With lower humidity at the same temperature, the room will feel more comfortable and cooler compared to higher humidity.

Comfort Zone Based on Temperature vs Humidity



At set temperature of 25°C, the room feels uncomfortable in high humidity.



Comfort zone defined by ASHRAE STANDARD.
 *ANSI/ASHRAE Standard 55-2010




At set temperature of 25°C, the room feels more comfortable when the relative humidity is below 60%.

*Applicable to AERO ELITE INVERTER, PREMIUM INVERTER and PREMIUM INVERTER HEAT PUMP.



15 Meters Long Air Distance with The Improved New AEROWINGS¹

Evolving to provide fast and cooling comfort, the New AEROWINGS incorporates two independently controlled flaps to cool the room in the shortest time possible with a bigger cross flow fan (105mm) and flap (103mm), improving the ability to lift air speed efficiently.



Bigger cross flow fan (105mm)

The new AEROWINGS provides longer airflow up to 15 meters with increased airflow by 10% and air speed by 20%².

1 2 Independent Motors
Control the Sub-Flap and Bigger Outer Flap separately.

2 Sub-Flap
Compresses and concentrates cool air.

3 Bigger Outer Flap (103mm)
Helps to deliver airflow further.

¹Applicable to AERO ELITE INVERTER, PREMIUM INVERTER and PREMIUM INVERTER HEAT PUMP. ²Compared to previous PREMIUM model (1.5HP)

NEW AEROWINGS



Shower Cooling

Shower airflow spreads fast, cool and concentrated air across room and to the wall, then showers down gently.





Fast Cooling

AEROWINGS twin flaps direct concentrated airflow downwards to cool you rapidly.

Shower Cooling Airflow Assessment

New AEROWINGS

Previous AEROWINGS




cooler ← warmer

The New AEROWINGS provides stronger and cooler air further up to 15 meters and directs airflow more upwards towards the ceiling to avoid direct and over cooling.

Fast Cooling Airflow Assessment

New AEROWINGS

Previous AEROWINGS



cooler ← warmer

The New AEROWINGS directs concentrated airflow downwards for instant cooling. The room is cooled faster with stronger and cooler air.

Efficient Airflow with Location Information Setting¹

Store and set the location of your installed air conditioner unit using the remote controller. Based on location information, airflow will be automatically optimised, sending airflow to the centre of the room. This gives more flexible installation options and efficient cooling enjoyment to its full potential with location information setting.

With location information

Air flows at the centre to cool evenly.



Without location information

Air flows unevenly, reducing cooling efficiency.





¹Applicable to AERO ELITE INVERTER, PREMIUM INVERTER and PREMIUM INVERTER HEAT PUMP.



Faster Cooling with iAUTO-X¹

iAUTO-X provides strong faster cooling through the use of Panasonic Thermal Enhancement Technology (P-TECH) enabling the compressor to achieve maximum frequency quickly from start-up. With the new iAUTO-X function, you can reactivate iAUTO-X for faster cooling even after reaching stable temperatures.



Concentrated airflow cools instantly. Room is evenly cooled.

Cool air blows downwards and cools the room at a slow pace, resulting in uneven cooling.

25%*
COOLER
FASTER

* Comparison of iAUTO-X Mode & normal COOL mode by using 1.5HP AERO ELITE INVERTER Model

iAUTO-X Mode:
iAUTO-X Mode, Outside temperature : 35°C/24°C
Remote setting temperature : 25°C, with Fan Speed: Auto
Horizontal Airflow direction : Auto
Vertical Airflow direction : Straight


Normal Mode:
Cool Mode, Outside temperature : 35°C/24°C
Remote setting temperature : 25°C, with Fan Speed: High
Horizontal Airflow direction : Middle
Vertical Airflow direction : Straight

Total time needed to cool down the room from 35°C to 29°C is measured.
At Panasonic Amenity Room (size:16.6m²)
The effect differs according to conditions in installation and usage.

Uniqueness of iAUTO-X¹

Automatic Fan Speed

iAUTO-X automatically switches fan speed to medium fan speed, high fan speed and super high fan speed depending on the temperature difference between the room and set temperature.



Flap Movement




After reaching the set temperature, the flap moves upwards automatically to perform shower cooling for an even cooling sensation at the set temperature avoiding direct cooling towards the body.



Reactivate iAUTO-X



Reactivate faster cooling with a second press of the iAUTO-X button!



¹Applicable to AERO ELITE INVERTER, PREMIUM INVERTER and PREMIUM INVERTER HEAT PUMP.



Better Living, Together with Eco-Friendly Technologies

Panasonic's Air Efficiency provides a sustainable living environment with technologies that reduce carbon emissions into the Earth's atmosphere while saving costs on the use of electricity, providing an eco-friendly solution for you and the environment.

Enjoy intelligent cooling with eco-friendly features such as reduced power usage, adjusted cooling power and efficient energy usage for better savings and energy consumption that's good for both you and the environment, altogether.





Powerful Performance with Efficiency

Panasonic's Inverter reduces power consumption by varying the speed of the compressor according to the temperature changes with the aim of minimising the temperature fluctuations so you can enjoy consistent cooling comfort.

Quick Cooling and Constant Comfort

PAM (Pulse Amplitude Modulation) increases the power output to accelerate compressor speed at start up for quick cooling and PWM (Pulse Width Modulated Wave) stabilises the set temperature without wasting energy, offering constant comfort.



Benefits of Panasonic Inverter Technology

The energy-saving abilities of Inverters provide a host of benefits for your comfort, including fast cooling upon start-up, constantly maintaining a set temperature, a wider power output range and reduced noise levels.




Reasons to Choose Panasonic Inverter Air-Conditioner



Save on Your Electricity Bill
Panasonic inverter air conditioner prevents overcooling or overheating regardless of room size or condition.



Stay Cool Throughout the Day
A wide power output range for inverter air conditioner models provides a balanced comfort regardless of temperature fluctuations caused by the occupancy level or heat-generating appliances.



Cut Down on Waiting Time
With powerful and quick start-up, you no longer have to wait to experience refreshing comfort.

CSPF

Cooling Seasonal Performance Factor

Panasonic Air Conditioners not only achieved high EER for rated operations, but also have a high Cooling Seasonal Performance Factor - a more realistic energy efficiency measurement based on customer's actual environment of use over an entire year.

Calculating CSPF

$$CSPF = \frac{CSTL}{CSEC}$$

Cooling Seasonal Total Load (CSTL)

Total amount of heat that is removed from the indoor air when equipment is operated for cooling the building during the cooling season.

Cooling Seasonal Energy Consumption (CSEC)

Total amount of energy consumed by the equipment when it is operated for cooling during the cooling season.



The Advantages of Seasonal Efficiency VS Rated Efficiency

Factor	Nominal	CSPF
Temperature	One point of temperature conditions, e.g. outdoor temperature 35°C for cooling. In reality, outdoor temperature continuously changes.	Adopts several rating temperatures for cooling, reflecting actual performance over an entire cooling season.
Cooling Capacity	Calculates based on full capacity. Hence, it is difficult to justify the benefits of INVERTER technology.	Integrates operations at partial load instead of full capacity. Benefits of INVERTER can be easily identified.

R32 REFRIGERANT

An Environmental-Friendly Refrigerant

R32 refrigerant is an excellent heat transfer medium which leads to greater energy and cost-effectiveness. It also has low global warming potential, hence it's friendlier to the environment.

- HIGHER COOLING CAPACITY** R32 has **higher cooling capacity** thereby increases heat transfer efficiency.
- REDUCE ENERGY COSTS** It consumes **less energy**, helping you to save on electricity costs.
- ECO FRIENDLY** R32 has **zero impact** on the ozone layer, therefore it's environmental friendly.

Refrigerant Properties of R32, R410A and R22

	R32	R410A	R22
Composition	Single Component	2 Components	Single Component
Chemical Formula	CH ₂ F ₂	CH ₂ F ₂ / CHF ₂ CF ₃	CHClF ₂
Boiling Point (°C)	-51.7	-51.5	-40.8
Ozone Depletion Potential (ODP)	0	0	0.055
Global Warming Potential (GWP)	675	2090	1810
Pressure	1.6 x	1.6 x	1x
Refrigerant Oil	Synthetic Oil (FW50S)	Synthetic Oil (FV50S)	Mineral Oil
Toxicity	None	None	None
Flammability	A2L Mildly flammable	A1 Non-flammable	A1 Non-flammable



Intelligently Balances Energy Savings and Comfort

As each room in your home is different, ECO Mode with Artificial Intelligence (A.I.) Control efficiently cools your room based on the amount of heat load and air conditioning capacity. It finds the perfect ECO balance between power consumption and time taken to reach the desired temperature to maintain your comfort with minimal energy waste.

ECO Mode with A.I. Control will automatically learn and judge what is the optimal ECO level based on:

- Room condition**
- Heat Source can be due to:**
 - (A) Sunlight and lighting in the room
 - (B) Computers and appliances
 - (C) Body heat

When Your Air Conditioner is Switched On



Daytime with sunlight



Night time with cool breeze

- Requires Fast Cooling ECO Mode with A.I. prioritises on maximising cooling comfort while saving energy through ECO Mode.
- Does not require Fast Cooling ECO Mode with A.I. prioritises on maximising energy savings over cooling comfort.

After Reaching Set Temperature



- Consistent comfort day or night
- Saves energy after reaching set temperature
- ECO Mode with A.I. continues to save energy and automatically adjusts room temperature for consistent cooling comfort

How to switch on ECO Mode with A.I. Control

- Press **ECO** to switch ON ECO mode.
- Press **ECO** second time to cancel/switch OFF ECO mode.



UP TO 20%* ENERGY SAVING ECO+A.I.

*Comparison of ECO Mode & normal mode by using 1.5HP Inverter Model

ECO Mode:
ECO Mode, Outside temperature : 35°C/24°C
Remote setting temperature : 25°C, with Fan Speed: High,
Horizontal Airflow direction : Middle
Vertical Airflow direction : Straight

Normal Mode:
Normal Mode, Outside temperature : 35°C/24°C
Remote setting temperature : 25°C, with Fan Speed: High,
Horizontal Airflow direction : Middle
Vertical Airflow direction : Straight

Total power consumption amount is measured for 1 hour under stable operation. At Panasonic Amenity Room (size : 13.3m²)
The effect differs according to conditions in installation and usage

* Applicable for models with ECO+A.I. function only.



Fits Perfectly Anywhere

Panasonic air conditioners are designed to be compact in size, minimalist with matt finishing, enabling them to be easily fitted and seamlessly harmonized with any interior. Its uniquely designed structure enhances durability, yet conveniently eases installation and maintenance routines.

The Good Design Award 2020 has recognised its achievement of balancing product design and function for the benefit of the global community¹.



¹ The Good Design Award 2020 applicable to STANDARD INVERTER with Wi-Fi (1.0HP- 2.0HP), STANDARD INVERTER with nanoe™ X (1.0HP-2.0HP), STANDARD NON-INVERTER R32 (1.0HP-1.5HP) and STANDARD INVERTER HEAT PUMP (1.0HP-1.5HP).

Easy Breezy Installation & Servicing


EASY REMOVAL



Easy to lock & unlock the front grille.

Makes installation & servicing easier when dismantling or assembling.

Simple steps for circuit board (PCB) removal



Remove control board cover.

Disconnect all the connectors.

Pull out main PCB, screw-free design makes it easy to remove PCB.

EASY ACCESS




Built-in support holder makes it easy to securely hold the indoor unit against the wall.

180mm bigger piping space improves work efficiency during installation and servicing.

More open working spaces provide easy view and unobstructed access to setup drain hose and piping.

Single wire insert tunnel with wider opening provides front visibility plus easy wire insertion and connection.

NEAT INSTALLATION



Stronger & more solid installation plate which provides more stability to better support indoor units.

Ensures indoor units fit well on the wall without any gaps.

WALL-MOUNTED ELITE *INVERTER* Single-Split Type



CS-VU9UKH-8 | CS-VU12UKH-8 | CS-VU18UKH-8



Wireless (Standard)



Wired CZ-RD514C (Optional)




Network Adaptor CZ-TACG1 (Optional)



MODEL	INDOOR UNIT (50Hz)		CS-VU9UKH-8	CS-VU12UKH-8	CS-VU18UKH-8
	OUTDOOR UNIT		CU-VU9UKH-8	CU-VU12UKH-8	CU-VU18UKH-8
Cooling Capacity	[min-max]	kW	2.50 [0.84-3.60]	3.40 [1.02-4.50]	5.20 [1.10-5.80]
	[min-max]	Btu/h	8,530 [2,860-12,300]	11,600 [3,480-15,300]	17,700 [3,750-19,800]
EER	[min-max]	Btu/hW	17.41 [13.30-13.67]	14.15 [14.20-12.75]	12.21 [12.93-11.86]
	[min-max]	W/W	5.10 [3.91-4.00]	4.15 [4.16-3.75]	3.59 [3.79-3.47]
CSPF		W/W	6.89	6.61	5.48
Electrical Data	Voltage	V	220	220	220
	Current	A	2.4	4.0	7.0
	Power Input [min-max]	W	490 [215-900]	820 [245-1,200]	1,450 [290-1,670]
Moisture Removal		L/h	1.5	2.0	2.9
		Pt/h	3.2	4.2	6.1
Air Circulation	Indoor	m ³ /min (ft ³ /min)	11.5 [405]	12.8 [450]	14.8 [520]
	Outdoor	m ³ /min (ft ³ /min)	31.3 [1,110]	31.3 [1,110]	34.9 [1,230]
Noise Level	Indoor [H / L / Q-Lo]	dB [A]	42/26/18	43/28/19	46/36/33
	Outdoor [H]	dB [A]	47	48	49
Dimensions Indoor (Outdoor)	Height	mm	306 [542]	306 [542]	306 [619]
		inch	12-1/16 [21-11/32]	12-1/16 [21-11/32]	12-1/16 [24-3/8]
	Width	mm	950 [780]	950 [780]	950 [824]
		inch	37-13/32 [30-23/32]	37-13/32 [30-23/32]	37-13/32 [32-15/32]
	Depth	mm	280 [289]	280 [289]	280 [299]
		inch	11-1/32 [11-13/32]	11-1/32 [11-13/32]	11-1/32 [11-25/32]
Net Weight	Indoor	kg (lb)	12 [26]	12 [26]	12 [26]
	Outdoor	kg (lb)	30 [66]	30 [66]	33 [73]
Refrigerant Pipe Diameter	Liquid Side	mm	ø 6.35	ø 6.35	ø 6.35
		inch	1/4	1/4	1/4
	Gas Side	mm	ø 9.52	ø 12.70	ø 15.88
		inch	3/8	1/2	5/8
Pipe Extension	Chargeless Pipe Length	m	7.5	7.5	10.0
	Maximum Pipe Length	m	20	20	30
	Maximum Elevation Length	m	15	15	20
	Additional Refrigerant Gas*	g/m	10	10	25
Power Supply			Indoor	Indoor	Indoor

*When pipes are not extended from the chargeless pipe length, the required amount of refrigerant is already in the unit.

FEATURES



BACKLIT SKY CONTROLLER

Enjoy innovative design at your fingertips with the new stylish and sleek Backlit Sky Controller. With fast access to key operations and a smooth gliding cover revealing more options, controlling your settings has become simple and intuitive. With a width of 58.9mm and a length of 164.7mm, the Sky Controller fits comfortably into your hand.



Wireless
Applicable to ELITE INVERTER

- Backlit LED screen lets you view operations status in the dark.
- Power Button.
- Switch on nanoe™ mode to activate nanoe™ X and nanoe-G for air purification and deodorisation even when the air conditioner is switched off.
- Toggles between RADIANT COOLING and Fast Cooling (DIRECT).
- Press up or down to set the temperature.
- iAUTO-X lets you come home with FAST COOLING. Then enjoy continuous comfort with RADIANT COOLING which avoids direct cooling.
- Set the airflow direction.
- Adjusts the fan speed.
- Toggles between iAUTO-X, COOL and DRY setting mode.
- Delays off timer with temperature control for better sleep.
- Set 24-hour Dual ON & OFF Timer.
- Set the actual time [hour and minute].

DUAL TIMER FOR 2 ON AND OFF TIMES PER DAY

Set the actual time (hour and minute).



- Select ON or OFF Timer.
- Set the time.

OUTDOOR UNIT




CU-VU9UKH-8
CU-VU12UKH-8



CU-VU18UKH-8

WALL-MOUNTED AERO ELITE *INVERTER* Single-Split Type




CS-XU9XKH-8 | CS-XU12XKH-8



Wireless (Standard)



Wired CZ-RD514C (Optional)



CS-XU18XKH-8 | CS-XU24XKH-8



Wireless (Standard)



Wired CZ-RD514C (Optional)



MODEL	INDOOR UNIT (50Hz)		CS-XU9XKH-8	CS-XU12XKH-8	CS-XU18XKH-8	CS-XU24XKH-8
	OUTDOOR UNIT		CU-XU9XKH-8	CU-XU12XKH-8	CU-XU18XKH-8	CU-XU24XKH-8
Cooling Capacity	[min-max]	kW	2.55 [0.92-3.40]	3.50 [1.02-4.20]	5.30 [1.10-6.21]	6.10 [1.12-7.18]
	[min-max]	Btu/h	8,700 [3,140-11,600]	11,900 [3,480-14,300]	18,100 [3,750-21,200]	20,800 [3,820-24,500]
EER	[min-max]	Btu/hW	12.79 [13.96-11.26]	12.53 [13.92-11.44]	13.71 [13.89-12.47]	13.00 [15.28-11.95]
	[min-max]	W/W	3.75 [4.09-3.30]	3.68 [4.08-3.36]	4.02 [4.07-3.65]	3.81 [4.48-3.50]
CSPF		W/W	5.85	6.34	7.28	6.88
Electrical Data	Voltage	V	220	220	220	220
	Current	A	3.2	4.4	6.2	7.4
	Power Input [min-max]	W	680 [225-1030]	950 [250-1,250]	1,320 [270-1,700]	1,600 [250-2,050]
Moisture Removal		L/h	1.6	2.0	2.9	3.4
		Pt/h	3.4	4.2	6.1	7.2
Air Circulation	Indoor	m ³ /min [ft ³ /min]	11.7 [415]	12.5 [440]	18.7 [660]	19.2 [680]
	Outdoor	m ³ /min [ft ³ /min]	26.5 [940]	30.9 [1,090]	34.9 [1,230]	46.3 [1,635]
Noise Level	Indoor [H / L / Q-Lo]	dB [A]	38/26/19	40/28/19	44/32/27	45/34/28
	Outdoor [H]	dB [A]	47	48	50	51
Dimensions Indoor [Outdoor]	Height	mm	295 [511]	295 [542]	295 [619]	295 [695]
		inch	11-5/8 [20-1/8]	11-5/8 [21-11/32]	11-5/8 [24-3/8]	11-5/8 [27-3/8]
	Width	mm	870 [650]	870 [780]	1,040 [824]	1,040 [875]
		inch	34-9/32 [25-19/32]	34-9/32 [30-23/32]	40-31/32 [32-15/32]	40-31/32 [34-15/32]
	Depth	mm	229 [230]	229 [289]	244 [299]	244 [320]
		inch	9-1/32 [9-1/16]	9-1/32 [11-13/32]	9-5/8 [11-25/32]	9-5/8 [12-5/8]
Net Weight	Indoor	kg [lb]	10 [22]	10 [22]	12 [26]	12 [26]
	Outdoor	kg [lb]	18 [40]	23 [51]	30 [66]	39 [86]
Refrigerant Pipe Diameter	Liquid Side	mm	ø 6.35	ø 6.35	ø 6.35	ø 6.35
		inch	1/4	1/4	1/4	1/4
	Gas Side	mm	ø 9.52	ø 9.52	ø 12.70	ø 12.70
		inch	3/8	3/8	1/2	1/2
Pipe Extension	Chargeless Pipe Length	m	7.5	7.5	10.0	10.0
	Maximum Pipe Length	m	20	20	30	30
	Maximum Elevation Length	m	15	15	20	20
	Additional Refrigerant Gas*	g/m	10	10	15	15
Power Supply			Indoor	Indoor	Indoor	Indoor

*When pipes are not extended from the chargeless pipe length, the required amount of refrigerant is already in the unit.

FEATURES



EASY-TO-USE REMOTE CONTROLLER

Panasonic's wireless remote controller features a large Liquid Crystal Display (LCD) panel which makes it even more user-friendly. So you can sit back and enjoy easy operation and long-lasting comfort from your Panasonic Air Conditioner.



Wireless
Applicable to
AERO ELITE INVERTER

- 1 LCD display for an easy overview of the operation status.
- 2 Power button.
- 3 Switch on nanoe™ mode to activate nanoe™ X and nanoe-G for air purification and deodorisation even when the air conditioner is switched off.
- 4 iAUTO-X cools your home with fast cooling together with Shower Cooling which avoids direct cooling while providing continuous comfort. Reactive faster cooling during stable temperature with second press of the iAUTO-X button.
- 5 Press up or down to set the temperature.
- 6 Toggles between iAUTO-X, COOL and DRY setting mode.
- 7 Set the airflow direction.
- 8 Adjusts the FAN SPEED or QUIET mode so you can sleep comfortably at night.
- 9 Delays off timer with temperature control for better sleep.
- 10 Switch on the ECO + A.I. mode to let you enjoy the comfort cooling with minimal energy waste.
- 11 Set 24-hour Dual ON & OFF Timer.
- 12 Set the actual time (hour and minute).



DUAL TIMER FOR 2 ON AND OFF TIMES PER DAY

For convenience, the dual timer repeats everyday until you cancel it.

- 1 Select ON or OFF Timer.
 - TIMER ON: [ON] → [1] → [2] → Cancel
 - TIMER OFF: [OFF] → [1] → [2] → Cancel
- 2 Set the time.
 - [SET]

OUTDOOR UNIT



CU-XU9XKH-8



CU-XU12XKH-8




CU-XU18XKH-8



CU-XU24XKH-8

WALL-MOUNTED PREMIUM **INVERTER** Single-Split Type



CS-U9XKH-8 | CS-U12XKH-8




Wireless (Standard)



Wired CZ-RD514C (Optional)



Network Adaptor CZ-TACG1 (Optional)



CS-U18XKH-8 | CS-U24XKH-8



Wireless (Standard)



Wired CZ-RD514C (Optional)




Network Adaptor CZ-TACG1 (Optional)



MODEL	INDOOR UNIT (50Hz)		CS-U9XKH-8	CS-U12XKH-8	CS-U18XKH-8	CS-U24XKH-8
	OUTDOOR UNIT		CU-U9XKH-8	CU-U12XKH-8	CU-U18XKH-8	CU-U24XKH-8
Cooling Capacity	[min-max] kW		2.55 [0.92-3.40]	3.50 [1.02-4.20]	5.30 [1.10-6.21]	6.10 [1.12-7.18]
	[min-max] Btu/h		8,700 [3,140-11,600]	11,900 [3,480-14,300]	18,100 [3,750-21,200]	20,800 [3,820-24,500]
EER	[min-max] Btu/hW		12.79 [13.96-11.26]	12.53 [13.92-11.44]	13.71 [13.89-12.47]	13.00 [15.28-11.95]
	[min-max] W/W		3.75 [4.09-3.30]	3.68 [4.08-3.36]	4.02 [4.07-3.65]	3.81 [4.48-3.50]
CSPF	W/W		5.84	6.33	7.28	6.87
Electrical Data	Voltage V		220	220	220	220
	Current A		3.2	4.4	6.2	7.4
	Power Input [min-max] W		680 [225-1,030]	950 [250-1,250]	1,320 [270-1,700]	1,600 [250-2,050]
Moisture Removal	L/h		1.6	2.0	2.9	3.4
	Pt/h		3.4	4.2	6.1	7.2
Air Circulation	Indoor m ³ /min (ft ³ /min)		11.7 [415]	12.5 [440]	18.7 [660]	19.2 [680]
	Outdoor m ³ /min (ft ³ /min)		26.5 [940]	30.9 [1,090]	34.9 [1,230]	46.3 [1,635]
Noise Level	Indoor [H / L / Q-Lo] dB [A]		38/26/19	40/28/19	44/32/27	45/34/28
	Outdoor [H] dB [A]		47	48	50	51
Dimensions Indoor [Outdoor]	Height	mm	295 [511]	295 [542]	295 [619]	295 [695]
		inch	11-5/8 [20-1/8]	11-5/8 [21-11/32]	11-5/8 [24-3/8]	11-5/8 [27-3/8]
	Width	mm	870 [650]	870 [780]	1,040 [824]	1,040 [875]
		inch	34-9/32 [25-19/32]	34-9/32 [30-23/32]	40-31/32 [32-15/32]	40-31/32 [34-15/32]
	Depth	mm	229 [230]	229 [289]	244 [299]	244 [320]
		inch	9-1/32 [9-1/16]	9-1/32 [11-13/32]	9-5/8 [11-25/32]	9-5/8 [12-5/8]
Net Weight	Indoor kg [lb]		10 [22]	10 [22]	12 [26]	12 [26]
	Outdoor kg [lb]		18 [40]	23 [51]	30 [66]	39 [86]
Refrigerant Pipe Diameter	Liquid Side	mm	ø 6.35	ø 6.35	ø 6.35	ø 6.35
		inch	1/4	1/4	1/4	1/4
	Gas Side	mm	ø 9.52	ø 9.52	ø 12.70	ø 12.70
		inch	3/8	3/8	1/2	1/2
Pipe Extension	Chargeless Pipe Length m		7.5	7.5	10.0	10.0
	Maximum Pipe Length m		20	20	30	30
	Maximum Elevation Length m		15	15	20	20
	Additional Refrigerant Gas* g/m		10	10	15	15
Power Supply			Indoor	Indoor	Indoor	Indoor

*When pipes are not extended from the chargeless pipe length, the required amount of refrigerant is already in the unit.

FEATURES



EASY-TO-USE REMOTE CONTROLLER

Panasonic's wireless remote controller features a large Liquid Crystal Display (LCD) panel which makes it even more user-friendly. So you can sit back and enjoy easy operation and long-lasting comfort from your Panasonic Air Conditioner.



Wireless Applicable to PREMIUM INVERTER

- LCD display for an easy overview of the operation status.
- Power button.
- Switch on nanoe™ mode to activate nanoe™ X and nanoe-G for air purification and deodorisation even when the air conditioner is switched off.
- iAUTO-X cools your home with fast cooling together with Shower Cooling which avoids direct cooling while providing continuous comfort. Reactivate faster cooling during stable temperature with a second press of the iAUTO-X button.
- Press up or down to set the temperature.
- Toggles between iAUTO-X, COOL and DRY setting mode.
- Set the airflow direction.
- Adjusts the FAN SPEED or QUIET mode so you can sleep comfortably at night.
- Delays off timer with temperature control for better sleep.
- Switch on the ECO + A.I. mode to let you enjoy the comfort cooling with minimal energy waste.
- Set the 24-hour Dual ON & OFF Timer.
- Set the actual time [hour and minute].



DUAL TIMER FOR 2 ON AND OFF TIMES PER DAY

For convenience, the dual timer repeats everyday until you cancel it.

- Select ON or OFF Timer.
 - TIMER ON: ① → ② → Cancel
 - TIMER OFF: ① → ② → Cancel
- Set the time.
 - SET

OUTDOOR UNIT



CU-U9XKH-8



CU-U12XKH-8



CU-U18XKH-8



CU-U24XKH-8

WALL-MOUNTED STANDARD **INVERTER** with Wi-Fi Single-Split Type




CS-WPU9XKH-8 | CS-WPU12XKH-8 | CS-WPU18XKH-8



Wireless (Standard)

Wired CZ-RD514C (Optional)



CS-WPU24XKH-8



Wireless (Standard)


Wired CZ-RD514C (Optional)



MODEL	INDOOR UNIT (50Hz)		CS-WPU9XKH-8	CS-WPU12XKH-8	CS-WPU18XKH-8	CS-WPU24XKH-8
	OUTDOOR UNIT		CU-WPU9XKH-8	CU-WPU12XKH-8	CU-WPU18XKH-8	CU-WPU24XKH-8
Cooling Capacity	[min-max] kW		2.65 [0.84-2.90]	3.50 [1.02-4.00]	5.00 [1.10-5.40]	6.10 [1.12-7.18]
	[min-max] Btu/h		9,040 [2,860-9,890]	11,900 [3,480-13,600]	17,100 [3,750-18,400]	20,800 [3,820-24,500]
EER	[min-max] Btu/hW		11.30 [12.71-10.99]	11.12 [12.65-11.06]	10.30 [12.93-10.22]	12.61 [15.28-11.95]
	[min-max] W/W		3.31 [3.73-3.22]	3.27 [3.71-3.25]	10.84 [13.66-10.80]	3.70 [4.48-3.50]
CSPF	W/W		4.81	5.06	5.09	6.22
Electrical Data	Voltage V		220	220	220	220
	Current A		3.9	5.0	7.7	7.7
	Power Input [min-max] W		800 [225-900]	1,070 [275-1,230]	1,660 [290-1,800]	1,650 [250-2,050]
Moisture Removal	L/h		1.6	2.0	2.8	3.4
	Pt/h		3.4	4.2	5.9	7.2
Air Circulation	Indoor m ³ /min (ft ³ /min)		10.3 [365]	11.0 [390]	12.6 [445]	19.2 [680]
	Outdoor m ³ /min (ft ³ /min)		26.7 [940]	30.2 [1,065]	39.3 [1,390]	34.9 [1,230]
Noise Level	Indoor [H / L / Q-Lo] dB [A]		36/26/21	37/28/21	44/34/28	45/34/29
	Outdoor [H] dB [A]		47	48	51	51
Dimensions Indoor [Outdoor]	Height	mm	290 [511]	290 [542]	290 [619]	295 [619]
		inch	11-7/16 [20-1/8]	11-7/16 [21-11/32]	11-7/16 [24-3/8]	11-5/8 [24-3/8]
	Width	mm	779 [650]	779 [780]	779 [824]	1,040 [824]
		inch	30-11/16 [25-19/32]	30-11/16 [30-23/32]	30-11/16 [32-15/32]	40-31/32 [32-15/32]
	Depth	mm	209 [230]	209 [289]	209 [299]	244 [299]
		inch	8-1/4 [9-1/16]	8-1/4 [11-13/32]	8-1/4 [11-25/32]	9-5/8 [11-25/32]
Net Weight	Indoor kg [lb]		8 [18]	8 [19]	9 [20]	12 [26]
	Outdoor kg [lb]		18 [40]	23 [51]	29 [64]	32 [71]
Refrigerant Pipe Diameter	Liquid Side	mm	ø 6.35	ø 6.35	ø 6.35	ø 6.35
		inch	1/4	1/4	1/4	1/4
	Gas Side	mm	ø 9.52	ø 9.52	ø 12.70	ø 12.70
		inch	3/8	3/8	1/2	1/2
Pipe Extension	Chargeless Pipe Length	m	7.5	7.5	10.0	10.0
	Maximum Pipe Length	m	20	20	30	30
	Maximum Elevation Length	m	15	15	20	20
	Additional Refrigerant Gas*	g/m	10	10	15	15
Power Supply			Indoor	Indoor	Indoor	Indoor

*When pipes are not extended from the chargeless pipe length, the required amount of refrigerant is already in the unit.

FEATURES



EASY-TO-USE REMOTE CONTROLLER

Panasonic's wireless remote controller features a large Liquid Crystal Display (LCD) panel which makes it even more user-friendly. So you can sit back and enjoy easy operation and long-lasting comfort from your Panasonic Air Conditioner.



- 1 LCD display for an easy overview of the operation status.
- 2 Toggles setting between POWERFUL mode and ECO with A.I. setting mode. POWERFUL mode provides fast cooling while ECO with A.I. mode provides energy saving.
- 3 Activates the nanoe-G function even when the air conditioner is switched off.
- 4 Press up or down to set the temperature.
- 5 Toggles between AUTO, COOL and DRY setting mode.
- 6 Delays off timer with temperature control for better sleep.
- 7 Adjusts the FAN SPEED or QUIET function allows you to sleep comfortably at night.
- 8 Set the airflow direction.
- 9 Set 24-hour Dual ON & OFF Timer.
- 10 Set the actual time (hour and minute).
- 11 Press Wireless LAN button for Wireless LAN connection.

Wireless
Applicable to
CS-WPU24XKH-8



Powerful Cooling at Start-up

POWERFUL Mode cools your room faster by 18%* at the start to bring you cooling comfort instantly on a hot day.

Press **POWERFUL/ECO** once to switch ON POWERFUL Mode.

* Comparison of POWERFUL Cool Mode & normal cool mode by using 1.5HP Inverter Model

OUTDOOR UNIT



CU-WPU9XKH-8



CU-WPU12XKH-8



CU-WPU18XKH-8
CU-WPU24XKH-8

WALL-MOUNTED STANDARD **INVERTER** with nanoe™ X Single-Split Type



CS-XPU9XKH-8 | CS-XPU12XKH-8 | CS-XPU18XKH-8




Wireless (Standard)



Wired CZ-RD514C (Optional)



Network Adaptor CZ-TACG1 (Optional)



CS-XPU18XKH-8B | CS-XPU24XKH-8



Wireless (Standard)



Wired CZ-RD514C (Optional)




Network Adaptor CZ-TACG1 (Optional)



MODEL	INDOOR UNIT (50Hz)	CS-XPU9XKH-8	CS-XPU12XKH-8	CS-XPU18XKH-8	CS-XPU18XKH-8B	CS-XPU24XKH-8	
	OUTDOOR UNIT	CU-XPU9XKH-8	CU-XPU12XKH-8	CU-XPU18XKH-8	CU-XPU18XKH-8B	CU-XPU24XKH-8	
Cooling Capacity	[min-max] kW	2.65 [0.84-2.90]	3.50 [1.02-4.00]	5.00 [1.10-5.40]	5.15 [1.10-5.80]	6.10 [1.12-7.18]	
	[min-max] Btu/h	9,040 [2,860-9,890]	11,900 [3,480-13,600]	17,100 [3,750-18,400]	17,600 [3,750-19,800]	20,800 [3,820-24,500]	
EER	[min-max] Btu/hW	11.30 [12.71-10.99]	11.12 [12.65-11.06]	10.30 [12.93-10.22]	11.35 [12.93-11.25]	12.61 [15.28-11.95]	
	[min-max] W/W	3.31 [3.73-3.22]	3.27 [3.71-3.25]	3.01 [3.79-3.00]	3.32 [3.79-3.30]	3.70 [4.48-3.50]	
CSPF	W/W	4.81	5.07	5.09	5.96	6.24	
Electrical Data	Voltage V	220	220	220	220	220	
	Current A	3.9	5.0	7.7	7.1	7.7	
	Power Input [min-max] W	800 [225-900]	1,070 [275-1,230]	1,660 [290-1,800]	1,550 [290-1,760]	1,650 [250-2,050]	
Moisture Removal	L/h	1.6	2.0	2.8	2.9	3.4	
	Pt/h	3.4	4.2	5.9	6.1	7.2	
Air Circulation	Indoor m ³ /min (ft ³ /min)	10.3 [365]	11.0 [390]	12.6 [445]	18.7 [660]	19.2 [680]	
	Outdoor m ³ /min (ft ³ /min)	26.7 [940]	30.2 [1,065]	39.3 [1,390]	39.3 [1,385]	34.9 [1,230]	
Noise Level	Indoor [H / L / Q-Lo] dB [A]	36/26/21	37/28/21	44/34/28	44/32/28	45/34/29	
	Outdoor [H] dB [A]	47	48	51	50	51	
Dimensions Indoor [Outdoor]	Height	mm	290 [511]	290 [542]	290 [619]	295 [619]	295 [619]
		inch	11-7/16 [20-1/8]	11-7/16 [21-11/32]	11-7/16 [24-3/8]	11-5/8 [24-3/8]	11-5/8 [24-3/8]
	Width	mm	779 [650]	779 [780]	779 [824]	1,040 [824]	1,040 [824]
		inch	30-11/16 [25-19/32]	30-11/16 [30-23/32]	30-11/16 [32-15/32]	40-31/32 [32-15/32]	40-31/32 [32-15/32]
	Depth	mm	209 [230]	209 [289]	209 [299]	244 [299]	244 [299]
		inch	8-1/4 [9-1/16]	8-1/4 [11-13/32]	8-1/4 [11-25/32]	9-5/8 [11-25/32]	9-5/8 [11-25/32]
Net Weight	Indoor kg [lb]	8 [18]	8 [18]	9 [20]	12 [26]	12 [26]	
	Outdoor kg [lb]	18[40]	23[51]	29[64]	29 [64]	32 [71]	
Refrigerant Pipe Diameter	Liquid Side	mm	ø 6.35	ø 6.35	ø 6.35	ø 6.35	ø 6.35
		inch	1/4	1/4	1/4	1/4	1/4
	Gas Side	mm	ø 9.52	ø 9.52	ø 12.70	ø 12.70	ø 12.70
		inch	3/8	3/8	1/2	1/2	1/2
Pipe Extension	Chargeless Pipe Length m	7.5	7.5	10.0	10.0	10.0	
	Maximum Pipe Length m	20	20	30	30	30	
	Maximum Elevation Length m	15	15	20	20	20	
	Additional Refrigerant Gas* g/m	10	10	15	15	15	
Power Supply		Indoor	Indoor	Indoor	Indoor	Indoor	


*When pipes are not extended from the chargeless pipe length, the required amount of refrigerant is already in the unit.

FEATURES



EASY-TO-USE REMOTE CONTROLLER

Panasonic's wireless remote controller features a large Liquid Crystal Display (LCD) panel which makes it even more user-friendly. So you can sit back and enjoy easy operation and long-lasting comfort from your Panasonic Air Conditioner.



Wireless

Applicable to CS-XPU18XKH-8B, CS-XPU24XKH-8

- LCD display for an easy overview of the operation status.
- Toggles setting between POWERFUL mode and ECO with A.I. setting mode. POWERFUL mode provides fast cooling while ECO with A.I. mode provides energy saving.
- Switch on nanoe™ Technology function to activate nanoe™ X and nanoe-G for air purification and deodorisation even when the air conditioner is switched off.
- Press up or down to set the temperature.
- Toggles between AUTO, COOL and DRY setting mode.
- Delays off timer with temperature control for better sleep.
- Adjusts the FAN SPEED or QUIET function allows you to sleep comfortably at night.
- Set the airflow direction.
- Set 24-hour Dual ON & OFF Timer.
- Set the actual time (hour and minute).



Powerful Cooling at Start-up

POWERFUL Mode cools your room faster by 18%* at the start to bring you cooling comfort instantly on a hot day.

Press **POWERFUL/ECO** once to switch ON POWERFUL Mode.

* Comparison of POWERFUL Cool Mode & normal cool mode by using 1.5HP Inverter Model

OUTDOOR UNIT



CU-XPU9XKH-8



CU-XPU12XKH-8



CU-XPU18XKH-8
CU-XPU18XKH-8B
CU-XPU24XKH-8


WALL-MOUNTED STANDARD NON-INVERTER Single-Split Type



CS-N9WKH-8 | CS-N12WKH-8



Wireless (Standard)



CS-N18XKH-8 | CS-N24XKH-8



Wireless (Standard)

nanoe-G

BIG FLAP
[CS-N9/12WKH-8]


AEROWINGS
[CS-N18/24XKH-8]

POWERFUL

MODEL	INDOOR UNIT OUTDOOR UNIT	[50Hz]	CS-N9WKH-8 CU-N9WKH-8	CS-N12WKH-8 CU-N12WKH-8	CS-N18XKH-8 CU-N18XKH-8	CS-N24XKH-8 CU-N24XKH-8
Cooling Capacity	[min-max]	kW	2.65	3.52	5.28	6.60
	[min-max]	Btu/h	9,040	12,000	18,000	22,500
EER	[min-max]	Btu/hW	11.89	12.00	11.25	10.82
	[min-max]	W/W	3.49	3.52	3.30	3.17
CSPF		W/W	3.44	3.48	3.50	3.37
Electrical Data	Voltage	V	220	220	220	220
	Current	A	3.6	4.8	7.4	9.6
	Power Input [min-max]	W	760	1,000	1,600	2,080
Moisture Removal		L/h	1.6	2.0	2.9	3.7
		Pt/h	3.4	4.2	6.1	7.8
Air Circulation	Indoor	m ³ /min [ft ³ /min]	10.5 [371]	12.0 [424]	18.5[653]	21.0 [741]
	Outdoor	m ³ /min [ft ³ /min]	27.6 [970]	29.0 [1,020]	39.3 [1,390]	39.0 [1,380]
Noise Level	Indoor [H / L / Q-Lo]	dB [A]	37/26	41/29	44/36	48/40
	Outdoor [H]	dB [A]	47	49	52	54
Dimensions Indoor [Outdoor]	Height	mm	290 [511]	290 [542]	295 [619]	295 [619]
		inch	11-7/16 [20-1/8]	11-7/16 [21-11/32]	11-5/8 [24-3/8]	11-5/8 [24-3/8]
	Width	mm	779 [650]	779 [780]	1,040 [824]	1,040 [824]
		inch	30-11/16 [25-19/32]	30-11/16 [30-23/32]	40-31/32[32-15/32]	40-31/32 [32-15/32]
	Depth	mm	209 [230]	209 [289]	244 [299]	244 [299]
		inch	8-1/4 [9-1/16]	8-1/4 [11-13/32]	9-5/8 [11-25/32]	9-5/8 [11-25/32]
Net Weight	Indoor	kg [lb]	8 [18]	8 [18]	12 [26]	12 [26]
	Outdoor	kg [lb]	22 [49]	27 [60]	36 [79]	42 [93]
Refrigerant Pipe Diameter	Liquid Side	mm	ø 6.35	ø 6.35	ø 6.35	ø 6.35
		inch	1/4	1/4	1/4	1/4
	Gas Side	mm	ø 9.52	ø 12.70	ø 12.70	ø 15.88
		inch	3/8	1/2	1/2	5/8
Pipe Extension	Chargeless Pipe Length	m	7.5	7.5	7.5	7.5
	Maximum Pipe Length	m	20	20	30	30
	Maximum Elevation Length	m	15	15	20	20
	Additional Refrigerant Gas*	g/m	10	10	15	25
Power Supply			Indoor	Indoor	Indoor	Indoor

*When pipes are not extended from the chargeless pipe length, the required amount of refrigerant is already in the unit.

FEATURES



EASY-TO-USE REMOTE CONTROLLER

Panasonic's wireless remote controller features a large Liquid Crystal Display (LCD) panel which makes it even more user-friendly. So you can sit back and enjoy easy operation and long-lasting comfort from your Panasonic Air Conditioner.



Wireless
Applicable to
CS-N18/24XKH-8

- 1 LCD display for an easy overview of the operation status.
- 2 Pressing the POWERFUL button to cool the room faster.
- 3 Activates the nanoe-G function even when the air conditioner is switched off.
- 4 Press up or down to set the temperature.
- 5 Toggles between AUTO, COOL and DRY setting mode.
- 6 Delays off timer with temperature control for better sleep.
- 7 Adjusts the FAN SPEED or QUIET function allows you to sleep comfortably at night.
- 8 Set the airflow direction.
- 9 Set the 24-hour ON & OFF Timer.
- 10 Set the actual time (hour and minute).



Powerful Cooling at Start-up

POWERFUL Mode cools your room faster at the start to bring you cooling comfort instantly on a hot day.

Press **POWERFUL** once to switch ON POWERFUL Mode.

OUTDOOR UNIT



CU-N9WKH-8




CU-N12WKH-8



CU-N18XKH-8
CU-N24XKH-8

WALL-MOUNTED PREMIUM **INVERTER** Heat Pump Single-Split Type




CS-XZ9XKH-8 | CS-XZ12XKH-8



Wireless (Standard)



Wired CZ-RD514C (Optional)



CS-XZ18XKH-8 | CS-XZ24XKH-8



Wireless (Standard)




Wired CZ-RD514C (Optional)



MODEL	INDOOR UNIT (50Hz)		CS-XZ9XKH-8	CS-XZ12XKH-8	CS-XZ18XKH-8	CS-XZ24XKH-8
	OUTDOOR UNIT		CU-XZ9XKH-8	CU-XZ12XKH-8	CU-XZ18XKH-8	CU-XZ24XKH-8
Cooling / Heating Capacity	[min-max]	kW	2.50 [1.00-3.70] 3.20 [1.00-5.30]	3.50 [1.00-4.20] 3.70 [1.00-5.80]	5.00 [1.10-6.70] 6.00 [1.10-8.00]	7.10 [1.40-8.90] 8.00 [1.40-10.00]
	[min-max]	Btu/h	8,530 [3,410-12,600] 10,900 [3,410-18,100]	11,900 [3,410-14,300] 12,600 [3,410-19,800]	17,100 [3,750-22,800] 20,500 [3,750-27,300]	24,200 [4,770-30,300] 27,300 [4,770-34,100]
EER / COP	[min-max]	Btu/hW	17.41[17.49-12.60] 16.77[17.49-12.48]	14.69[17.49-11.92] 16.36[17.49-12.77]	15.13[16.30-11.40] 15.41[17.05-11.62]	10.61[11.09-9.04] 11.67[11.93-10.33]
	[min-max]	W/W	5.10[5.13-3.70] 4.92[5.13-3.66]	4.32[5.13-3.50] 4.81[5.13-3.74]	4.42[4.78-3.35] 4.51[5.00-3.40]	3.11[3.26-2.66] 3.42[3.50-3.03]
CSPF		W/W	7.70	7.16	7.08	5.31
Electrical Data	Voltage	V	220	220	220	220
	Running Current	A	2.4 3.1	4.0 3.8	5.4 6.3	10.7 11.0
	Power Input (min-max)	W	490[195-1,000] 650[195-1,450]	810[195-1,200] 770[195-1,550]	1,130[230-2,000] 1,330[220-2,350]	2,280[430-3,350] 2,340[400-3,300]
Moisture Removal		L/h	1.5	2.0	2.8	4.1
		Pt/h	3.2	4.2	5.9	8.7
Air Circulation (Indoor/Hi)		m ³ /min	11.6	13.0	18.7	20.8
		ft ³ /min	410 410	460 460	660 660	735 735
Noise Level	Indoor [H / L / Q-Lo]	dB [A]	40/25/19 40/28/23	42/28/19 42/33/30	45/35/28 45/33/28	47/37/30 47/37/30
		dB [A]	47 48	48 50	48 50	53 53
	Outdoor [H]	dB [A]				
Dimensions Indoor (Outdoor)	Height	mm	295[542]	295[542]	295[695]	295[695]
		inch	11-5/8[21-11/32]	11-5/8[21-11/32]	11-5/8[27-3/8]	11-5/8[27-3/8]
	Width	mm	870[780]	870[780]	1,040[875]	1,040[875]
		inch	34-9/32[30-23/32]	34-9/32[30-23/32]	40-31/32[34-15/32]	40-31/32[34-15/32]
	Depth	mm	229[289]	229[289]	244[320]	244[320]
		inch	9-1/32[11-13/32]	9-1/32[11-13/32]	9-5/8[12-5/8]	9-5/8[12-5/8]
Net Weight	Indoor	kg (lb)	10[22]	10[22]	12[26]	14[31]
	Outdoor	kg (lb)	31[68]	31[68]	41[90]	50[110]
Refrigerant Pipe Diameter	Liquid Side	mm	ø 6.35	ø 6.35	ø 6.35	ø 6.35
		inch	1/4	1/4	1/4	1/4
	Gas Side	mm	ø 9.52	ø 9.52	ø 12.70	ø 15.88
		inch	3/8	3/8	1/2	5/8
Pipe Extension	Chargeless Pipe Length	m	7.5	7.5	7.5	10.0
	Maximum Pipe Length	m	20	20	30	30
	Maximum Elevation Length	m	15	15	15	20
	Additional Refrigerant Gas*	g/m	10	10	15	25
Power Supply			Indoor	Indoor	Indoor	Indoor

*When pipes are not extended from the chargeless pipe length, the required amount of refrigerant is already in the unit.

FEATURES



EASY-TO-USE REMOTE CONTROLLER

Panasonic's wireless remote controller feature a large Liquid Crystal Display (LCD) panel which makes it even more user-friendly. So you can sit back and enjoy easy operation and long-lasting comfort from your Panasonic Air Conditioner.



- 1 LCD display for an easy overview of the operation status.
- 2 Power button.
- 3 Switch on nanoe™ mode to activate nanoe™ X and nanoe-G for air purification and deodorisation even when the air conditioner is switched off.
- 4 iAUTO-X cools your home with fast cooling together with Shower Cooling which avoids direct cooling while providing continuous comfort. Reactive faster cooling during stable temperature with second press of the iAUTO-X button.
- 5 Press up or down to set the temperature.
- 6 Toggles between iAUTO-X, COOL, HEAT and DRY setting mode.
- 7 Set the airflow direction.
- 8 Adjusts the FAN SPEED or QUIET mode so you can sleep comfortably at night.
- 9 Delays off timer with temperature control for better sleep.
- 10 Switch on the ECO + A.I. mode to let you enjoy the comfort cooling with minimal energy waste.
- 11 Set 24-hour Dual ON & OFF Timer.
- 12 Set the actual time (hour and minute).

Wireless
Applicable to
PREMIUM INVERTER
HEAT PUMP

DUAL TIMER FOR 2 ON AND OFF TIMES PER DAY

For convenience, the dual timer repeats everyday until you cancel it.



- 1 Select ON or OFF Timer.
 - TIMER ON: [ON] → [1] → [2] → Cancel
 - TIMER OFF: [OFF] → [1] → [2] → Cancel
- 2 Set the time.
 - [SET]

OUTDOOR UNIT



CU-XZ9XKH-8
CU-XZ12XKH-8



CU-XZ18XKH-8
CU-XZ24XKH-8

WALL-MOUNTED STANDARD **INVERTER** Heat Pump Single-Split Type



CS-YZ9WKH-8 | CS-YZ12WKH-8




Wireless (Standard)



Wired CZ-RD514C (Optional)



Network Adaptor CZ-TACG1 (Optional)



CS-YZ18XKH-8



Wireless (Standard)



Wired CZ-RD514C (Optional)




Network Adaptor CZ-TACG1 (Optional)



MODEL	INDOOR UNIT (50Hz)		CS-YZ9WKH-8	CS-YZ12WKH-8	CS-YZ18XKH-8
	OUTDOOR UNIT		CU-YZ9WKH-8	CU-YZ12WKH-8	CU-YZ18XKH-8
Cooling / Heating Capacity	[min-max]	kW	2.65 [0.84-3.00] 3.15 [0.84-3.50]	3.50 [0.92-3.80] 3.84 [0.92-4.10]	5.20 [1.20-6.00] 5.40 [1.20-7.70]
	[min-max]	Btu/h	9,040 [2,860-10,200] 10,700 [2,860-11,900]	11,900 [3,140-13,000] 13,100 [3,140-14,000]	17,700 [4,090-20,500] 18,400 [4,090-26,300]
EER / COP	[min-max]	Btu/hW	12.91 [13.00-10.20] 14.08 [14.30-12.02]	11.02 [11.21-10.40] 12.24 [12.56-11.57]	12.46 [17.04-11.71] 13.63 [18.59-12.23]
	[min-max]	W/W	3.79 [3.82-3.00] 4.14 [4.20-3.54]	3.24 [3.29-3.04] 3.59 [3.68-3.39]	3.66 [5.00-3.43] 4.00 [5.45-3.58]
CSPF		W/W	6.43	5.17	6.83
Electrical Data	Voltage	V	220	220	220
	Running Current	A	3.4 3.5	5.0 5.0	6.7 6.2
	Power Input (min-max)	W	700 [220-1,000] 760 [200-990]	1,080 [280-1,250] 1,070 [250-1,210]	1,420 [240-1,750] 1,350 [220-2,150]
Moisture Removal		L/h	1.6	2.0	2.9
		Pt/h	3.4	4.2	6.1
Air Circulation (Indoor/Hi)		m ³ /min	11.9	12.4	18.7
		ft ³ /min	420 420	440 440	660 660
Noise Level	Indoor [H / L / Q-Lo]	dB [A]	41/26/22 41/28/25	42/30/25 42/33/30	44/37/28 44/37/32
	Outdoor [H]	dB [A]	50 50	50 50	50 50
Dimensions Indoor (Outdoor)	Height	mm	290 [542]	295 [542]	295 [619]
		inch	11-7/16 [21-11/32]	11-7/16 [21-11/32]	11-5/8 [24-3/8]
	Width	mm	779 [780]	779 [780]	1,040 [824]
		inch	30-11/16 [30-23/32]	30-11/16 [30-23/32]	40-31/32 [32-15/32]
Depth	mm	209 [289]	209 [289]	244 [299]	
	inch	8-1/4 [11-13/32]	8-1/4 [11-13/32]	9-5/8 [11-25/32]	
Net Weight	Indoor	kg [lb]	8 [18]	8 [18]	12 [26]
	Outdoor	kg [lb]	25 [55]	25 [55]	34 [75]
Refrigerant Pipe Diameter	Liquid Side	mm	φ 6.35	φ 6.35	φ 6.35
		inch	1/4	1/4	1/4
	Gas Side	mm	φ 9.52	φ 9.52	φ 12.70
		inch	3/8	3/8	1/2
Pipe Extension	Chargeless Pipe Length	m	7.5	7.5	7.5
	Maximum Pipe Length	m	15	15	30
	Maximum Elevation Length	m	15	15	15
	Additional Refrigerant Gas*	g/m	10	10	15
Power Supply			Indoor	Indoor	Indoor


*When pipes are not extended from the chargeless pipe length, the required amount of refrigerant is already in the unit.

FEATURES



EASY-TO-USE REMOTE CONTROLLER

Panasonic's wireless remote controller features a large Liquid Crystal Display (LCD) panel which makes it even more user-friendly. So you can sit back and enjoy easy operation and long-lasting comfort from your Panasonic Air Conditioner.



Wireless
Applicable to
CS-YZ18XKH-8

- 1 LCD display for an easy overview of the operation status.
- 2 Toggles setting between POWERFUL mode and ECO with A.I. setting mode. POWERFUL mode provides fast cooling while ECO with A.I. mode provides energy saving.
- 3 Activates the nanoe-G function even when the air conditioner is switched off.
- 4 Press up or down to set the temperature.
- 5 Toggles between AUTO, COOL, HEAT and DRY setting mode.
- 6 Delays off timer with temperature control for better sleep.
- 7 Adjusts the FAN SPEED or QUIET function allows you to sleep comfortably at night.
- 8 Set the airflow direction.
- 9 Set 24-hour Dual ON & OFF Timer.
- 10 Set the actual time (hour and minute).



Powerful Cooling at Start-up

POWERFUL Mode cools your room faster by 18%* at the start to bring you cooling comfort instantly on a hot day.

Press **POWERFUL/ECO** once to switch ON POWERFUL Mode.

* Comparison of POWERFUL Cool Mode & normal cool mode by using 1.5HP Inverter Model.

OUTDOOR UNIT



CU-YZ9WKH-8
CU-YZ12WKH-8





CU-YZ18XKH-8



3 Key Elements for Quality Air


Envisioning a comfortable environment is now made a reality. Panasonic maintains three key elements such as Air Conditioning, Air Ventilation and Air Purification to ensure you can enjoy quality air that enriches your life.

QUALITY AIR FOR LIFE



Air Conditioning





Panasonic air conditioners offer comfortable cooling while harmonising with any interior designs.

<p>Wall-mounted Air Conditioner</p>  <p>Cool air descends from above for gentle and even cooling.</p>	<p>4-Way Cassette</p>  <p>360° wide and comfortable airflow.</p>
--	---



nanoe™ X technology

Deodorises and effectively inhibits bacteria, viruses and pollutants in the air and surfaces (adhered) for a clean and safe environment.

<p>Wall-mounted Air Conditioner</p>  <p>Purifies your living space by inhibiting various pollutants to protect you and your family.</p>	<p>Humidifying Air Purifier</p>  <p>Safe air with HEPA composite filter that removes 99.97% of 0.3µm particles.</p>	<p>air-e</p>  <p>Deodorises unpleasant smells and fabrics, occupying only a minimal space.</p>	<p>Portable nanoe™ X Generator</p>  <p>The portable and lightweight design makes it ideal for any environment.</p>
---	---	--	--



Ventilation

Maintains a circulated air flow while ventilating indoor air by minimising CO₂ and VOCs to keep the space fresh all-round.

<p>ERV</p>  <p>Brings fresh air in from outside while expelling stale air and heat.</p>	<p>Supply Fan</p>  <p>Ensures only fresh, clean air enters the room and removes particles.</p>
--	---



COMPLETE AIR MANAGEMENT SYSTEM

Complete Air Management System

Utilising the Indoor Air Quality (IAQ) sensor to continuously monitor air quality while adjusting cooling and ventilation volume, Panasonic's Complete Air Management System provides clear air, optimised at a comfortable temperature and humidity.

This system minimises the required time to purify contaminated air and restore fresh air to your environment using less energy. Delivering our promise of the future, with the Complete Air Management System*.

Linked operation of air conditioner + supply fan + IAQ remote controller

*Product availability may vary depending on country.

Functions of the Complete Air Management System

Evaluates Air Quality Visibly

- Sensing and assessing air in 4 levels.
- Air quality is still monitored when the system is off, so you can check the air conditions at home via the app anytime, anywhere.
- Updates status every 5 minutes, allowing you to check the current conditions at your convenience.




Sensor Information	Values
Temperature	-9 — 50°C
Humidity	20 — 95%
PM 2.5	0 — 2,000 μg/m³
CO ₂	400 — 3,000ppm

Evaluation	Points	Color	Overall Evaluation
Excellent	25 points	Blue	All excellent status (100 points)
Good	20 points	Green	Total of 4 elements 71-99 points
Fair	15 points	Orange	Total of 4 elements 56-70 points
Poor	10 points	Red	Total of 4 elements under 55 points



Intelligent Sensing

- Detects air quality constantly with IAQ sensors, automatically controlling cooling and airflow.



Benefits of Complete Air Management System

The Complete Air Management System gives you the ability to monitor air quality by cooling, ventilating and purifying the space at your convenience for greater mornings and better nights, all-day long.



*Illustrations of app screens may differ from actual screen appearance.

Expanding the nanoe™ world in Japan-24/7, Anywhere, Anytime.

Increasingly adopted in a wide range of industries such as railway, automotive, hotel and hospital industries

Public Transport



JR Kyushu



Keihan Railway



KEIO



JR East

Office



4-way cassette air conditioners



Hitachi

Home



Humidifying air purifiers




Humidifiers



Clothes drying dehumidifiers



Fans



Air conditioners

Automotive

Toyota Lexus

Expanding adoption to 40 models



Suzuki

Mazda

Subaru



Public spaces



Ceiling-embedded nanoe™ generators

Hotels



Cafes



Hospitals



Nursery schools



Nursing homes




Panasonic is committed to the improvement of air quality with nanoe™ technology.


Trade names, trademarks and images of products/services are used in this material under approval by the entities concerned in Japan. (As of May 31st, 2020)

The Development of nanoe™ technology

nanoe™ technology development started with the aim of using water's natural tendency to dissolve odour-causing substances. Through repeated improvements on the nanoe™ device over the years, it now generates 20 times more hydroxyl radicals to ensure the air is purified at all times.



Effectiveness of nanoe X Generator Mark 2 vs nanoe X Generator Mark 1



*Lifespan of hydroxyl radicals contained in water is around 10 minutes, during this time they have the capacity to act against the pollutants. It may require longer to inhibit pollutants effectively, see the tests on effectiveness on nanoe™ X on airborne and adhesive pollutants.



Deodorises frequently encountered odours



Odour causing substances such as cigarette smoke and garbage are removed to a hardly noticeable level.



Acts on odour causing substances & deodorises them

nanoe™ X particles, which are smaller than steam particles, penetrate into deepest parts of fibres allowing for highly effective deodorisation.

How nanoe™ X Reduces Odour



[Representative evidence]

** : Units based on Panasonic standards

	Odours	Result**	Capacity	Time (Hr.)	Testing organisation	Report No.
Adhered	Cigarette smoke odour	Odour intensity reduced by 2.4 levels	Approx. 23m ³	0.2	Panasonic Product Analysis Center	4AA33-160615-N04
	Pet odour	Odour intensity reduced by 1.5 levels	Approx. 23m ³	1	Panasonic Product Analysis Center	4AA33-160315-A34
	Durian odour	Odour intensity reduced by 1.0 levels	Approx. 23m ³	0.5	Panasonic Product Analysis Center	1V332-180402-K01
	BBQ odour	Odour intensity reduced by 1.2 levels	Approx. 23m ³	2	Panasonic Product Analysis Center	4AA33-151221-N01
	Sweat odour (Nonanoic acid)	Odour intensity reduced by 1.1 levels	Approx. 23m ³	1	Panasonic Product Analysis Center	Y16HM016
	Sweat odour (Hexanoic acid)	Odour intensity reduced by 2.6 levels	Approx. 23m ³	1	Panasonic Product Analysis Center	4AA33-160315-A35
	Scalp odour (Pillow cover)	Odour intensity reduced by 0.65 levels	Approx. 23m ³	6	[Supervision] Odour and Aroma Design Course, Department of Integrated Informatics, Faculty of Informatics, Daido University	
	Garbage odour (Methylmercaptan)	Odour intensity reduced by 1.2 levels	Approx. 23m ³	0.5	Panasonic Product Analysis Center	1V332-18220-K11
	Garbage odour (Trimethylamine)	Odour intensity reduced by 1.4 levels	Approx. 23m ³	0.5	Panasonic Product Analysis Center	1V332-180220-K12
	Damp odour (Triethylamine)	Odour intensity reduced by 1.7 levels	Approx. 23m ³	0.5	Panasonic Product Analysis Center	Y16RA002


Results may vary based on usage, and seasonal and environment variables (temperature and humidity). nanoe™ X and nanoe™ inhibit activity or growth of viruses, but do not prevent infection. Deodorisation effect varies according to the environment (temperature and humidity), operation time, odour, and fabric types.



Inhibits activity of airborne, adhered bacteria and viruses

nanoe™ X inhibits the activity of airborne and adhered bacteria and viruses.


How nanoe™ X Inhibits Bacteria & Viruses



nanoe™ X reliably reaches virus.




Hydroxyl radicals transform virus proteins.



Virus activity is inhibited.

[Representative evidence]

** : Units based on Panasonic standards



[Representative evidence]

	Bacteria & viruses	Result**	Capacity	Time (Hr.)	Testing organisation	Report No.
Airborne	Virus Bacteriophage ΦX174	99.7% inhibited	Approx. 25m ³	6	Kitasato Research Center for Environmental Science	24_0300_1
	Bacteria Staphylococcus aureus	99.9% inhibited	Approx. 25m ³	4	Kitasato Research Center for Environmental Science	2016_0279
Adhered	Virus Bacteriophage ΦX174	99.8% inhibited	Approx. 25m ³	8	Japan Food Research Laboratories	13001265005-01
	Bacteria Staphylococcus aureus	99.1% inhibited	Approx. 25m ³	8	Japan Food Research Laboratories	13044083003-01
Adhered Novel Coronavirus	SARS-CoV-2	99.9% inhibited	45L	2	Texcell France	1140-01 A1
	SARS-CoV-2	91.4% inhibited	6.7m ³	8	Texcell France	1140-01 C3
	SARS-CoV-2	99.7% inhibited	6.7m ³	24	Texcell France	1140-01 C3
Adhered virus	Influenza virus (H1N1 subtype)	99.9% inhibited	1m ³	2	Kitasato Research Center for Environmental Science	21_0084_1
	Feline calicivirus (Related form of norovirus)	99.9% inhibited	25L	2	Japan Food Research Laboratories	207031493-001
	Coxsackievirus (B6)	99.1% inhibited	45L	2	Kitasato Research Center for Environmental Science	22_0085
	Poliovirus type 1 (Lsc-2ab)	99.7% inhibited	45L	2	Kitasato Research Center for Environmental Science	22_0096
Adhered bacteria	Bacterium enterohemorrhagic escherichia coli (O157)	99.99% inhibited	45L	1	Japan Food Research Laboratories	208120880-001
	Methicillin-resistant staphylococcus aureus (MRSA)	99.99% inhibited	45L	1	Japan Food Research Laboratories	208120880-002
	Staphylococcus aureus	99.99% inhibited	1m ³	24	Kitasato Research Center for Environmental Science	20_0154_2
	Bacillus	99.6% inhibited	45L	0.5	Japan Food Research Laboratories	11000924001-01
	Micrococcus	99.9% inhibited	45L	2	Japan Food Research Laboratories	11000924001-02
	Serratia	99.9% inhibited	45L	2	Japan Food Research Laboratories	11000924001-03
	Kocuria	99.9% inhibited	45L	1	Japan Food Research Laboratories	11000922001-01


Results may vary based on usage, and seasonal and environment variables (temperature and humidity). nanoe™ X and nanoe™ inhibit activity or growth of viruses, but do not prevent infection.




Inhibits activity of airborne mould and adhered mould

nanoe[™]X is effective in removing various airborne mould within a room as well as inhibiting the growth of adhered mould.


How nanoe[™]X Inhibits Growth of Mould



Airborne Mould



Adhered Mould



[Representative evidence]

** : Units based on Panasonic standards

	Mould	Result**	Capacity	Time (Hr.)	Testing organisation	Report No.
Airborne	Cladosporium	99% inhibited	Approx. 23m ³	1	Japan Food Research Laboratories	205061541-001
	Alternaria	Inhibited	Approx. 23m ³	8	Japan Food Research Laboratories	18077411001-0201
Adhered	Aspergillus	Inhibited	Approx. 23m ³	8	Japan Food Research Laboratories	17145307001-0801
	Cladosporium	Inhibited	Approx. 23m ³	8	Japan Food Research Laboratories	17145307001-0901
	Eurotium	Inhibited	Approx. 23m ³	8	Japan Food Research Laboratories	17145307001-1001
	Fusarium	Inhibited	Approx. 23m ³	8	Japan Food Research Laboratories	17145307001-1101
	Mucor	Inhibited	Approx. 23m ³	8	Japan Food Research Laboratories	17145307001-1201
	Penicillium	Inhibited	Approx. 23m ³	8	Japan Food Research Laboratories	17145307001-1301
	Stachybotrys	Inhibited	Approx. 23m ³	8	Japan Food Research Laboratories	17145307001-1401
	Aspergillus	99.5% inhibited	45L	8	Japan Food Research Laboratories	11038081001-02
	Penicillium	99.5% inhibited	45L	4	Japan Food Research Laboratories	11028760001-01
	Fusarium	99.9% inhibited	45L	4	Japan Food Research Laboratories	11018692001-02
	Eurotium	99.9% inhibited	45L	8	Kitasato Research Center for Environmental Science	22_0455
	Mucor	99.9% inhibited	45L	8	Japan Food Research Laboratories	11038080001-01
	Stachybotrys	99.9% inhibited	45L	8	Kitasato Research Center for Environmental Science	22_0455
	Alternaria	99.9% inhibited	45L	16	Japan Food Research Laboratories	11038082001-01

Results may vary based on usage, and seasonal and environment variables (temperature and humidity). nanoe[™]X and nanoe[™] inhibit activity or growth of viruses, but do not prevent infection.



Inhibits pet-derived allergens and major allergens

In addition to allergens from sources such as dog / cat dander, mite faeces / carcasses, and airborne mould, other major allergens are also inhibited.

How nanoe[™]X Inhibits Allergens



[Representative evidence]

** : Units based on Panasonic standards

	Allergens	Result**	Capacity	Time (Hr.)	Testing organisation	Report No.
Mites	Dermatophagoides pteronyssinus	Inhibited	Approx. 23m ³	24	Panasonic Product Analysis Center	4AA33-160615-F01
	Dermatophagoides farinae	Inhibited	Approx. 23m ³	24	Panasonic Product Analysis Center	4AA33-170301-F15
Mould	Alternaria (Sooty moulds)	Inhibited	Approx. 23m ³	24	Panasonic Product Analysis Center	4AA33-160615-F02
	Aspergillus (Aspergillus genus)	Inhibited	Approx. 23m ³	24	Panasonic Product Analysis Center	
	Candida	Inhibited	Approx. 23m ³	24	Panasonic Product Analysis Center	
	Malassezia	Inhibited	Approx. 23m ³	24	Panasonic Product Analysis Center	
Insect	Cockroach	Inhibited	Approx. 23m ³	24	Panasonic Product Analysis Center	4AA33-160615-F03
	Moth	Inhibited	Approx. 23m ³	24		
Animal	Dog (dander)	Inhibited	Approx. 23m ³	24	Panasonic Product Analysis Center	4AA33-160620-F01
	Cat (dander)	Inhibited	Approx. 23m ³	24		


Results may vary based on usage, and seasonal and environment variables (temperature and humidity). nanoe[™]X and nanoe[™] inhibit activity or growth of viruses, but do not prevent infection.



Inhibits pollens globally all year round

nanoe[™]X is effective in inhibiting a variety of pollens globally all year round. The inhibition effect has been confirmed for the 13 varieties of pollens, including those found in Europe and North America.

How nanoe[™]X Inhibits Pollen



[Representative evidence]

** : Units based on Panasonic standards

Pollen Allergens	Result**	Capacity	Time (Hr.)	Testing organisation	Report No.
Cedar	97% inhibited	Approx. 23m ²	8	Panasonic Product Analysis Center	4AA33-151001-F01
Cypress	Inhibited	Approx. 23m ²	24	Panasonic Product Analysis Center	4AA33-151028-F01
Orchard grass	Inhibited	Approx. 23m ²	24		
Ragweed	Inhibited	Approx. 23m ²	24		
Alnus japonica	Inhibited	Approx. 23m ²	24		
Japanese white birch	Inhibited	Approx. 23m ²	24	Panasonic Product Analysis Center	4AA33-160601-F01
Artemisia	Inhibited	Approx. 23m ²	24		
Olive	Inhibited	Approx. 23m ²	24		
Juniper	Inhibited	Approx. 23m ²	24		
Casuarina	Inhibited	Approx. 23m ²	24	Panasonic Product Analysis Center	4AA33-160601-F02
Miscanthus	Inhibited	Approx. 23m ²	24		
Timothy grass	Inhibited	Approx. 23m ²	24		
Humulus japonicus	Inhibited	Approx. 23m ²	24		


Results may vary based on usage, and seasonal and environment variables (temperature and humidity). nanoe™ X and nanoe™ inhibit activity or growth of viruses, but do not prevent infection.




Inhibition of hazardous substances known to be found in PM2.5

Breakdown effects of aromatic carboxylic acid (benzoic acid) and paraffin (hexadecane), harmful substances, have been verified.


How nanoe™ X Inhibits Hazardous Substances



nanoe™ X reliably reaches hazardous substance.




Hydroxyl radicals denature hazardous substances proteins.



Hazardous substance is inhibited.


Aromatic Carboxylic Acid

Benzoic acid



Paraffin

Hexadecane



[Representative evidence]

** : Units based on Panasonic standards

	Hazardous substances	Result**	Capacity	Time (Hr.)	Testing organisation	Report No.
Pollutants	Paraffin (Hexadecane)	99% inhibited	Approx. 23m ²	16	Panasonic Product Analysis Center	Y17NF089
	Aromatic carboxylic acid (Benzoic acid)	99% inhibited	Approx. 23m ²	8	Panasonic Product Analysis Center	Y17NF096
Carcinogen	Benzo [a] anthracene (BaA)	78% inhibited	36L	8	Panasonic Product Analysis Center	Y13NF141
	Benzo [b] fluoranthene (BbF)	79% inhibited	36L	8	Panasonic Product Analysis Center	Y13NF142
	Benzo [a] pyrene (BaP)	97% inhibited	36L	8	Panasonic Product Analysis Center	Y13NF143
	Indeno [1,2,3-cd] pyrene (IcP)	97% inhibited	36L	8	Panasonic Product Analysis Center	Y13NF144
	Dibenzo [a,h] anthracene (Dha)	81% inhibited	36L	8	Panasonic Product Analysis Center	Y13NF145


Results may vary based on usage, and seasonal and environment variables (temperature and humidity). nanoe™ X and nanoe™ inhibit activity or growth of viruses, but do not prevent infection.



Moisturised skin, straighter & sleeker hair

nanoe™ X combines with natural sebum to coat the skin, leading to smooth, well-hydrated skin. Furthermore, the abundant moisture found in nanoe™ X hydrates the hair, contributing to straighter, sleeker hair.

nanoe™ X achieved an improvement in skin moisture content equivalent to a 20 percentage point increase in environmental humidity.



[Representative evidence]

** : Units based on Panasonic standards

Skin and hair	Result**	Capacity	Time (Hr.)	Testing organisation	Report No.
Skin	Effective	Approx. 34m ²	1	Panasonic Product Analysis Center	USG-KT-14K-012-TM
	Effective	Standard household	28 days	FCG Research Institute, Inc.	19104
Hair	Effective	Approx. 46m ²	8 Hr. x 15 days	Panasonic Product Analysis Center	USD-KS-15S-009-TM

Results may vary based on usage, and seasonal and environment variables (temperature and humidity). nanoe™ X and nanoe™ inhibit activity or growth of viruses, but do not prevent infection.

Test reports of nanoe™ X

The effects of nanoe™ X have been proven through experiment tests conducted by institute and laboratory. It has also been verified by the relevant authority.



Indonesia
PT. Anugrah
Analisis Sempurna



Singapore
Temasek Polytechnic



Malaysia
SIRIM Berhad



Vietnam
Pasteur Institute



Thailand
King Mongkut's University
of Technology Thonburi



Inside Cleaning

How inside cleaning works


1 Power "OFF"



First, the air conditioner has to be switched off.

Remark:
Main power must be switched on for the entire duration.

2 nanoe™ X runs on Fan Operation




Fan Operation : ON
Flap : Slightly open
nanoe™ Technology LED : ON

nanoe™ X device applies high voltage to the moisture collected in the air to produce water particles that contain hydroxyl radicals.

The indoor unit will automatically run on Fan Operation for 2.5 hours during the inside cleaning process. The flap will open slightly, allowing airflow to circulate the hydroxyl radicals and perform inside cleaning within the air conditioning unit.

3 Effective inhibition with hydroxyl radicals from nanoe™ X Inside Cleaning*

nanoe™ X inhibits bacteria and viruses through the airflow route within 2.5 hours during the inside cleaning process.




Substance Name	Target Parts	Result	Capacity	Time (Hr.)	Testing Organisation	Report No.
Bacteria <i>Escherichia coli</i> NBRC3301	Filter	99% inhibited [compared to non-operation]	42.8m ³	2.5	Protectea,Ltd	PR190803
	Heat exchanger fin	99% inhibited [compared to non-operation]	42.8m ³	2.5	Protectea,Ltd	PR190803
	Air outlet	99% inhibited [compared to non-operation]	42.8m ³	2.5	Protectea,Ltd	PR191102
Virus <i>Escherichia coli</i> Phage QB NBRC20012	Filter	99% inhibited [compared to non-operation]	42.8m ³	2.5	Protectea,Ltd	PR190803
	Heat exchanger fin	99% inhibited [compared to non-operation]	42.8m ³	2.5	Protectea,Ltd	PR190803
	Air outlet	99% inhibited [compared to non-operation]	42.8m ³	2.5	Protectea,Ltd	PR191102

* Applicable to AERO ELITE INVERTER, PREMIUM INVERTER, STANDARD INVERTER with nanoe™ X and PREMIUM INVERTER HEAT PUMP.



What is PM2.5?

"Particulate matter," also known as PM is made up of a number of components including extremely small particles and liquid droplets. Sized at less than 2.5 micrometers (PM2.5), these particles are said to pose health problems as they can easily enter our lungs.




Sources of PM2.5

PM2.5 can be found suspended in the air, including dust, dirt, smoke and liquid droplets. These fine particles come from man-made sources such as the combustion of fossil fuels, open burning and industrial processes as well as natural ones, which include sea sprays and dust carried by strong winds.



PM2.5 Removal Efficiency Based On Time



[Representative evidence]

** : Units based on Panasonic standards

Substances name	Result**	Capacity	Time (Hr.)	Testing organisation	Report No.
Airborne Cigarette smoke [as PM2.5]	Removed by 99% [compared to the initial concentration]	23m ³	202 mins.	FCG Research Institute, Inc.	25034

Split Type	ELITE INVERTER	AERO ELITE INVERTER	PREMIUM INVERTER	STANDARD INVERTER With Wi-Fi	STANDARD INVERTER With nanoe™X	STANDARD NON-INVERTER	PREMIUM INVERTER HEAT PUMP	STANDARD INVERTER HEAT PUMP
WALL-MOUNTED								
Models	CS-VU9UKH-8 CS-VU12UKH-8 CS-VU18UKH-8	CS-XU9XKH-8 CS-XU12XKH-8 CS-XU18XKH-8 CS-XU24XKH-8	CS-U9XKH-8 CS-U12XKH-8 CS-U18XKH-8 CS-U24XKH-8	CS-WPU9XKH-8 CS-WPU12XKH-8 CS-WPU18XKH-8 CS-WPU24XKH-8	CS-XPU9XKH-8 CS-XPU12XKH-8 CS-XPU18XKH-8 CS-XPU18XKH-8B CS-XPU24XKH-8	CS-N9WKH-8 CS-N12WKH-8 CS-N18XKH-8 CS-N24XKH-8	CS-XZ9XKH-8 CS-XZ12XKH-8 CS-XZ18XKH-8 CS-XZ24XKH-8	CS-YZ9WKH-8 CS-YZ12WKH-8 CS-YZ18XKH-8 CS-YZ24XKH-8
COMFORT								
Radiant Cooling	•							
iAUTO-X	•	•	•				•	
SLEEP	•	•	•	•	•	•	•	•
Inverter Control	•	•	•	•	•		•	•
Powerful Mode				•	•	•		•
Humidity Sensor		•	•				•	
ECO Mode with A.I.		•	•	•	•		•	•
Quiet Mode	•	•	•	•	•	•	•	•
Soft Dry Operation Mode	•	•	•	•	•	•	•	•
Personal Airflow Creation	•	•	•	• (WPU24)	• (XPU18-8B/24)	• (N18/24)	•	• (YZ18)
Airflow Direction Control (Up & Down)				• (WPU9/12/18)	• (XPU9/12/18)	• (N9/12)		• (YZ9/12)
Manual Horizontal Airflow Direction Control				• (WPU9/12/18)	• (XPU9/12/18)	• (N9/12)		• (YZ9/12)
Auto Changeover Mode (Heat Pump)							•	•
Hot Start Control							•	•
CLEANER AIR								
nanoe™X	•	•	•		•		•	
nanoe-G	•	•	•	•	•	•	•	•
Dust Sensor	•							
Anti-Dust Coating	•							
Odour-Removing Function	•	•	•	•	•	•	•	•
Removable, Washable Panel		•	•	•	•	•	•	•
CONVENIENCE								
24-Hour Dual ON & OFF Real Setting Timer	•	•	•	•	•		•	•
24-Hour ON & OFF Real Setting Timer						•		
LCD Wireless Remote Control	•	•	•	•	•	•	•	•
Wireless LAN Remote Control For Internet Connection	• (Optional)	• (Built-in)	• (Optional)	• (Built-in)	• (Optional)		• (Built-in)	• (Optional)
Wired Remote Control	• (Optional)	• (Optional)	• (Optional)	• (Optional)	• (Optional)		• (Optional)	• (Optional)
RELIABILITY								
Random Auto Restart (32 Restart Patterns)	•	•	•	•	•	•	•	•
Blue Fin Condenser	•	•	•	•	•	•	•	•
Long Piping (Numbers indicate the maximum pipe length)	20m (VU9/12) 30m (VU18)	20m (XU9/12) 30m (XU18)	20m (U9/12) 30m (U18/24)	20m (WPU9/12) 30m (WPU18/24)	20m (XPU9/12) 30m (XPU18/18-8B/24)	20m (N9/12) 30m (N18/24)	20m (XZ9/12) 30m (XZ18/24)	15m (YZ9/12) 30m (YZ18)
Top-Panel Maintenance Access	•	•	•	•	•	•	•	•
Self-Diagnostic Function	•	•	•	•	•		•	•

COMFORT

RADIANT COOLING
Cools the ceiling and walls first, providing continuous cooling comfort without direct airflow.

iAUTO-X
Come home to ultra-fast cooling, and then enjoy continuous comfort. Shower Cooling that evenly distributes cool air. Reactivate faster cooling with a second press of the iAUTO-X button.

SLEEP MODE
Delays off timer with temperature control for better sleep.

INVERTER CONTROL
Varies the rotation speed of the compressor for higher energy savings.

POWERFUL MODE
Press the POWERFUL mode to cool your room faster during startup to provides fast comfort with full power and a strong airflow.

iAUTO
Automatically switches fan speed for faster cooling with just one touch of a button.

HUMIDITY SENSOR
Controls relative humidity below 60% for ideal sleep.

ECO MODE WITH A.I.
Auto-adjusts to the optimal ECO level based on heat load conditions and air conditioning cooling capacity.

QUIET MODE
Enjoy the comfort of running your air conditioner at night for a relaxing sleep.

SOFT DRY OPERATION MODE
Starts with cooling to dehumidify, then provides continuous breeze at a low frequency to keep a room dry without much change to the temperature.

PERSONAL AIRFLOW CREATION
Vertical and horizontal airflow patterns can be combined as desired to achieve optimum comfort, with operation possible by remote even from a distance.

AIRFLOW DIRECTION CONTROL (UP & DOWN)
Vertical airflow patterns can be controlled with operation by remote, even from a distance.

MANUAL HORIZONTAL AIRFLOW DIRECTION CONTROL
Horizontal airflow patterns can be manually adjusted.

AUTO CHANGEOVER MODE (HEAT PUMP)
In Auto Mode the unit will select if heating or cooling is required.

HOT START CONTROL
On the start of the heating cycle and after the defrost cycle, the indoor fan will start up once the indoor heat exchanger is warm.

CLEANER AIR

nanoe™X
nanoe™X effectively deodorises and inhibits, for a fresher and cleaner living space.

nanoe-G
nanoe-G works effectively on removing dust particles as small as PM2.5.

DUST SENSOR
Monitors particle concentration levels and turns on nanoe-G if levels are high.

REMOVABLE, WASHABLE PANEL
Anti-dust coating prevents dust from accumulating on cross flow fan by keeping it clean.

ANTI-DUST COATING
Gives you easy access to the filter as well as making the unit easy to clean.

ODOUR-REMOVING FUNCTION
With this function, there's no unpleasant odor when the unit starts up. That's because the fan remains off momentarily, while the source of the odour inside the air conditioner is suppressed.

The unit must be in cool or dry mode and the fan speed must be set to automatic.

CONVENIENCE

24-HOUR DUAL ON & OFF REAL SETTING TIMER
This feature enables you to preset two different sets of start/stop operation timer (hour and minute) within a 24-hour time frame.

24-HOUR ON & OFF REAL SETTING TIMER
The exact operating time (hour and minute) of the air conditioner can be set in advance. From here on, the unit will operate in accordance to these preset hours every day until the system is reset.

LCD WIRELESS REMOTE CONTROL
Easy control of the unit from anywhere in the room.

Wireless LAN REMOTE CONTROL FOR INTERNET CONNECTION
Control air conditioners remotely by turning your mobile device into a remote controller using internet connection.

WIRED REMOTE CONTROL
Control at the unit from fixed location where wired remote controller is installed.

RELIABILITY







































































RANDOM AUTO RESTART
When multiple units are connected and there is a power outage, they will turn on at different times in order to not spike the power supply.

BLUE FIN CONDENSER
Extra protection from the elements with a longer lasting coil.

LONG PIPING
Long piping offers more flexible installation options.

TOP-PANEL MAINTENANCE ACCESS
Easy access for maintenance.

SELF-DIAGNOSTIC FUNCTION
Should a malfunction occur, the unit diagnoses the problem and shows the corresponding alphanumeric code. This allows for quicker servicing.

Horse Power (HP)	1.0HP	1.5HP	2.0HP	2.5HP	Features
Capacity (Btu/h)	9,000	12,000	18,000	24,000	
WALL-MOUNTED ELITE INVERTER Page 34-35	 CS-VU9UKH-8 <small>(CU-VU9UKH-8)</small>	 CS-VU12UKH-8 <small>(CU-VU12UKH-8)</small>	 CS-VU18UKH-8 <small>(CU-VU18UKH-8)</small>	 CS-VU24UKH-8 <small>(CU-VU24UKH-8)</small>	  SKYWING   XTRA QUIET 18dB <small>(CS-VU9UKH-8)</small>
WALL-MOUNTED AERO ELITE INVERTER Page 36-37	 CS-XU9XKH-8 <small>(CU-XU9XKH-8)</small>	 CS-XU12XKH-8 <small>(CU-XU12XKH-8)</small>	 CS-XU18XKH-8 <small>(CU-XU18XKH-8)</small>	 CS-XU24XKH-8 <small>(CU-XU24XKH-8)</small>	   NEW AEROWINGS    
WALL-MOUNTED PREMIUM INVERTER Page 38-39	 CS-U9XKH-8 <small>(CU-U9XKH-8)</small>	 CS-U12XKH-8 <small>(CU-U12XKH-8)</small>	 CS-U18XKH-8 <small>(CU-U18XKH-8)</small>	 CS-U24XKH-8 <small>(CU-U24XKH-8)</small>	  NEW AEROWINGS    
WALL-MOUNTED STANDARD INVERTER With Wi-Fi Page 40-41	 CS-WPU9XKH-8 <small>(CU-WPU9XKH-8)</small>	 CS-WPU12XKH-8 <small>(CU-WPU12XKH-8)</small>	 CS-WPU18XKH-8 <small>(CU-WPU18XKH-8)</small>	 CS-WPU24XKH-8 <small>(CU-WPU24XKH-8)</small>	  BIG FLAP <small>(CS-WPU9/12/18XKH-8)</small> AEROWINGS <small>(CS-WPU24XKH-8)</small>   
WALL-MOUNTED STANDARD INVERTER With nanoe™ X Page 42-43	 CS-XPU9XKH-8 <small>(CU-XPU9XKH-8)</small>	 CS-XPU12XKH-8 <small>(CU-XPU12XKH-8)</small>	 CS-XPU18XKH-8 <small>(CU-XPU18XKH-8)</small>  CS-XPU18XKH-8B <small>(CU-XPU18XKH-8B)</small>	 CS-XPU24XKH-8 <small>(CU-XPU24XKH-8)</small>	  BIG FLAP <small>(CS-XPU9/12/18XKH-8)</small> AEROWINGS <small>(CS-XPU18XKH-8B, CS-XPU24XKH-8)</small>   
WALL-MOUNTED STANDARD NON-INVERTER Page 44-45	 CS-N9WKH-8 <small>(CU-N9WKH-8)</small>	 CS-N12WKH-8 <small>(CU-N12WKH-8)</small>	 CS-N18XKH-8 <small>(CU-N18XKH-8)</small>	 CS-N24XKH-8 <small>(CU-N24XKH-8)</small>	 BIG FLAP <small>(CS-N9/12WKH-8)</small> AEROWINGS <small>(CS-N18/24XKH-8)</small> 
WALL-MOUNTED PREMIUM INVERTER HEAT PUMP Page 46-47	 CS-XZ9XKH-8 <small>(CU-XZ9XKH-8)</small>	 CS-XZ12XKH-8 <small>(CU-XZ12XKH-8)</small>	 CS-XZ18XKH-8 <small>(CU-XZ18XKH-8)</small>	 CS-XZ24XKH-8 <small>(CU-XZ24XKH-8)</small>	   NEW AEROWINGS    
WALL-MOUNTED STANDARD INVERTER HEAT PUMP Page 48-49	 CS-YZ9WKH-8 <small>(CU-YZ9WKH-8)</small>	 CS-YZ12WKH-8 <small>(CU-YZ12WKH-8)</small>	 CS-YZ18XKH-8 <small>(CU-YZ18XKH-8)</small>	 CS-YZ24XKH-8 <small>(CU-YZ24XKH-8)</small>	 BIG FLAP <small>(CS-YZ9/12WKH-8)</small> AEROWINGS <small>(CS-YZ18XKH-8)</small> 