

MULTI-SPLIT COMBINATION CAPACITY TABLE

XU Series Multi-Split System

CU-2XU20YBZ

INDOOR UNIT COMBINATION		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
1 Room	2.8	2.8	2.80				2.80	1.10 ~ 3.50	610	220 ~ 820	2.9	2.8	1.6
	3.5	3.5	3.50				3.50	1.10 ~ 4.20	820	220 ~ 1,220	3.9	3.6	2.0
	5.0	5.0	4.50				4.50	1.20 ~ 5.60	1,330	230 ~ 1,690	6.1	5.6	2.5
	6.0	6.0	4.50				4.50	1.20 ~ 6.20	1,300	230 ~ 1,820	6.0	5.5	2.5
2 Rooms	2.8 + 2.8	5.6	2.10	2.10			4.20	1.50 ~ 6.30	830	260 ~ 1,800	4.0	3.7	1.4 + 1.4
	2.8 + 3.5	6.3	1.87	2.33			4.20	1.50 ~ 6.35	830	260 ~ 1,800	4.0	3.7	1.2 + 1.5
	2.8 + 5.0	7.8	1.51	2.69			4.20	1.50 ~ 6.40	830	250 ~ 1,800	4.0	3.7	1.0 + 1.6
	2.8 + 6.0	8.8	1.37	2.93			4.30	1.50 ~ 6.60	850	250 ~ 1,800	4.1	3.8	0.9 + 1.7
	3.5 + 3.5	7.0	2.10	2.10			4.20	1.50 ~ 6.40	830	260 ~ 1,800	4.0	3.7	1.4 + 1.4
	3.5 + 5.0	8.5	1.73	2.47			4.20	1.50 ~ 6.50	830	250 ~ 1,800	4.0	3.7	1.1 + 1.5
	3.5 + 6.0	9.5	1.66	2.84			4.50	1.50 ~ 6.70	900	250 ~ 1,800	4.3	4.0	1.1 + 1.7

CU-3XU28YBZ

INDOOR UNIT COMBINATION Cooling		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
1 Room	2.8	2.8	2.80				2.80	1.70 ~ 3.93	610	380 ~ 1,090	3.0	2.8	1.6
	3.5	3.5	3.50				3.50	1.70 ~ 5.10	820	380 ~ 1,440	4.0	3.7	2.0
	5.0	5.0	5.00				5.00	1.90 ~ 6.55	1,370	400 ~ 2,280	6.3	5.8	2.7
	6.0	6.0	6.00				6.00	1.90 ~ 7.57	1,780	400 ~ 2,510	8.1	7.5	3.3
	7.1	7.1	7.10				7.10	1.90 ~ 8.03	2,250	400 ~ 2,850	10.3	9.5	4.1
2 Rooms	2.8 + 2.8	5.6	2.80	2.80			5.60	1.90 ~ 7.90	1,360	400 ~ 2,400	6.4	5.8	1.6 + 1.6
	2.8 + 3.5	6.3	2.76	3.44			6.20	1.90 ~ 8.25	1,600	400 ~ 2,600	7.5	6.9	1.6 + 2.0
	2.8 + 5.0	7.8	2.23	3.97			6.20	2.80 ~ 8.95	1,490	520 ~ 2,700	7.0	6.4	1.5 + 2.3
	2.8 + 6.0	8.8	2.00	4.30			6.30	2.80 ~ 9.20	1,460	520 ~ 2,680	6.8	6.3	1.3 + 2.4
	2.8 + 7.1	9.9	1.80	4.55			6.35	2.80 ~ 9.25	1,480	520 ~ 2,690	6.9	6.4	1.2 + 2.5
	3.5 + 3.5	7.0	3.10	3.10			6.20	1.90 ~ 8.30	1,600	400 ~ 2,600	7.5	6.9	1.7 + 1.7
	3.5 + 5.0	8.5	2.59	3.71			6.30	2.80 ~ 9.00	1,530	520 ~ 2,700	7.2	6.6	1.6 + 2.2
	3.5 + 6.0	9.5	2.34	4.01			6.35	2.80 ~ 9.25	1,480	520 ~ 2,690	6.9	6.4	1.5 + 2.3
	3.5 + 7.1	10.6	2.11	4.29			6.40	2.80 ~ 9.30	1,500	520 ~ 2,700	7.0	6.4	1.4 + 2.4
	5.0 + 5.0	10.0	3.20	3.20			6.40	2.80 ~ 9.40	1,460	520 ~ 2,700	6.8	6.3	1.8 + 1.8
	5.0 + 6.0	11.0	2.95	3.55			6.50	2.80 ~ 9.55	1,510	520 ~ 2,740	7.1	6.5	1.7 + 2.1
	5.0 + 7.1	12.1	2.69	3.81			6.50	2.80 ~ 9.60	1,500	520 ~ 2,740	7.0	6.4	1.6 + 2.2
6.0 + 6.0	12.0	3.30	3.30			6.60	2.80 ~ 9.80	1,500	520 ~ 2,740	7.0	6.4	1.9 + 1.9	
3 Rooms	2.8 + 2.8 + 2.8	8.4	2.07	2.07	2.07		6.20	2.80 ~ 9.20	1,240	530 ~ 2,600	5.8	5.3	1.3 + 1.3 + 1.3
	2.8 + 2.8 + 3.5	9.1	1.91	1.91	2.38		6.20	2.80 ~ 9.25	1,240	530 ~ 2,600	5.8	5.3	1.2 + 1.2 + 1.5
	2.8 + 2.8 + 5.0	10.6	1.66	1.66	2.97		6.30	2.80 ~ 9.40	1,270	520 ~ 2,620	5.9	5.4	1.1 + 1.1 + 1.7
	2.8 + 2.8 + 6.0	11.6	1.57	1.57	3.36		6.50	2.80 ~ 9.70	1,310	520 ~ 2,500	6.1	5.6	1.0 + 1.0 + 1.9
	2.8 + 2.8 + 7.1	12.7	1.46	1.46	3.69		6.60	2.80 ~ 9.80	1,340	520 ~ 2,500	6.2	5.7	0.9 + 0.9 + 2.1
	2.8 + 3.5 + 3.5	9.8	1.77	2.21	2.21		6.20	2.80 ~ 9.30	1,240	530 ~ 2,600	5.8	5.3	1.1 + 1.4 + 1.4
	2.8 + 3.5 + 5.0	11.3	1.56	1.95	2.79		6.30	2.80 ~ 9.45	1,270	520 ~ 2,620	5.9	5.4	1.0 + 1.3 + 1.6
	2.8 + 3.5 + 6.0	12.3	1.48	1.85	3.17		6.50	2.80 ~ 9.75	1,310	520 ~ 2,500	6.1	5.6	0.9 + 1.2 + 1.8
	3.5 + 3.5 + 3.5	10.5	2.08	2.08	2.08		6.25	2.80 ~ 9.35	1,260	530 ~ 2,600	5.8	5.4	1.3 + 1.3 + 1.3
3.5 + 3.5 + 5.0	12.0	1.84	1.84	2.63		6.30	2.80 ~ 9.50	1,270	520 ~ 2,620	5.9	5.4	1.2 + 1.2 + 1.6	

MULTI-SPLIT COMBINATION CAPACITY TABLE

CU-4XU33YBZ

INDOOR UNIT COMBINATION Cooling		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h	
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V		
1 Room	2.8	2.8	2.80				2.80	1.70 ~ 3.93	610	380 ~ 1,090	3.0	2.8	1.6	
	3.5	3.5	3.50				3.50	1.70 ~ 5.10	820	380 ~ 1,440	4.0	3.7	2.0	
	5.0	5.0	5.00				5.00	1.90 ~ 6.55	1,370	400 ~ 2,280	6.3	5.8	2.7	
	6.0	6.0	6.00				6.00	1.90 ~ 7.57	1,780	400 ~ 2,510	8.1	7.5	3.3	
	7.1	7.1	7.10				7.10	1.90 ~ 8.03	2,250	400 ~ 2,850	10.3	9.5	4.1	
2 Rooms	2.8 + 2.8	5.6	2.80	2.80			5.60	1.90 ~ 7.70	1,390	400 ~ 2,470	6.6	6.0	1.6 + 1.6	
	2.8 + 3.5	6.3	2.80	3.50			6.30	1.90 ~ 8.35	1,750	400 ~ 2,980	8.2	7.4	1.6 + 2.0	
	2.8 + 5.0	7.8	2.37	4.23			6.60	2.80 ~ 9.15	1,690	520 ~ 3,020	8.0	7.3	1.5 + 2.4	
	2.8 + 6.0	8.8	2.10	4.50			6.60	2.80 ~ 9.50	1,610	520 ~ 3,030	7.6	6.9	1.4 + 2.5	
	2.8 + 7.1	9.9	1.87	4.73			6.60	2.80 ~ 9.55	1,600	520 ~ 3,030	7.6	6.9	1.2 + 2.6	
	3.5 + 3.5	7.0	3.30	3.30			6.60	1.90 ~ 8.40	1,880	400 ~ 2,980	8.8	8.0	1.9 + 1.9	
	3.5 + 5.0	8.5	2.72	3.88			6.60	2.80 ~ 9.20	1,680	520 ~ 3,020	7.9	7.2	1.6 + 2.3	
	3.5 + 6.0	9.5	2.43	4.17			6.60	2.80 ~ 9.55	1,600	520 ~ 3,030	7.6	6.9	1.5 + 2.4	
	3.5 + 7.1	10.6	2.18	4.42			6.60	2.80 ~ 9.60	1,590	520 ~ 3,030	7.5	6.8	1.4 + 2.4	
	5.0 + 5.0	10.0	3.30	3.30			6.60	2.80 ~ 9.70	1,570	520 ~ 3,050	7.4	6.7	1.9 + 1.9	
	5.0 + 6.0	11.0	3.00	3.60			6.60	2.80 ~ 9.85	1,540	520 ~ 3,070	7.3	6.6	1.7 + 2.1	
	5.0 + 7.1	12.1	2.75	3.90			6.65	2.80 ~ 9.90	1,560	520 ~ 3,070	7.4	6.7	1.6 + 2.3	
	6.0 + 6.0	12.0	3.35	3.35			6.70	2.80 ~ 10.20	1,560	520 ~ 3,000	7.4	6.7	1.9 + 1.9	
	6.0 + 7.1	13.1	3.09	3.66			6.75	2.80 ~ 10.25	1,580	520 ~ 3,000	7.5	6.8	1.7 + 2.1	
	7.1 + 7.1	14.2	3.40	3.40			6.80	2.80 ~ 10.30	1,600	520 ~ 3,000	7.6	6.9	1.9 + 1.9	
	3 Rooms	2.8 + 2.8 + 2.8	8.4	2.20	2.20	2.20		6.60	2.80 ~ 9.75	1,520	530 ~ 3,010	7.1	6.5	1.4 + 1.4 + 1.4
		2.8 + 2.8 + 3.5	9.1	2.03	2.03	2.54		6.60	2.80 ~ 9.80	1,510	530 ~ 3,010	7.1	6.5	1.3 + 1.3 + 1.6
2.8 + 2.8 + 5.0		10.6	1.74	1.74	3.11		6.60	2.80 ~ 10.00	1,480	520 ~ 3,100	6.9	6.4	1.1 + 1.1 + 1.8	
2.8 + 2.8 + 6.0		11.6	1.59	1.59	3.41		6.60	2.80 ~ 10.35	1,400	520 ~ 3,080	6.6	6.0	1.0 + 1.0 + 2.0	
2.8 + 2.8 + 7.1		12.7	1.46	1.46	3.69		6.60	2.80 ~ 10.40	1,390	520 ~ 3,080	6.5	6.0	0.9 + 0.9 + 2.1	
2.8 + 3.5 + 3.5		9.8	1.89	2.36	2.36		6.60	2.80 ~ 9.85	1,500	530 ~ 3,010	7.0	6.4	1.2 + 1.5 + 1.5	
2.8 + 3.5 + 5.0		11.3	1.64	2.04	2.92		6.60	2.80 ~ 10.05	1,470	520 ~ 3,100	6.9	6.3	1.0 + 1.3 + 1.7	
2.8 + 3.5 + 6.0		12.3	1.50	1.88	3.22		6.60	2.80 ~ 10.40	1,390	520 ~ 3,080	6.5	6.0	1.0 + 1.2 + 1.8	
2.8 + 3.5 + 7.1		13.4	1.38	1.72	3.50		6.60	2.80 ~ 10.45	1,380	520 ~ 3,080	6.5	5.9	0.9 + 1.1 + 2.0	
2.8 + 5.0 + 5.0		12.8	1.44	2.58	2.58		6.60	2.80 ~ 10.35	1,440	520 ~ 3,090	6.7	6.2	0.9 + 1.6 + 1.6	
2.8 + 5.0 + 6.0		13.8	1.34	2.39	2.87		6.60	2.80 ~ 10.70	1,340	520 ~ 3,090	6.3	5.8	0.8 + 1.5 + 1.7	
2.8 + 5.0 + 7.1		14.9	1.25	2.23	3.17		6.65	2.80 ~ 10.75	1,360	520 ~ 3,090	6.4	5.8	0.8 + 1.5 + 1.8	
2.8 + 6.0 + 6.0		14.8	1.26	2.70	2.70		6.65	2.80 ~ 10.65	1,430	520 ~ 3,090	6.7	6.1	0.8 + 1.6 + 1.6	
2.8 + 6.0 + 7.1		15.9	1.18	2.53	2.99		6.70	2.80 ~ 10.70	1,450	520 ~ 3,090	6.8	6.2	0.7 + 1.6 + 1.7	
2.8 + 7.1 + 7.1		17.0	1.12	2.84	2.84		6.80	2.80 ~ 10.80	1,490	520 ~ 3,090	7.0	6.4	0.7 + 1.7 + 1.7	
3.5 + 3.5 + 3.5		10.5	2.20	2.20	2.20		6.60	2.80 ~ 9.90	1,490	530 ~ 3,010	7.0	6.4	1.4 + 1.4 + 1.4	
3.5 + 3.5 + 5.0		12.0	1.93	1.93	2.75		6.60	2.80 ~ 10.10	1,460	520 ~ 3,100	6.8	6.3	1.2 + 1.2 + 1.6	
3.5 + 3.5 + 6.0		13.0	1.78	1.78	3.05		6.60	2.80 ~ 10.45	1,380	520 ~ 3,080	6.5	5.9	1.1 + 1.1 + 1.7	
3.5 + 3.5 + 7.1		14.1	1.64	1.64	3.32		6.60	2.80 ~ 10.50	1,370	520 ~ 3,080	6.4	5.9	1.0 + 1.0 + 1.9	
3.5 + 5.0 + 5.0		13.5	1.71	2.44	2.44		6.60	2.80 ~ 10.40	1,430	520 ~ 3,100	6.7	6.1	1.1 + 1.5 + 1.5	
3.5 + 5.0 + 6.0		14.5	1.61	2.29	2.75		6.65	2.80 ~ 10.75	1,360	520 ~ 3,090	6.4	5.8	1.0 + 1.5 + 1.6	
3.5 + 5.0 + 7.1		15.6	1.50	2.15	3.05		6.70	2.80 ~ 10.80	1,380	520 ~ 3,090	6.5	5.9	1.0 + 1.4 + 1.7	
3.5 + 6.0 + 6.0		15.5	1.51	2.59	2.59		6.70	2.80 ~ 10.70	1,450	520 ~ 3,090	6.8	6.2	1.0 + 1.6 + 1.6	
3.5 + 6.0 + 7.1		16.6	1.42	2.44	2.89		6.75	2.80 ~ 10.75	1,470	520 ~ 3,090	6.9	6.3	0.9 + 1.5 + 1.7	
5.0 + 5.0 + 5.0		15.0	2.22	2.22	2.22		6.65	2.80 ~ 10.45	1,420	520 ~ 3,100	6.7	6.1	1.4 + 1.4 + 1.4	
5.0 + 5.0 + 6.0		16.0	2.09	2.09	2.51		6.70	2.80 ~ 10.85	1,450	520 ~ 3,110	6.8	6.2	1.4 + 1.4 + 1.5	
5.0 + 5.0 + 7.1		17.1	1.99	1.99	2.82		6.80	2.80 ~ 10.90	1,500	520 ~ 3,120	7.0	6.4	1.3 + 1.3 + 1.7	
5.0 + 6.0 + 6.0		17.0	2.01	2.42	2.42		6.85	2.80 ~ 10.95	1,500	520 ~ 3,140	7.0	6.4	1.3 + 1.5 + 1.5	

XU Series Multi-Split System

CU-4XU33YBZ

INDOOR UNIT COMBINATION		Total	Cooling Capacity [kW]						Input Power [W]		Current [50Hz] [A]		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
4 Rooms	2.8 + 2.8 + 2.8 + 2.8	11.2	1.65	1.65	1.65	1.65	6.55	2.80 ~ 10.60	1,330	530 ~ 3,030	6.2	5.7	1.1 + 1.1 + 1.1 + 1.1
	2.8 + 2.8 + 2.8 + 3.5	11.9	1.60	1.60	1.60	2.00	6.55	2.80 ~ 10.65	1,330	530 ~ 3,030	6.2	5.7	1.0 + 1.0 + 1.0 + 1.3
	2.8 + 2.8 + 2.8 + 5.0	13.4	1.49	1.49	1.49	2.33	6.65	2.80 ~ 10.75	1,340	520 ~ 2,970	6.2	5.7	0.9 + 0.9 + 0.9 + 1.5
	2.8 + 2.8 + 2.8 + 6.0	14.4	1.31	1.31	1.31	2.87	6.75	2.80 ~ 10.85	1,350	520 ~ 2,980	6.3	5.7	0.8 + 0.8 + 0.8 + 1.7
	2.8 + 2.8 + 2.8 + 7.1	15.5	1.21	1.21	1.21	3.17	6.80	2.80 ~ 10.90	1,350	520 ~ 2,980	6.3	5.7	0.8 + 0.8 + 0.8 + 1.8
	2.8 + 2.8 + 3.5 + 3.5	12.6	1.11	1.11	1.11	3.47	6.55	2.80 ~ 10.70	1,330	530 ~ 3,030	6.2	5.7	0.7 + 0.7 + 0.7 + 2.0
	2.8 + 2.8 + 3.5 + 5.0	14.1	1.01	1.01	1.01	3.77	6.65	2.80 ~ 10.80	1,340	520 ~ 2,970	6.2	5.7	0.7 + 0.7 + 0.7 + 2.2
	2.8 + 2.8 + 3.5 + 6.0	15.1	1.51	1.51	1.89	1.89	6.75	2.80 ~ 10.90	1,360	520 ~ 2,980	6.3	5.8	1.0 + 1.0 + 1.2 + 1.2
	2.8 + 2.8 + 3.5 + 7.1	16.2	1.41	1.41	1.77	2.21	6.80	2.80 ~ 10.95	1,360	520 ~ 2,980	6.3	5.8	0.9 + 0.9 + 1.1 + 1.4
	2.8 + 2.8 + 5.0 + 5.0	15.6	1.25	1.25	1.56	2.74	6.70	2.80 ~ 10.90	1,360	520 ~ 2,980	6.3	5.8	0.8 + 0.8 + 1.0 + 1.6
	2.8 + 2.8 + 5.0 + 6.0	16.6	1.16	1.16	1.44	3.04	6.80	2.80 ~ 11.00	1,380	520 ~ 2,990	6.4	5.9	0.7 + 0.7 + 0.9 + 1.7
	2.8 + 2.8 + 6.0 + 6.0	17.6	1.07	1.07	1.33	3.33	7.00	2.80 ~ 11.20	1,440	520 ~ 3,000	6.7	6.1	0.7 + 0.7 + 0.8 + 1.9
	2.8 + 3.5 + 3.5 + 3.5	13.3	0.97	0.97	1.21	3.65	6.60	2.80 ~ 10.75	1,340	530 ~ 3,030	6.2	5.7	0.7 + 0.7 + 0.8 + 2.1
	2.8 + 3.5 + 3.5 + 5.0	14.8	1.33	1.33	2.07	2.07	6.70	2.80 ~ 10.85	1,340	520 ~ 2,970	6.2	5.7	0.8 + 0.8 + 1.3 + 1.3
	2.8 + 3.5 + 3.5 + 6.0	15.8	1.18	1.18	1.85	2.59	6.80	2.80 ~ 10.95	1,360	520 ~ 2,980	6.3	5.8	0.7 + 0.7 + 1.2 + 1.6
	2.8 + 3.5 + 3.5 + 7.1	16.9	1.10	1.10	1.72	2.88	6.85	2.80 ~ 11.00	1,390	520 ~ 2,980	6.4	5.9	0.7 + 0.7 + 1.1 + 1.7
	2.8 + 3.5 + 5.0 + 5.0	16.3	1.02	1.02	1.58	3.18	6.70	2.80 ~ 10.95	1,360	520 ~ 2,980	6.3	5.8	0.7 + 0.7 + 1.0 + 1.8
	2.8 + 3.5 + 5.0 + 6.0	17.3	1.07	1.07	2.33	2.33	6.80	2.80 ~ 11.05	1,380	520 ~ 2,990	6.4	5.9	0.7 + 0.7 + 1.5 + 1.5
	3.5 + 3.5 + 3.5 + 3.5	14.0	1.00	1.00	2.18	2.62	6.60	2.80 ~ 10.80	1,330	530 ~ 3,030	6.2	5.7	0.7 + 0.7 + 1.4 + 1.6
	3.5 + 3.5 + 3.5 + 5.0	15.5	1.43	1.79	1.79	1.79	6.70	2.80 ~ 10.90	1,340	520 ~ 2,970	6.2	5.7	0.9 + 1.2 + 1.2 + 1.2
	3.5 + 3.5 + 3.5 + 6.0	16.5	1.34	1.68	1.68	2.10	6.80	2.80 ~ 11.00	1,360	520 ~ 2,980	6.3	5.8	0.8 + 1.1 + 1.1 + 1.4
	3.5 + 3.5 + 3.5 + 7.1	17.6	1.20	1.49	1.49	2.62	6.85	2.80 ~ 11.05	1,390	520 ~ 2,980	6.4	5.9	0.7 + 0.9 + 0.9 + 1.6
	3.5 + 3.5 + 5.0 + 5.0	17.0	1.11	1.39	1.39	2.91	6.70	2.80 ~ 11.00	1,360	520 ~ 2,980	6.3	5.8	0.7 + 0.9 + 0.9 + 1.7

CU-4XU38YBZ

INDOOR UNIT COMBINATION		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
1 Room	Cooling												
	2.8	2.8	2.80				2.80	1.70 ~ 3.93	610	380 ~ 1,090	3.0	2.8	1.6
	3.5	3.5	3.50				3.50	1.70 ~ 5.10	820	380 ~ 1,440	4.0	3.7	2.0
	5.0	5.0	5.00				5.00	1.90 ~ 6.55	1,200	400 ~ 2,280	5.5	5.1	2.7
	6.0	6.0	6.00				6.00	1.90 ~ 7.57	1,460	400 ~ 2,510	6.7	6.2	3.3
	7.1	7.1	7.10				7.10	1.90 ~ 8.03	2,250	400 ~ 2,850	10.3	9.5	4.1
2 Rooms	2.8 + 2.8	5.6	2.80	2.80			5.60	1.90 ~ 8.40	1,320	400 ~ 2,600	6.2	5.7	1.6 + 1.6
	2.8 + 3.5	6.3	2.80	3.50			6.30	1.90 ~ 8.90	1,600	400 ~ 2,850	7.5	6.9	1.6 + 2.0
	2.8 + 5.0	7.8	2.66	4.74			7.40	2.90 ~ 9.55	1,930	520 ~ 2,950	8.9	8.2	1.6 + 2.6
	2.8 + 6.0	8.8	2.35	5.05			7.40	2.90 ~ 10.00	1,880	520 ~ 2,970	8.7	8.0	1.5 + 2.8
	2.8 + 7.1	9.9	2.09	5.31			7.40	2.90 ~ 10.05	1,870	520 ~ 2,970	8.7	7.9	1.4 + 2.9
	3.5 + 3.5	7.0	3.50	3.50			7.00	1.90 ~ 9.00	1,990	400 ~ 2,850	9.2	8.5	2.0 + 2.0
	3.5 + 5.0	8.5	3.05	4.35			7.40	2.90 ~ 9.60	1,920	520 ~ 2,950	8.9	8.2	1.7 + 2.4
	3.5 + 6.0	9.5	2.73	4.67			7.40	2.90 ~ 10.05	1,880	520 ~ 2,970	8.7	8.0	1.6 + 2.5
	3.5 + 7.1	10.6	2.44	4.96			7.40	2.90 ~ 10.10	1,870	520 ~ 2,970	8.7	7.9	1.5 + 2.7
	5.0 + 5.0	10.0	3.70	3.70			7.40	2.90 ~ 9.70	1,890	520 ~ 3,000	8.8	8.0	2.2 + 2.2
	5.0 + 6.0	11.0	3.39	4.06			7.45	2.90 ~ 10.15	1,860	520 ~ 3,010	8.6	7.9	1.9 + 2.3
	5.0 + 7.1	12.1	3.10	4.40			7.50	2.90 ~ 10.20	1,880	520 ~ 3,010	8.7	8.0	1.7 + 2.4
	6.0 + 6.0	12.0	3.75	3.75			7.50	2.90 ~ 10.50	1,820	520 ~ 3,050	8.4	7.7	2.2 + 2.2
	6.0 + 7.1	13.1	3.46	4.09			7.55	2.90 ~ 10.55	1,840	520 ~ 3,050	8.5	7.8	2.0 + 2.3
	7.1 + 7.1	14.2	3.80	3.80			7.60	2.90 ~ 10.60	1,860	520 ~ 3,050	8.6	7.9	2.2 + 2.2

MULTI-SPLIT COMBINATION CAPACITY TABLE

CU-4XU38YBZ

INDOOR UNIT COMBINATION		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
3 Rooms	2.8 + 2.8 + 2.8	8.4	2.47	2.47	2.47		7.40	2.90 ~ 10.05	1,800	530 ~ 3,000	8.3	7.7	1.5 + 1.5 + 1.5
	2.8 + 2.8 + 3.5	9.1	2.28	2.28	2.85		7.40	2.90 ~ 10.10	1,790	530 ~ 3,000	8.3	7.6	1.5 + 1.5 + 1.7
	2.8 + 2.8 + 5.0	10.6	1.95	1.95	3.49		7.40	2.90 ~ 10.40	1,710	520 ~ 3,030	8.0	7.3	1.3 + 1.3 + 2.0
	2.8 + 2.8 + 6.0	11.6	1.79	1.79	3.83		7.40	2.90 ~ 10.55	1,730	520 ~ 3,050	8.1	7.4	1.2 + 1.2 + 2.2
	2.8 + 2.8 + 7.1	12.7	1.63	1.63	4.14		7.40	2.90 ~ 10.60	1,720	520 ~ 3,050	8.1	7.4	1.0 + 1.0 + 2.4
	2.8 + 3.5 + 3.5	9.8	2.11	2.64	2.64		7.40	2.90 ~ 10.15	1,780	530 ~ 3,000	8.3	7.6	1.4 + 1.6 + 1.6
	2.8 + 3.5 + 5.0	11.3	1.83	2.29	3.27		7.40	2.90 ~ 10.45	1,700	520 ~ 3,030	8.0	7.3	1.2 + 1.5 + 1.9
	2.8 + 3.5 + 6.0	12.3	1.68	2.11	3.61		7.40	2.90 ~ 10.60	1,710	520 ~ 3,050	8.0	7.3	1.1 + 1.4 + 2.1
	2.8 + 3.5 + 7.1	13.4	1.56	1.95	3.95		7.45	2.90 ~ 10.65	1,730	520 ~ 3,050	8.1	7.4	1.0 + 1.3 + 2.3
	2.8 + 5.0 + 5.0	12.8	1.62	2.89	2.89		7.40	2.90 ~ 10.60	1,710	520 ~ 3,050	8.0	7.3	1.0 + 1.7 + 1.7
	2.8 + 5.0 + 6.0	13.8	1.51	2.70	3.24		7.45	2.90 ~ 10.90	1,670	520 ~ 3,100	7.8	7.2	1.0 + 1.6 + 1.8
	2.8 + 5.0 + 7.1	14.9	1.41	2.52	3.57		7.50	2.90 ~ 10.95	1,690	520 ~ 3,100	7.9	7.3	0.9 + 1.5 + 2.1
	2.8 + 6.0 + 6.0	14.8	1.42	3.04	3.04		7.50	2.90 ~ 11.20	1,660	520 ~ 3,100	7.8	7.1	0.9 + 1.7 + 1.7
	2.8 + 6.0 + 7.1	15.9	1.33	2.85	3.37		7.55	2.90 ~ 11.25	1,680	520 ~ 3,100	7.9	7.2	0.8 + 1.7 + 1.9
	2.8 + 7.1 + 7.1	17.0	1.25	3.17	3.17		7.60	2.90 ~ 11.30	1,700	520 ~ 3,100	8.0	7.3	0.8 + 1.8 + 1.8
	3.5 + 3.5 + 3.5	10.5	2.47	2.47	2.47		7.40	2.90 ~ 10.20	1,780	530 ~ 3,000	8.3	7.6	1.5 + 1.5 + 1.5
	3.5 + 3.5 + 5.0	12.0	2.16	2.16	3.08		7.40	2.90 ~ 10.50	1,690	520 ~ 3,030	7.9	7.3	1.4 + 1.4 + 1.7
	3.5 + 3.5 + 6.0	13.0	2.01	2.01	3.44		7.45	2.90 ~ 10.65	1,730	520 ~ 3,050	8.1	7.4	1.3 + 1.3 + 2.0
	3.5 + 3.5 + 7.1	14.1	1.86	1.86	3.78		7.50	2.90 ~ 10.70	1,750	520 ~ 3,050	8.1	7.4	1.2 + 1.2 + 2.2
	3.5 + 5.0 + 5.0	13.5	1.93	2.76	2.76		7.45	2.90 ~ 10.65	1,730	520 ~ 3,050	8.1	7.4	1.2 + 1.6 + 1.6
	3.5 + 5.0 + 6.0	14.5	1.81	2.59	3.10		7.50	2.90 ~ 10.95	1,690	520 ~ 3,100	7.9	7.3	1.2 + 1.6 + 1.7
	3.5 + 5.0 + 7.1	15.6	1.69	2.42	3.44		7.55	2.90 ~ 11.00	1,710	520 ~ 3,100	8.0	7.3	1.1 + 1.5 + 2.0
	3.5 + 6.0 + 6.0	15.5	1.70	2.92	2.92		7.55	2.90 ~ 11.25	1,680	520 ~ 3,100	7.9	7.2	1.1 + 1.7 + 1.7
	3.5 + 6.0 + 7.1	16.6	1.60	2.75	3.25		7.60	2.90 ~ 11.30	1,700	520 ~ 3,100	8.0	7.3	1.0 + 1.6 + 1.8
	5.0 + 5.0 + 5.0	15.0	2.50	2.50	2.50		7.50	2.90 ~ 10.70	1,750	520 ~ 3,050	8.1	7.4	1.5 + 1.5 + 1.5
	5.0 + 5.0 + 6.0	16.0	2.36	2.36	2.83		7.55	2.90 ~ 11.05	1,710	520 ~ 3,100	8.0	7.3	1.5 + 1.5 + 1.7
	5.0 + 5.0 + 7.1	17.1	2.22	2.22	3.16		7.60	2.90 ~ 11.10	1,730	520 ~ 3,100	8.1	7.4	1.4 + 1.4 + 1.8
	5.0 + 6.0 + 6.0	17.0	2.24	2.68	2.68		7.60	2.90 ~ 11.30	1,700	520 ~ 3,100	8.0	7.3	1.5 + 1.6 + 1.6
4 Rooms	2.8 + 2.8 + 2.8 + 2.8	11.2	1.65	1.65	1.65	1.65	7.40	2.90 ~ 10.80	1,480	530 ~ 3,080	6.9	6.3	1.1 + 1.1 + 1.1 + 1.1
	2.8 + 2.8 + 2.8 + 3.5	11.9	1.60	1.60	1.60	2.00	7.40	2.90 ~ 10.85	1,480	530 ~ 3,080	6.9	6.3	1.0 + 1.0 + 1.0 + 1.3
	2.8 + 2.8 + 2.8 + 5.0	13.4	1.49	1.49	1.49	2.33	7.50	2.90 ~ 10.90	1,500	520 ~ 3,090	7.0	6.4	0.9 + 0.9 + 0.9 + 1.5
	2.8 + 2.8 + 2.8 + 6.0	14.4	1.31	1.31	1.31	2.87	7.60	2.90 ~ 11.00	1,530	520 ~ 3,100	7.1	6.5	0.8 + 0.8 + 0.8 + 1.7
	2.8 + 2.8 + 2.8 + 7.1	15.5	1.21	1.21	1.21	3.17	7.65	2.90 ~ 11.10	1,540	520 ~ 3,100	7.1	6.5	0.8 + 0.8 + 0.8 + 1.8
	2.8 + 2.8 + 3.5 + 3.5	12.6	1.11	1.11	1.11	3.47	7.40	2.90 ~ 10.90	1,480	530 ~ 3,080	6.9	6.3	0.7 + 0.7 + 0.7 + 2.0
	2.8 + 2.8 + 3.5 + 5.0	14.1	1.01	1.01	1.01	3.77	7.50	2.90 ~ 11.00	1,510	520 ~ 3,090	7.0	6.4	0.7 + 0.7 + 0.7 + 2.2
	2.8 + 2.8 + 3.5 + 6.0	15.1	1.51	1.51	1.89	1.89	7.60	2.90 ~ 11.10	1,530	520 ~ 3,100	7.1	6.5	1.0 + 1.0 + 1.2 + 1.2
	2.8 + 2.8 + 3.5 + 7.1	16.2	1.41	1.41	1.77	2.21	7.65	2.90 ~ 11.20	1,540	520 ~ 3,100	7.1	6.5	0.9 + 0.9 + 1.1 + 1.4
	2.8 + 2.8 + 5.0 + 5.0	15.6	1.25	1.25	1.56	2.74	7.55	2.90 ~ 11.10	1,520	520 ~ 3,100	7.1	6.5	0.8 + 0.8 + 1.0 + 1.6
	2.8 + 2.8 + 5.0 + 6.0	16.6	1.16	1.16	1.44	3.04	7.65	2.90 ~ 11.20	1,540	520 ~ 3,110	7.1	6.5	0.7 + 0.7 + 0.9 + 1.7
	2.8 + 2.8 + 6.0 + 6.0	17.6	1.07	1.07	1.33	3.33	8.00	2.90 ~ 11.60	1,620	520 ~ 3,100	7.5	6.9	0.7 + 0.7 + 0.8 + 1.9
	2.8 + 3.5 + 3.5 + 3.5	13.3	0.97	0.97	1.21	3.65	7.45	2.90 ~ 10.95	1,490	530 ~ 3,080	6.9	6.3	0.7 + 0.7 + 0.8 + 2.1
	2.8 + 3.5 + 3.5 + 5.0	14.8	1.33	1.33	2.07	2.07	7.55	2.90 ~ 11.10	1,510	520 ~ 3,090	7.0	6.4	0.8 + 0.8 + 1.3 + 1.3
	2.8 + 3.5 + 3.5 + 6.0	15.8	1.18	1.18	1.85	2.59	7.65	2.90 ~ 11.20	1,530	520 ~ 3,100	7.1	6.5	0.7 + 0.7 + 1.2 + 1.6
	2.8 + 3.5 + 3.5 + 7.1	16.9	1.10	1.10	1.72	2.88	7.70	2.90 ~ 11.30	1,550	520 ~ 3,100	7.2	6.6	0.7 + 0.7 + 1.1 + 1.7
	2.8 + 3.5 + 5.0 + 5.0	16.3	1.02	1.02	1.58	3.18	7.55	2.90 ~ 11.20	1,520	520 ~ 3,100	7.1	6.5	0.7 + 0.7 + 1.0 + 1.8
	2.8 + 3.5 + 5.0 + 6.0	17.3	1.07	1.07	2.33	2.33	7.65	2.90 ~ 11.30	1,540	520 ~ 3,110	7.1	6.5	0.7 + 0.7 + 1.5 + 1.5
	3.5 + 3.5 + 3.5 + 3.5	14.0	1.00	1.00	2.18	2.62	7.45	2.90 ~ 11.00	1,490	530 ~ 3,080	6.9	6.3	0.7 + 0.7 + 1.4 + 1.6
	3.5 + 3.5 + 3.5 + 5.0	15.5	1.43	1.79	1.79	1.79	7.55	2.90 ~ 11.20	1,510	520 ~ 3,090	7.0	6.4	0.9 + 1.2 + 1.2 + 1.2
	3.5 + 3.5 + 3.5 + 6.0	16.5	1.34	1.68	1.68	2.10	7.65	2.90 ~ 11.30	1,530	520 ~ 3,100	7.1	6.5	0.8 + 1.1 + 1.1 + 1.4
	3.5 + 3.5 + 3.5 + 7.1	17.6	1.20	1.49	1.49	2.62	7.70	2.90 ~ 11.40	1,550	520 ~ 3,100	7.2	6.6	0.7 + 0.9 + 0.9 + 1.6
	3.5 + 3.5 + 5.0 + 5.0	17.0	1.11	1.39	1.39	2.91	7.55	2.90 ~ 11.30	1,520	520 ~ 3,100	7.1	6.5	0.7 + 0.9 + 0.9 + 1.7

U Series Multi-Split System

CU-2U18YBZ

INDOOR UNIT COMBINATION		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
1 Room	2.8	2.8	2.80				2.80	1.10 ~ 3.50	650	220 ~ 890	3.1	2.9	1.6
	3.5	3.5	3.50				3.50	1.10 ~ 4.20	890	220 ~ 1,370	4.2	3.9	2.0
	5.0	5.0	5.00				5.00	1.10 ~ 5.10	1,800	220 ~ 1,860	8.3	7.6	2.7
2 Rooms	2.8 + 2.8	5.6	2.50	2.50			5.00	1.50 ~ 5.90	1,270	260 ~ 1,900	5.9	5.5	1.5 + 1.5
	2.8 + 3.5	6.3	2.22	2.78			5.00	1.50 ~ 5.95	1,270	260 ~ 1,900	5.9	5.5	1.4 + 1.6
	2.8 + 5.0	7.8	1.81	3.24			5.05	1.50 ~ 6.05	1,290	250 ~ 1,900	6.0	5.5	1.2 + 1.8
	3.5 + 3.5	7.0	2.50	2.50			5.00	1.50 ~ 6.00	1,270	260 ~ 1,900	5.9	5.5	1.5 + 1.5
	3.5 + 5.0	8.5	2.10	3.00			5.10	1.50 ~ 6.10	1,310	250 ~ 1,900	6.1	5.6	1.4 + 1.7

CU-3U27YBZ

INDOOR UNIT COMBINATION Cooling		Total	Cooling Capacity [kW]						Input Power [W]		Current [50Hz] [A]		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
1 Room	2.8	2.8	2.80				2.80	1.70 ~ 3.60	650	380 ~ 930	3.0	2.8	1.6
	3.5	3.5	3.50				3.50	1.70 ~ 4.60	890	380 ~ 1,470	4.2	3.9	2.0
	5.0	5.0	5.00				5.00	1.70 ~ 5.60	1,600	380 ~ 1,920	7.3	6.8	2.7
	6.0	6.0	6.00				6.00	1.90 ~ 7.30	1,780	400 ~ 2,830	8.1	7.5	3.3
	7.1	7.1	7.10				7.10	1.90 ~ 7.50	2,570	400 ~ 3,070	11.8	10.9	4.1
2 Rooms	2.8 + 2.8	5.6	2.80	2.80			5.60	1.70 ~ 7.35	1,580	380 ~ 2,690	7.5	6.9	1.6 + 1.6
	2.8 + 3.5	6.3	2.80	3.50			6.30	1.90 ~ 7.90	1,970	400 ~ 2,970	9.2	8.5	1.6 + 2.0
	2.8 + 5.0	7.8	2.30	4.10			6.40	2.60 ~ 7.95	2,030	540 ~ 3,000	9.5	8.7	1.5 + 2.3
	2.8 + 6.0	8.8	2.28	4.88			7.15	2.80 ~ 8.45	2,130	550 ~ 3,020	10.0	9.1	1.5 + 2.7
	2.8 + 7.1	9.9	2.04	5.16			7.20	2.80 ~ 8.50	2,160	550 ~ 3,020	10.1	9.3	1.3 + 2.8
	3.5 + 3.5	7.0	3.18	3.18			6.35	1.90 ~ 7.95	2,000	400 ~ 2,970	9.4	8.6	1.8 + 1.8
	3.5 + 5.0	8.5	2.66	3.79			6.45	2.60 ~ 8.00	2,060	540 ~ 3,000	9.6	8.8	1.6 + 2.2
	3.5 + 6.0	9.5	2.63	4.52			7.15	2.80 ~ 8.50	2,130	550 ~ 3,020	10.0	9.1	1.6 + 2.5
	3.5 + 7.1	10.6	2.38	4.82			7.20	2.80 ~ 8.55	2,160	550 ~ 3,020	10.1	9.3	1.5 + 2.6
	5.0 + 5.0	10.0	3.25	3.25			6.50	2.60 ~ 8.10	2,060	540 ~ 3,000	9.6	8.8	1.8 + 1.8
	5.0 + 6.0	11.0	3.27	3.93			7.20	2.80 ~ 8.55	2,130	550 ~ 3,020	10.0	9.1	1.9 + 2.3
	5.0 + 7.1	12.1	3.00	4.25			7.25	2.80 ~ 8.60	2,160	550 ~ 3,020	10.1	9.3	1.7 + 2.4
	6.0 + 6.0	12.0	3.73	3.73			7.45	2.80 ~ 9.20	2,320	550 ~ 3,220	10.9	10.0	2.2 + 2.2
	6.0 + 7.1	13.1	3.44	4.06			7.50	2.80 ~ 9.25	2,350	550 ~ 3,220	11.0	10.1	2.0 + 2.3
	7.1 + 7.1	14.2	3.75	3.75			7.50	2.80 ~ 9.30	2,350	550 ~ 3,220	11.0	10.1	2.2 + 2.2
3 Rooms	2.8 + 2.8 + 2.8	8.4	2.33	2.33	2.33		7.00	2.80 ~ 9.00	1,830	550 ~ 3,050	8.5	7.8	1.5 + 1.5 + 1.5
	2.8 + 2.8 + 3.5	9.1	2.15	2.15	2.69		7.00	2.80 ~ 9.05	1,830	550 ~ 3,050	8.5	7.8	1.4 + 1.4 + 1.6
	2.8 + 2.8 + 5.0	10.6	1.86	1.86	3.33		7.05	2.80 ~ 9.10	1,850	550 ~ 3,050	8.6	7.9	1.2 + 1.2 + 1.9
	2.8 + 2.8 + 6.0	11.6	1.73	1.73	3.70		7.15	2.80 ~ 9.25	1,860	540 ~ 3,030	8.6	7.9	1.1 + 1.1 + 2.2
	2.8 + 2.8 + 7.1	12.7	1.59	1.59	4.03		7.20	2.80 ~ 9.30	1,860	540 ~ 3,030	8.6	7.9	1.0 + 1.0 + 2.3
	2.8 + 3.5 + 3.5	9.8	2.00	2.50	2.50		7.00	2.80 ~ 9.10	1,830	550 ~ 3,050	8.5	7.8	1.3 + 1.5 + 1.5
	2.8 + 3.5 + 5.0	11.3	1.75	2.18	3.12		7.05	2.80 ~ 9.15	1,840	550 ~ 3,050	8.5	7.8	1.1 + 1.4 + 1.8
	2.8 + 3.5 + 6.0	12.3	1.63	2.03	3.49		7.15	2.80 ~ 9.30	1,850	540 ~ 3,030	8.6	7.9	1.0 + 1.3 + 2.0
	2.8 + 3.5 + 7.1	13.4	1.50	1.88	3.81		7.20	2.80 ~ 9.35	1,850	540 ~ 3,030	8.6	7.9	1.0 + 1.2 + 2.2
	2.8 + 5.0 + 5.0	12.8	1.58	2.81	2.81		7.20	2.80 ~ 9.20	1,890	550 ~ 3,050	8.8	8.0	1.0 + 1.6 + 1.6
	2.8 + 5.0 + 6.0	13.8	1.48	2.64	3.17		7.30	2.80 ~ 9.35	1,900	540 ~ 3,030	8.8	8.1	0.9 + 1.6 + 1.8
	2.8 + 6.0 + 6.0	14.8	1.42	3.04	3.04		7.50	2.80 ~ 9.50	1,980	540 ~ 2,740	9.2	8.4	0.9 + 1.7 + 1.7
	3.5 + 3.5 + 3.5	10.5	2.33	2.33	2.33		7.00	2.80 ~ 9.15	1,830	550 ~ 3,050	8.5	7.8	1.5 + 1.5 + 1.5
	3.5 + 3.5 + 5.0	12.0	2.06	2.06	2.94		7.05	2.80 ~ 9.20	1,840	550 ~ 3,050	8.5	7.8	1.3 + 1.3 + 1.7
	3.5 + 3.5 + 6.0	13.0	1.93	1.93	3.30		7.15	2.80 ~ 9.35	1,850	540 ~ 3,030	8.6	7.9	1.2 + 1.2 + 1.9
	3.5 + 3.5 + 7.1	14.1	1.79	1.79	3.63		7.20	2.80 ~ 9.40	1,850	540 ~ 3,030	8.6	7.9	1.2 + 1.2 + 2.1
	3.5 + 5.0 + 5.0	13.5	1.87	2.67	2.67		7.20	2.80 ~ 9.25	1,890	550 ~ 3,050	8.8	8.0	1.2 + 1.6 + 1.6
	3.5 + 5.0 + 6.0	14.5	1.76	2.52	3.02		7.30	2.80 ~ 9.40	1,900	540 ~ 3,030	8.8	8.1	1.1 + 1.5 + 1.7

MULTI-SPLIT COMBINATION CAPACITY TABLE

CU-4U28YBZ

INDOOR UNIT COMBINATION Cooling		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
1 Room	2.8	2.8	2.80				2.80	1.70 ~ 3.60	650	380 ~ 930	3.0	2.8	1.6
	3.5	3.5	3.50				3.50	1.70 ~ 4.60	890	380 ~ 1,470	4.2	3.9	2.0
	5.0	5.0	5.00				5.00	1.70 ~ 5.60	1,600	380 ~ 1,920	7.3	6.8	2.7
	6.0	6.0	6.00				6.00	1.90 ~ 7.30	1,780	400 ~ 2,830	8.1	7.5	3.3
	7.1	7.1	7.10				7.10	1.90 ~ 7.50	2,570	400 ~ 3,070	11.8	10.9	4.1
2 Rooms	2.8 + 2.8	5.6	2.80	2.80			5.60	1.70 ~ 7.35	1,750	380 ~ 2,850	8.3	7.6	1.6 + 1.6
	2.8 + 3.5	6.3	2.80	3.50			6.30	1.90 ~ 7.90	2,150	400 ~ 3,100	10.2	9.3	1.6 + 2.0
	2.8 + 5.0	7.8	2.30	4.10			6.40	2.60 ~ 8.00	2,210	540 ~ 3,100	10.5	9.6	1.5 + 2.3
	2.8 + 6.0	8.8	2.28	4.88			7.15	2.80 ~ 8.45	2,240	550 ~ 3,210	10.6	9.7	1.5 + 2.7
	2.8 + 7.1	9.9	2.04	5.16			7.20	2.80 ~ 8.50	2,260	550 ~ 3,210	10.7	9.8	1.3 + 2.8
	3.5 + 3.5	7.0	3.18	3.18			6.35	1.90 ~ 7.95	2,150	400 ~ 3,100	10.2	9.3	1.8 + 1.8
	3.5 + 5.0	8.5	2.66	3.79			6.45	2.60 ~ 8.05	2,230	540 ~ 3,110	10.5	9.7	1.6 + 2.2
	3.5 + 6.0	9.5	2.63	4.52			7.15	2.80 ~ 8.50	2,240	550 ~ 3,210	10.6	9.7	1.6 + 2.5
	3.5 + 7.1	10.6	2.38	4.82			7.20	2.80 ~ 8.55	2,260	550 ~ 3,210	10.7	9.8	1.5 + 2.6
	5.0 + 5.0	10.0	3.25	3.25			6.50	2.60 ~ 8.10	2,250	540 ~ 3,110	10.6	9.8	1.8 + 1.8
	5.0 + 6.0	11.0	3.27	3.93			7.20	2.80 ~ 8.55	2,260	550 ~ 3,210	10.7	9.8	1.9 + 2.3
	5.0 + 7.1	12.1	3.00	4.25			7.25	2.80 ~ 8.60	2,280	550 ~ 3,210	10.8	9.9	1.7 + 2.4
	6.0 + 6.0	12.0	3.95	3.95			7.90	2.80 ~ 9.20	2,570	550 ~ 3,210	12.2	11.1	2.3 + 2.3
	6.0 + 7.1	13.1	3.64	4.31			7.95	2.80 ~ 9.25	2,590	550 ~ 3,210	12.2	11.2	2.1 + 2.4
	7.1 + 7.1	14.2	4.00	4.00			8.00	2.80 ~ 9.30	2,610	550 ~ 3,210	12.3	11.3	2.3 + 2.3
3 Rooms	2.8 + 2.8 + 2.8	8.4	2.33	2.33	2.33		7.00	2.80 ~ 9.00	2,080	550 ~ 3,180	9.8	9.0	1.5 + 1.5 + 1.5
	2.8 + 2.8 + 3.5	9.1	2.15	2.15	2.69		7.00	2.80 ~ 9.05	2,080	550 ~ 3,180	9.8	9.0	1.4 + 1.4 + 1.6
	2.8 + 2.8 + 5.0	10.6	1.86	1.86	3.33		7.05	2.80 ~ 9.10	2,100	550 ~ 3,180	9.9	9.1	1.2 + 1.2 + 1.9
	2.8 + 2.8 + 6.0	11.6	1.73	1.73	3.70		7.15	2.80 ~ 9.25	2,040	540 ~ 3,160	9.6	8.8	1.1 + 1.1 + 2.2
	2.8 + 2.8 + 7.1	12.7	1.59	1.59	4.03		7.20	2.80 ~ 9.30	2,060	540 ~ 3,160	9.7	8.9	1.0 + 1.0 + 2.3
	2.8 + 3.5 + 3.5	9.8	2.00	2.50	2.50		7.00	2.80 ~ 9.10	2,080	550 ~ 3,180	9.8	9.0	1.3 + 1.5 + 1.5
	2.8 + 3.5 + 5.0	11.3	1.75	2.18	3.12		7.05	2.80 ~ 9.15	2,100	550 ~ 3,180	9.9	9.1	1.1 + 1.4 + 1.8
	2.8 + 3.5 + 6.0	12.3	1.63	2.03	3.49		7.15	2.80 ~ 9.30	2,040	540 ~ 3,160	9.6	8.8	1.0 + 1.3 + 2.0
	2.8 + 3.5 + 7.1	13.4	1.50	1.88	3.81		7.20	2.80 ~ 9.35	2,060	540 ~ 3,160	9.7	8.9	1.0 + 1.2 + 2.2
	2.8 + 5.0 + 5.0	12.8	1.58	2.81	2.81		7.20	2.80 ~ 9.20	2,170	550 ~ 3,180	10.3	9.4	1.0 + 1.6 + 1.6
	2.8 + 5.0 + 6.0	13.8	1.48	2.64	3.17		7.30	2.80 ~ 9.35	2,110	540 ~ 3,160	10.0	9.1	0.9 + 1.6 + 1.8
	2.8 + 5.0 + 7.1	14.9	1.38	2.47	3.50		7.35	2.80 ~ 9.40	2,130	540 ~ 3,160	10.1	9.2	0.9 + 1.5 + 2.0
	2.8 + 6.0 + 6.0	14.8	1.50	3.22	3.22		7.95	2.80 ~ 9.55	2,280	540 ~ 3,210	10.8	9.9	1.0 + 1.8 + 1.8
	2.8 + 6.0 + 7.1	15.9	1.41	3.02	3.57		8.00	2.80 ~ 9.60	2,300	540 ~ 3,210	10.9	10.0	0.9 + 1.7 + 2.1
	3.5 + 3.5 + 3.5	10.5	2.33	2.33	2.33		7.00	2.80 ~ 9.15	2,080	550 ~ 3,180	9.8	9.0	1.5 + 1.5 + 1.5
	3.5 + 3.5 + 5.0	12.0	2.06	2.06	2.94		7.05	2.80 ~ 9.20	2,100	550 ~ 3,200	9.9	9.1	1.3 + 1.3 + 1.7
	3.5 + 3.5 + 6.0	13.0	1.93	1.93	3.30		7.15	2.80 ~ 9.35	2,040	540 ~ 3,160	9.6	8.8	1.2 + 1.2 + 1.9
	3.5 + 3.5 + 7.1	14.1	1.79	1.79	3.63		7.20	2.80 ~ 9.40	2,060	540 ~ 3,160	9.7	8.9	1.2 + 1.2 + 2.1
	3.5 + 5.0 + 5.0	13.5	1.87	2.67	2.67		7.20	2.80 ~ 9.25	2,170	550 ~ 3,180	10.3	9.4	1.2 + 1.6 + 1.6
	3.5 + 5.0 + 6.0	14.5	1.76	2.52	3.02		7.30	2.80 ~ 9.40	2,110	540 ~ 3,160	10.0	9.1	1.1 + 1.5 + 1.7
	3.5 + 5.0 + 7.1	15.6	1.65	2.36	3.35		7.35	2.80 ~ 9.45	2,130	540 ~ 3,160	10.1	9.2	1.1 + 1.5 + 1.9
	3.5 + 6.0 + 6.0	15.5	1.81	3.10	3.10		8.00	2.80 ~ 9.60	2,300	540 ~ 3,210	10.9	10.0	1.2 + 1.7 + 1.7
	5.0 + 5.0 + 5.0	15.0	2.42	2.42	2.42		7.25	2.80 ~ 9.30	2,170	550 ~ 3,180	10.3	9.4	1.5 + 1.5 + 1.5
	5.0 + 5.0 + 6.0	16.0	2.30	2.30	2.76		7.35	2.80 ~ 9.45	2,130	540 ~ 3,160	10.1	9.2	1.5 + 1.5 + 1.6

U Series Multi-Split System

CU-4U28YBZ

INDOOR UNIT COMBINATION Cooling		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
4 Rooms	2.8 + 2.8 + 2.8 + 2.8	11.2	1.88	1.88	1.88	1.88	7.50	2.80 ~ 9.40	1,850	550 ~ 3,380	8.7	7.9	1.2 + 1.2 + 1.2 + 1.2
	2.8 + 2.8 + 2.8 + 3.5	11.9	1.76	1.76	1.76	2.21	7.50	2.80 ~ 9.45	1,850	550 ~ 3,380	8.7	7.9	1.1 + 1.1 + 1.1 + 1.4
	2.8 + 2.8 + 2.8 + 5.0	13.4	1.58	1.58	1.58	2.82	7.55	2.80 ~ 9.50	1,840	550 ~ 3,380	8.6	7.9	1.0 + 1.0 + 1.0 + 1.7
	2.8 + 2.8 + 2.8 + 6.0	14.4	1.52	1.52	1.52	3.25	7.80	2.80 ~ 10.00	1,910	540 ~ 3,200	8.9	8.2	1.0 + 1.0 + 1.0 + 1.8
	2.8 + 2.8 + 2.8 + 7.1	15.5	1.42	1.42	1.42	3.60	7.85	2.80 ~ 10.10	1,940	540 ~ 3,200	9.1	8.3	0.9 + 0.9 + 0.9 + 2.1
	2.8 + 2.8 + 3.5 + 3.5	12.6	1.67	1.67	2.08	2.08	7.50	2.80 ~ 9.50	1,850	550 ~ 3,440	8.7	7.9	1.1 + 1.1 + 1.3 + 1.3
	2.8 + 2.8 + 3.5 + 5.0	14.1	1.50	1.50	1.87	2.68	7.55	2.80 ~ 9.55	1,840	550 ~ 3,380	8.6	7.9	1.0 + 1.0 + 1.2 + 1.6
	2.8 + 2.8 + 3.5 + 6.0	15.1	1.46	1.46	1.83	3.14	7.90	2.80 ~ 10.10	1,960	540 ~ 3,200	9.2	8.4	0.9 + 0.9 + 1.2 + 1.8
	2.8 + 2.8 + 3.5 + 7.1	16.2	1.38	1.38	1.73	3.51	8.00	2.80 ~ 10.20	2,000	540 ~ 3,200	9.4	8.6	0.9 + 0.9 + 1.1 + 2.0
	2.8 + 2.8 + 5.0 + 5.0	15.6	1.36	1.36	2.44	2.44	7.60	2.80 ~ 9.60	1,890	550 ~ 3,380	8.9	8.1	0.9 + 0.9 + 1.5 + 1.5
	2.8 + 3.5 + 3.5 + 3.5	13.3	1.59	1.99	1.99	1.99	7.55	2.80 ~ 9.55	1,850	550 ~ 3,440	8.7	7.9	1.0 + 1.3 + 1.3 + 1.3
	2.8 + 3.5 + 3.5 + 5.0	14.8	1.44	1.80	1.80	2.57	7.60	2.80 ~ 9.60	1,890	550 ~ 3,380	8.9	8.1	0.9 + 1.2 + 1.2 + 1.6
	2.8 + 3.5 + 3.5 + 6.0	15.8	1.40	1.75	1.75	3.00	7.90	2.80 ~ 10.10	1,960	540 ~ 3,200	9.2	8.4	0.9 + 1.1 + 1.1 + 1.7
	3.5 + 3.5 + 3.5 + 3.5	14.0	1.89	1.89	1.89	1.89	7.55	2.80 ~ 9.60	1,850	550 ~ 3,380	8.7	7.9	1.2 + 1.2 + 1.2 + 1.2
	3.5 + 3.5 + 3.5 + 5.0	15.5	1.72	1.72	1.72	2.45	7.60	2.80 ~ 9.65	1,890	550 ~ 3,380	8.9	8.1	1.1 + 1.1 + 1.1 + 1.5

CU-4U34YBZ

INDOOR UNIT COMBINATION Cooling		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
1 Room	2.8	2.8	2.80				2.80	1.70 ~ 3.60	650	380 ~ 930	3.0	2.8	1.6
	3.5	3.5	3.50				3.50	1.70 ~ 4.60	890	380 ~ 1,470	4.2	3.9	2.0
	5.0	5.0	5.00				5.00	1.70 ~ 5.60	1,600	380 ~ 1,920	7.3	6.8	2.7
	6.0	6.0	6.00				6.00	1.90 ~ 7.57	1,460	400 ~ 2,510	6.7	6.2	3.3
	7.1	7.1	7.10				7.10	1.90 ~ 8.03	2,250	400 ~ 2,850	10.3	9.5	4.1
2 Rooms	2.8 + 2.8	5.6	2.80	2.80			5.60	1.70 ~ 8.20	1,380	380 ~ 2,310	6.5	6.0	1.6 + 1.6
	2.8 + 3.5	6.3	2.80	3.50			6.30	1.90 ~ 8.55	1,600	400 ~ 2,550	7.6	7.0	1.6 + 2.0
	2.8 + 5.0	7.8	2.80	5.00			7.80	2.90 ~ 8.95	2,420	570 ~ 2,950	11.3	10.5	1.6 + 2.7
	2.8 + 6.0	8.8	2.74	5.86			8.60	2.90 ~ 9.80	2,460	560 ~ 3,040	11.5	10.7	1.6 + 3.2
	2.8 + 7.1	9.9	2.45	6.20			8.65	2.90 ~ 9.90	2,480	560 ~ 3,040	11.6	10.8	1.5 + 3.5
	3.5 + 3.5	7.0	3.50	3.50			7.00	1.90 ~ 8.60	1,800	400 ~ 2,550	8.4	7.8	2.0 + 2.0
	3.5 + 5.0	8.5	3.27	4.68			7.95	2.90 ~ 9.00	2,460	570 ~ 2,950	11.5	10.7	1.9 + 2.5
	3.5 + 6.0	9.5	3.19	5.46			8.65	2.90 ~ 9.90	2,480	560 ~ 3,040	11.6	10.8	1.8 + 3.0
	3.5 + 7.1	10.6	2.87	5.83			8.70	2.90 ~ 10.00	2,500	560 ~ 3,040	11.7	10.8	1.7 + 3.2
	5.0 + 5.0	10.0	4.05	4.05			8.10	2.90 ~ 9.20	2,500	570 ~ 2,950	11.7	10.8	2.3 + 2.3
	5.0 + 6.0	11.0	3.98	4.77			8.75	2.90 ~ 10.20	2,500	560 ~ 3,040	11.7	10.8	2.3 + 2.6
	5.0 + 7.1	12.1	3.64	5.16			8.80	2.90 ~ 10.30	2,520	560 ~ 3,040	11.8	10.9	2.1 + 2.8
	6.0 + 6.0	12.0	4.70	4.70			9.40	2.90 ~ 10.40	2,810	560 ~ 3,140	13.2	12.2	2.5 + 2.5
	6.0 + 7.1	13.1	4.33	5.12			9.45	2.90 ~ 10.45	2,830	560 ~ 3,140	13.3	12.3	2.4 + 2.8
	7.1 + 7.1	14.2	4.75	4.75			9.50	2.90 ~ 10.50	2,850	560 ~ 3,160	13.3	12.4	2.6 + 2.6

MULTI-SPLIT COMBINATION CAPACITY TABLE

CU-4U34YBZ

INDOOR UNIT COMBINATION		Total	Cooling Capacity (kW)						Input Power (W)		Current [50Hz] (A)		Moisture Removal Volume L/h
			Room A	Room B	Room C	Room D	Total	min ~ max	Rated	min ~ max	220V	240V	
3 Rooms	2.8 + 2.8 + 2.8	8.4	2.80	2.80	2.80		8.40	2.90 ~ 10.00	2,110	570 ~ 2,810	9.9	9.1	1.6 + 1.6 + 1.6
	2.8 + 2.8 + 3.5	9.1	2.65	2.65	3.31		8.60	2.90 ~ 10.10	2,210	570 ~ 2,810	10.3	9.6	1.6 + 1.6 + 1.9
	2.8 + 2.8 + 5.0	10.6	2.30	2.30	4.10		8.70	2.90 ~ 10.20	2,250	570 ~ 2,810	10.5	9.8	1.5 + 1.5 + 2.3
	2.8 + 2.8 + 6.0	11.6	2.20	2.20	4.71		9.10	2.90 ~ 10.60	2,520	560 ~ 3,100	11.8	10.9	1.4 + 1.4 + 2.5
	2.8 + 2.8 + 7.1	12.7	2.02	2.02	5.12		9.15	2.90 ~ 10.70	2,540	560 ~ 3,100	11.9	11.0	1.3 + 1.3 + 2.8
	2.8 + 3.5 + 3.5	9.8	2.47	3.09	3.09		8.65	2.90 ~ 10.15	2,230	570 ~ 2,810	10.4	9.7	1.5 + 1.7 + 1.7
	2.8 + 3.5 + 5.0	11.3	2.17	2.71	3.87		8.75	2.90 ~ 10.25	2,270	570 ~ 2,810	10.6	9.8	1.4 + 1.6 + 2.3
	2.8 + 3.5 + 6.0	12.3	2.08	2.60	4.46		9.15	2.90 ~ 10.70	2,540	560 ~ 3,100	11.9	11.0	1.3 + 1.6 + 2.5
	2.8 + 3.5 + 7.1	13.4	1.92	2.40	4.87		9.20	2.90 ~ 10.80	2,560	560 ~ 3,100	12.0	11.1	1.2 + 1.5 + 2.7
	2.8 + 5.0 + 5.0	12.8	1.96	3.50	3.50		8.95	2.90 ~ 10.50	2,450	570 ~ 2,960	11.5	10.6	1.3 + 2.0 + 2.0
	2.8 + 5.0 + 6.0	13.8	1.88	3.35	4.02		9.25	2.90 ~ 10.80	2,520	560 ~ 3,100	11.8	10.9	1.2 + 1.9 + 2.3
	2.8 + 5.0 + 7.1	14.9	1.75	3.12	4.43		9.30	2.90 ~ 10.90	2,540	560 ~ 3,100	11.9	11.0	1.1 + 1.8 + 2.5
	2.8 + 6.0 + 6.0	14.8	1.78	3.81	3.81		9.40	2.90 ~ 11.05	2,540	560 ~ 3,120	11.9	11.0	1.1 + 2.2 + 2.2
	2.8 + 6.0 + 7.1	15.9	1.66	3.57	4.22		9.45	2.90 ~ 11.10	2,560	560 ~ 3,120	12.0	11.1	1.1 + 2.1 + 2.4
	2.8 + 7.1 + 7.1	17.0	1.56	3.97	3.97		9.50	2.90 ~ 11.15	2,580	560 ~ 3,120	12.1	11.2	1.0 + 2.3 + 2.3
	3.5 + 3.5 + 3.5	10.5	2.90	2.90	2.90		8.70	2.90 ~ 10.20	2,250	570 ~ 2,810	10.5	9.8	1.7 + 1.7 + 1.7
	3.5 + 3.5 + 5.0	12.0	2.57	2.57	3.67		8.80	2.90 ~ 10.30	2,290	570 ~ 2,810	10.7	9.9	1.6 + 1.6 + 2.1
	3.5 + 3.5 + 6.0	13.0	2.48	2.48	4.25		9.20	2.90 ~ 10.80	2,560	560 ~ 3,100	12.0	11.1	1.5 + 1.5 + 2.4
	3.5 + 3.5 + 7.1	14.1	2.30	2.30	4.66		9.25	2.90 ~ 10.90	2,580	560 ~ 3,100	12.1	11.2	1.5 + 1.5 + 2.5
	3.5 + 5.0 + 5.0	13.5	2.33	3.33	3.33		9.00	2.90 ~ 10.55	2,470	570 ~ 2,960	11.6	10.7	1.5 + 1.9 + 1.9
	3.5 + 5.0 + 6.0	14.5	2.24	3.21	3.85		9.30	2.90 ~ 10.90	2,540	560 ~ 3,100	11.9	11.0	1.5 + 1.8 + 2.3
	3.5 + 5.0 + 7.1	15.6	2.10	3.00	4.26		9.35	2.90 ~ 11.00	2,560	560 ~ 3,100	12.0	11.1	1.4 + 1.7 + 2.4
	3.5 + 6.0 + 6.0	15.5	2.12	3.64	3.64		9.40	2.90 ~ 11.10	2,540	560 ~ 3,120	11.9	11.0	1.4 + 2.1 + 2.1
	3.5 + 6.0 + 7.1	16.6	1.99	3.42	4.04		9.45	2.90 ~ 11.15	2,560	560 ~ 3,120	12.0	11.1	1.3 + 2.0 + 2.3
4 Rooms	5.0 + 5.0 + 5.0	15.0	3.03	3.03	3.03		9.10	2.90 ~ 10.60	2,470	570 ~ 2,960	11.6	10.7	1.7 + 1.7 + 1.7
	5.0 + 5.0 + 6.0	16.0	2.94	2.94	3.53		9.40	2.90 ~ 11.00	2,580	560 ~ 3,100	12.1	11.2	1.7 + 1.7 + 2.0
	5.0 + 5.0 + 7.1	17.1	2.76	2.76	3.92		9.45	2.90 ~ 11.10	2,600	560 ~ 3,100	12.2	11.3	1.6 + 1.6 + 2.3
	5.0 + 6.0 + 6.0	17.0	2.79	3.35	3.35		9.50	2.90 ~ 11.20	2,580	560 ~ 3,120	12.1	11.2	1.6 + 1.9 + 1.9
	2.8 + 2.8 + 2.8 + 2.8	11.2	2.25	2.25	2.25	2.25	9.00	2.90 ~ 10.85	2,270	570 ~ 3,100	10.5	9.7	1.5 + 1.5 + 1.5 + 1.5
	2.8 + 2.8 + 2.8 + 3.5	11.9	2.12	2.12	2.12	2.65	9.00	2.90 ~ 10.90	2,270	570 ~ 3,100	10.5	9.7	1.4 + 1.4 + 1.4 + 1.6
	2.8 + 2.8 + 2.8 + 5.0	13.4	1.89	1.89	1.89	3.38	9.05	2.90 ~ 10.95	2,290	570 ~ 3,100	10.6	9.8	1.2 + 1.2 + 1.2 + 1.9
	2.8 + 2.8 + 2.8 + 6.0	14.4	1.78	1.78	1.78	3.81	9.15	2.90 ~ 11.10	2,320	560 ~ 3,040	10.8	10.0	1.1 + 1.1 + 1.1 + 2.2
	2.8 + 2.8 + 2.8 + 7.1	15.5	1.66	1.66	1.66	4.21	9.20	2.90 ~ 11.15	2,330	560 ~ 3,040	10.8	10.0	1.1 + 1.1 + 1.1 + 2.4
	2.8 + 2.8 + 3.5 + 3.5	12.6	2.00	2.00	2.50	2.50	9.00	2.90 ~ 10.95	2,270	570 ~ 3,100	10.5	9.7	1.3 + 1.3 + 1.5 + 1.5
	2.8 + 2.8 + 3.5 + 5.0	14.1	1.80	1.80	2.25	3.21	9.05	2.90 ~ 11.00	2,290	570 ~ 3,100	10.6	9.8	1.2 + 1.2 + 1.5 + 1.8
	2.8 + 2.8 + 3.5 + 6.0	15.1	1.70	1.70	2.12	3.64	9.15	2.90 ~ 11.15	2,320	560 ~ 3,040	10.8	10.0	1.1 + 1.1 + 1.4 + 2.1
	2.8 + 2.8 + 3.5 + 7.1	16.2	1.59	1.59	1.99	4.03	9.20	2.90 ~ 11.20	2,330	560 ~ 3,040	10.8	10.0	1.0 + 1.0 + 1.3 + 2.3
	2.8 + 2.8 + 5.0 + 5.0	15.6	1.63	1.63	2.92	2.92	9.10	2.90 ~ 11.10	2,290	570 ~ 3,100	10.6	9.8	1.0 + 1.0 + 1.7 + 1.7
	2.8 + 2.8 + 5.0 + 6.0	16.6	1.55	1.55	2.77	3.33	9.20	2.90 ~ 11.25	2,320	560 ~ 3,040	10.8	10.0	1.0 + 1.0 + 1.6 + 1.9
	2.8 + 2.8 + 6.0 + 6.0	17.6	1.51	1.51	3.24	3.24	9.50	2.90 ~ 11.50	2,430	560 ~ 3,100	11.3	10.4	1.0 + 1.0 + 1.8 + 1.8
	2.8 + 3.5 + 3.5 + 3.5	13.3	1.91	2.38	2.38	2.38	9.05	2.90 ~ 11.00	2,290	570 ~ 3,100	10.6	9.8	1.2 + 1.5 + 1.5 + 1.5
	2.8 + 3.5 + 3.5 + 5.0	14.8	1.72	2.15	2.15	3.07	9.10	2.90 ~ 11.05	2,290	570 ~ 3,100	10.6	9.8	1.1 + 1.4 + 1.4 + 1.7
	2.8 + 3.5 + 3.5 + 6.0	15.8	1.63	2.04	2.04	3.49	9.20	2.90 ~ 11.25	2,230	560 ~ 3,040	10.8	10.0	1.0 + 1.3 + 1.3 + 2.0
	2.8 + 3.5 + 3.5 + 7.1	16.9	1.53	1.92	1.92	3.89	9.25	2.90 ~ 11.30	2,340	560 ~ 3,040	10.9	10.0	1.0 + 1.2 + 1.2 + 2.3
	2.8 + 3.5 + 5.0 + 5.0	16.3	1.56	1.95	2.79	2.79	9.10	2.90 ~ 11.15	2,290	570 ~ 3,100	10.6	9.8	1.0 + 1.3 + 1.6 + 1.6
	2.8 + 3.5 + 5.0 + 6.0	17.3	1.49	1.86	2.66	3.19	9.20	2.90 ~ 11.35	2,320	560 ~ 3,040	10.8	10.0	0.9 + 1.2 + 1.6 + 1.8
	3.5 + 3.5 + 3.5 + 3.5	14.0	2.26	2.26	2.26	2.26	9.05	2.90 ~ 11.05	2,290	570 ~ 3,100	10.6	9.8	1.5 + 1.5 + 1.5 + 1.5
	3.5 + 3.5 + 3.5 + 5.0	15.5	2.05	2.05	2.05	2.94	9.10	2.90 ~ 11.10	2,290	570 ~ 3,100	10.6	9.8	1.3 + 1.3 + 1.3 + 1.7
	3.5 + 3.5 + 3.5 + 6.0	16.5	1.95	1.95	1.95	3.35	9.20	2.90 ~ 11.35	2,330	560 ~ 3,040	10.8	10.0	1.3 + 1.3 + 1.3 + 1.9
	3.5 + 3.5 + 3.5 + 7.1	17.6	1.84	1.84	1.84	3.73	9.25	2.90 ~ 11.40	2,340	560 ~ 3,040	10.9	10.0	1.2 + 1.2 + 1.2 + 2.2
	3.5 + 3.5 + 5.0 + 5.0	17.0	1.87	1.87	2.68	2.68	9.10	2.90 ~ 11.20	2,290	570 ~ 3,100	10.6	9.8	1.2 + 1.2 + 1.6 + 1.6