



2-WAY FSV-EX ME2 Series Space-saving Combination Model

Table showing appearance, HP (8 to 24), Model name (U-8ME2H7 to U-24ME2H7), Power supply, Capacity (Cooling/Heating in kW, BTU/h), EER/COP, Dimensions, Net weight, Electrical ratings, Starting current, Air flow rate, Refrigerant amount, External static pressure, Piping connections, and Ambient temperature operating range for models 8 to 24.



Table showing appearance, HP (26 to 48), Model name (U-26ME2H7 to U-48ME2H7), Power supply, Capacity, EER/COP, Dimensions, Net weight, Electrical ratings, Starting current, Air flow rate, Refrigerant amount, External static pressure, Piping connections, and Ambient temperature operating range for models 26 to 48.

Table showing appearance, HP (50 to 66), Model name (U-50ME2H7SP to U-66ME2H7SP), Power supply, Capacity, EER/COP, Dimensions, Net weight, Electrical ratings, Starting current, Air flow rate, Refrigerant amount, External static pressure, Piping connections, and Ambient temperature operating range for models 50 to 66.

Table showing appearance, HP (68 to 80), Model name (U-68ME2H7SP to U-80ME2H7SP), Power supply, Capacity, EER/COP, Dimensions, Net weight, Electrical ratings, Starting current, Air flow rate, Refrigerant amount, External static pressure, Piping connections, and Ambient temperature operating range for models 68 to 80.

Global remarks

Table with 3 columns: Rated conditions, Cooling, Heating. Values include Indoor air temperature (27°C DB / 19°C WB, 20°C DB) and Outdoor air temperature (35°C DB, 7°C DB / 6°C WB).

These specifications are subject to change without notice.