		SC-GNW10
RECEIVER UNIT		
peaker System		
Configutration		4ch
Output Power	RMS (1 kHz, T.H.D 10.0 %, 4Ω, 20 kHz LPF)	Total Output Power (Non-simultaneous drive): 8 W*1 (Front L/R : 2 W + 2 W, Surround L/R : 2 W + 2 W)
Speaker Unit		Front L/R : Approx. 38 mm Full Range Cone type Surround L/R : Approx. 38 mm Full Range Cone type
_PCM	LPCM Multi Channel Input	Y (USB, PC only)
Power Supply	El om marti onarmer mpar	r (deb) i deniji
(on a. eapp.)	Туре	Li-ion Li-ion
Battery	Operating Time	Approx. 9 h*2 *3
J	Charging Time	Approx. 4 h ^{*2 *4}
Power Cord	During USB charging	USB Type C, DC 5V (USB AC adaptor (optional) capable of supplying with an output current of 1500 mA)
	During USB power operating	USB Type C, DC 5V (USB AC adaptor (optional) capable of supplying with an output current of 900 mA*5)
Connection		
	2.4 GHz Wireless Connection	Y (Proprietary)
Wireless	Bluetooth	-
	Line of sight communication distance	Approx. 10 m
M/imp al	USB Type C (Operating with power supply)	Y
Wired	USB Type C (Charging while Operating) AUX in / Mic out (Φ 3.5 mm ST)	<u>-</u>
Sound Function	AUX 1117 Wile Out (\$\Phi_{3.5} \text{11111 31})	
Surround		V
		RPG / FPS / Voice / Cinema / Music / Stereo
Sound Mode		(When using the App for PC, 3 additional modes can be set)
	Mic Mute	×1 (Tact Switch)
	Volume control Up / Down	×1 (Rotary Switch)
Operation	Sound Mode	×1 (Tact Switch)
	Wireless Paring	Y (Factory Default Paring)
	Auto Power Off	Υ (5.1.5.1.5.)
Operation	Bass Volume Control Speaker Balance Adjustment	Y (5 Levels) Y (7 Levels)
(When using the App for PC)	Chat Audio Output Adjustment	Y (7 Levels)
Microphone	onat Addio odtpat Adjustment	T (7 Levels)
Built-in Microphone		×2 (MEMS type)
Noise & Echo cancelling		Y (Al Voice Control)
Terminals		
JSB Port		USB Type C
Design		
Body Colour		Mat Black
Speaker Net		Cloth Net
		Y (Teal)
RGB Light		Paring & Mic Mute Indicator Function
Dimensions, Weight		
-	Dimensions (W x H x D)	Approx. 256 x 56 x 221 mm
Paciavar Unit		
Reciever Unit	Weight	Approx. 403 g
Reciever Unit	Weight	Approx. 403 g
Reciever Unit WIRELESS TRANSMITTER U		Approx. 403 g

WIRELESS TRANSMITTER	UNII	
Power Supply		
Power Cord		USB Type C, 5V, 500 mA
Terminals		
USB Port		USB Type C
AUX	Audio Output	3.5 mm Stereo Mini*6 (For connection to an active subwoofer (optional))
Switch		
Wireless Paring		×1 (Tact Switch)
Design		
Body Colour		Mat Black
RGB Light		Y (Teal) Paring & Mic Mute Indicator Function
Dimensions, Weight		
Wireless Transmitter Unit	Dimensions (W x H x D)	Approx. 112 x 33 x 61 mm
	Weight	Approx. 69 g

COMMON	
General	
Compatible Equipment ^{*7}	PC, PS4, PS5, Nintendo Switch (TV mode)
PC Compatible OS ^{*8}	Windows 10/11
Cumplied Assessment	Approx. 1.0 m USB Cable (For Wireless Transmitter),
Supplied Accessory	Approcx. 0.2 m USB Charging Cord

NOTIFICATION

- *1: The volume reduces if you use the unit with the USB cable connected.
- *2: Continuous operating time and charging time depend on the operating conditions and the surrounding environment.
- *3: Sound quality set to the factory settings, with a sound source stipulated by Panasonic, at Vol 8
- *4: When using a USB AC adaptor (optional) that is capable of supplying an output current of 1500 mA at 5 V DC. Ambient temperature 25 °C (77 °F) / When recharging a fully discharged battery.
- *5: Operation may stop when supplied from a device that does not have the recommended power capacity (output current of 900 mA or more), but this does not indicate a malfunction.
- *6: An audio cable for connecting an active subwoofer (optional) is not supplied. As noise may occur, use an audio cable (optional) that is 3 m (9.8 ft) or shorter.

 *7: Before connecting with other devices, be sure to read the operating instructions for each of the devices.
- *8: Operation is not guaranteed on all computers that are running the supported OSs.

Specifications are subject to change without notice. All numbers given here are approximate.