

Superior product for special locations
Less Corrosion Long Life Better Appearance.



STAINLESS STEEL CONDUIT PIPE

WHITE CONDUIT PIPE
(UL,BS)

STAINLESS STEEL
CONDUIT PIPE

PHOTOVOLTAIC MODULE HIT™

PRODUCT NUMBER INDEX
COMBINATION MODEL NUMBER INDEX

1. High Resistance to Corrosion

Stainless steel (SUS304) construction **ensures extreme protection against rust** in corrosive areas, such as food processing lines, chemical plants, water treatment plants, seashore plants, etc.

2. Conforming to IMC Conduit

Internal diameter and length **conform to IMC requirements**. Can be combined with steel conduit for a more flexible, reliable wiring installation in a variety of applications.

Stainless conduit fittings help form a complete, professional wiring system.

3. Long Lifetime


Conduit systems must remain in a good condition wherever they are installed. Stainless steel conduit delivers a long lifetime and **requires little maintenance especially** in high altitude installations.

4. Brilliant Appearance

Stainless steel conduit polished to a bright finish for a superior appearance. This ensures an **attractive appearance** of special importance to food processing lines.



Stainless Steel Conduit Pipes with one coupling on one end



Item No.	Nominal Size (inch)	Outside Diameter (mm)	Wall Thickness (mm)	Length (mm)	Weight (kg/Pce)	Bundle (Pcs)
DWSM 012	1/2"	21.1	2.1	3,030	3.08	10
DWSM 034	3/4"	26.4	2.1	3,030	3.95	10
DWSM 100	1"	33.6	2.8	3,025	6.56	5
DWSM 114	1-1/4"	42.2	2.8	3,025	8.39	3
DWSM 112	1-1/2"	48.3	2.8	3,025	9.69	3
DWSM 200	2"	60.3	2.8	3,025	12.29	1
DWSM 300	3"	88.9	4.0	3,010	26.23	1
DWSM 400	4"	114.2	4.0	3,005	34.12	1

Stainless Steel Conduit Fittings

Couplings




Item No.	Nominal Size (inch)	Weight (Kg/pc)	Inner Packing (Pcs)	Outer Box (Pcs)
DFSM 11012	1/2"	0.053	25	50
DFSM 11034	3/4"	0.068	10	20
DFSM 11100	1"	0.119	10	20
DFSM 11114	1-1/4"	0.151	10	10
DFSM 11112	1-1/2"	0.190	5	5
DFSM 11200	2"	0.281	3	6
DFSM 11300	3"	0.728	5	5
DFSM 11400	4"	1.019	5	5

Locknuts



Item No.	Nominal Size (inch)	Weight (Kg/pc)	Inner Packing (Pcs)	Outer Box (Pcs)
DFSM 12012	1/2"	0.004	50	-
DFSM 12034	3/4"	0.006	50	-
DFSM 12100	1"	0.013	50	-
DFSM 12114	1-1/4"	0.018	50	-
DFSM 12112	1-1/2"	0.022	30	-
DFSM 12200	2"	0.029	30	-
DFSM 12300	3"	0.063	10	-
DFSM 12400	4"	0.076	10	-

Normal Bends



Item No.	Nominal Size (inch)	Weight (Kg/pc)	Inner Packing (Pcs)	Outer Box (Pcs)
DFSM 13012	1/2"	0.284	1	10
DFSM 13034	3/4"	0.434	1	8
DFSM 13100	1"	0.872	1	6
DFSM 13114	1-1/4"	1.409	1	-
DFSM 13112	1-1/2"	1.860	1	-
DFSM 13200	2"	2.572	1	-
DFSM 13300	3"	7.419	1	-
DFSM 13400	4"	13.945	1	-

Saddles



Item No.	Nominal Size (inch)	Weight (Kg/pc)	Inner Packing (Pcs)	Outer Box (Pcs)
DFSM 16012	1/2"	0.011	25	-
DFSM 16034	3/4"	0.013	25	-
DFSM 16100	1"	0.025	25	-
DFSM 16114	1-1/4"	0.028	25	-
DFSM 16112	1-1/2"	0.045	15	-
DFSM 16200	2"	0.055	5	-
DFSM 16300	3"	0.113	5	-
DFSM 16400	4"	0.140	5	-

WHITE CONDUIT PIPE
(UL,BS)

STAINLESS STEEL
CONDUIT PIPE

PHOTOVOLTAIC MODULE FIT™

PRODUCT NUMBER INDEX
COMBINATION MODEL NUMBER INDEX