






170 Ø145 28

DIMENSIONS Unit: mm

FEATURES

- nanoe[™]X Technology approved by the National Asthma Council of Australia's Sensitive Choice Program
- Whisper quiet at 27dB(A)
- Easy Installation built-in cord & 3-pin plug
- Compact and Modern Design



SPECIFICATIONS

Model	Electrica	Electrical Supply		Power Consumption	Noise @1m	Weight
FV-15CSD1	240V	50Hz	4.7L/s	4W	27dB(A)	1.3kg

- The value of air volume, power consumption and noise are specified at static pressure OPa.
- The value of air volume is the mean value and a tolerance of +-10% is allowed.
- The value of noise level is a weighted average sound pressure level, the mean value is measured by Panasonic. A tolerance of +3dB/-7dB is allowed. The noise is measure at 1m apart from the left, the front and below of the tested product.
- Conditions of generating nanoe[™]X
 - Room temperature: about 5°C ~ 40°C (dew point temperature more than 2°C).
 - Relative humidity: about 30% ~ 85%.
- nanoeTMX is generated using the air in the room, and its amount is subject to the temperature and humidity in the air.

EFFECTIVENESS OF nanoe™X
















For further details and validation data, please refer to the following website: https://aircon.panasonic.com/introducing/whats_nanoe/nanoex.html

Please read the Installation Instructions carefully before installing the unit, and the Operating Instructions before using it. Specifications are subject to change without prior notice. The contents of this catalogue are accurate as of August 2021. Due to printing considerations, the actual colours may vary slightly from those shown. All graphics are provided merely for the purpose of illustrating a point.

Panasonic Australia Pty. Limited

1 Innovation Road Macquarie Park NSW 2113 ACN 001 592 187 ABN 83 001 592 187 Website: aircon panasonic.com.au **Panasonic**