


WALL-MOUNTED : AERO SERIES PREMIUM REVERSE CYCLE INVERTER Single -Split Type



CS-Z25VKR | CS-Z35VKR | CS-Z42VKR



CS-Z50VKR | CS-Z60VKR | CS-Z71VKR | CS-Z80VKR



SPECIFICATIONS

MODEL	(240V / 1 Phase / 50Hz)	CS-Z25VKR [CU-Z25VKR]	CS-Z35VKR [CU-Z35VKR]	CS-Z42VKR [CU-Z42VKR]	CS-Z50VKR [CU-Z50VKR]	CS-Z60VKR [CU-Z60VKR]	CS-Z71VKR [CU-Z71VKR]	CS-Z80VKR [CU-Z80VKR]	
Cooling / Heating Capacity	(min-max) kW	2.50 (0.90-3.00) 3.20 (0.90-4.00)	3.50 (0.90-4.00) 4.20 (0.90-5.00)	4.20 (0.90-5.00) 5.10 (0.90-7.10)	5.00 (0.90-4.00) 6.00 (1.00-6.00)	6.00 (1.20-7.10) 7.20 (1.20-8.00)	7.10 (1.20-8.10) 8.00 (1.20-9.10)	8.00 (2.30-9.00) 9.00 (2.30-11.00)	
	(min-max) Btu/h	8,530 (3,070-10,200) 10,760 (3,070-12,100)	11,900 (3,070-13,600) 14,700 (3,070-15,800)	14,300 (3,070-17,100) 17,400 (3,070-24,200)	17,100 (3,240-20,500) 20,500 (3,580-27,300)	20,500 (5,800-24,200) 24,600 (5,800-29,000)	24,200 (5,800-27,400) 27,300 (5,800-33,800)	27,300 (7,840-30,700) 30,700 (7,500-37,500)	
Air Flow	Indoor L/s	193/203	207/220	222/222	328/332	332/340	355/362	370/370	
Dehumidification	L/h	1.5	2.0	2.4	2.8	3.3	4.1	4.7	
Electrical Data	Running Current A	2.30/2.90	3.75/4.40	4.70/5.90	5.10/5.80	7.00/7.80	8.60/9.20	10.80/11.30	
	Power Input (min-max) kW	0.50 (0.19-0.75) 0.62 (0.17-1.30)	0.80 (0.20-1.04) 0.94 (0.18-1.54)	1.07 (0.23-1.48) 1.34 (0.23-2.25)	1.13 (0.23-2.05) 1.31 (0.23-2.65)	1.58 (0.44-2.20) 1.78 (0.40-2.50)	1.97 (0.44-2.48) 2.11 (0.40-3.30)	2.32 (0.44-2.82) 2.41 (0.35-3.30)	
A/EER / EER / COP / COP	W/W	4.87/5.00 5.06/5.16	4.31/4.38 4.51/4.57	3.88/3.93 3.77/3.81	4.38/4.42 4.54/4.58	3.77/3.80 4.02/4.06	3.58/3.60 3.77/3.79	3.43/3.45 3.72/3.73	
	Star Rating	5.0 5.5	4.0 4.5	4.0 4.5	4.0 4.5	3.0 3.5	2.5 3.0	2.0 2.5	
Noise Level	Sound Pressure Level** dB(A)	Indoor (H / L / Q-La)	43/25/19 42/27/21	44/26/19 44/29/21	47/30/23 46/31/27	47/34/31 45/33/29	47/36/33 47/35/32	49/37/34 49/37/34	51/38/35 50/39/35
		Outdoor (H / Q-La)	47/- 47/-	49/- 49/-	47/42 49/42	47/42 49/42	53/48 53/48	54/49 55/50	55/50 55/50
	Sound Power Level dB	Indoor (H / L / Q-La)	59/41/25 58/43/27	60/42/25 62/47/43	63/44/29 62/47/43	63/50/47 61/49/45	63/52/49 63/51/48	65/53/50 65/53/50	67/54/51 66/54/51
		Outdoor (H / Q-La)	62/- 62/-	64/- 65/-	62/57 62/57	62/57 62/57	67/62 67/62	68/63 68/63	69/64 69/64
Net Weight	Indoor [Outdoor]	kg	10(31)	10(31)	10(43)	13(44)	13(50)	13(40)	
Dimensions	Indoor (H x W x D)	mm	295 x 919 x 194	295 x 919 x 194	295 x 919 x 194	302 x 1,120 x 236	302 x 1,120 x 236	302 x 1,120 x 236	
	Outdoor (H x W x D)	mm	562 x 780 x 289	562 x 780 x 289	695 x 875 x 320	695 x 875 x 320	695 x 875 x 320	795 x 875 x 320	
Refrigerator Pipe Diameter	Liquid Side	mm[/inch]	ø 6.35 [1/4]	ø 6.35 [1/4]	ø 6.35 [1/4]	ø 6.35 [1/4]	ø 6.35 [1/4]	ø 6.35 [1/4]	
	Gas Side	mm[/inch]	ø 9.52 [3/8]	ø 9.52 [3/8]	ø 12.70 [1/2]	ø 12.70 [1/2]	ø 12.70 [1/2]	ø 15.88 [5/8]	
Pipe Extension Length	min-max (m)	3-20	3-20	3-30	3-30	3-30	3-30		
Maximum Elevation Length	m	15	15	15	15	15	20		
Pipe Length For Additional Gas	m	7.5	7.5	7.5	10	10	10		
Additional Gas Amount	g/m	10	10	15	15	15	25		
Power Supply	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor		
Operating Range [Outdoor]	Cooling Degree °C	+5 ~ +44	+5 ~ +44	+5 ~ +44	+5 ~ +44	+5 ~ +44	+5 ~ +44		
	Heating Degree °C	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24	-15 ~ +24		
Refrigerant Type		R32	R32	R32	R32	R32	R32		

\*\* Indoor temperature display and some special function are not available through the App for all models.

\*\* Sound pressure level specification is measured according to JIS C9612.

SPECIFICATIONS & FEATURES

Products in this brochure contain R32 refrigerant. Please refer to Panasonic's installation instructions and service manuals before installation and servicing this product.

Only persons and/or companies qualified and experienced in the installation, service and repair of refrigerant products should be permitted to do so.

The purchaser must ensure that the person and/or company who is to install, service or repair this air conditioner has qualifications and experience in refrigerant products.

Suitable access for warranty and service is required.

Future improvement, specifications, designs of product and availability are subject to change without notice. Please check with your dealer.

ALL CAPACITY AND ENERGY EFFICIENCY RATINGS ARE BASED ON AS/NZS3823.1.1

COOLING	Indoor temperature Outdoor temperature	27°C DB/19°C WB 35°C DB
HEATING	Indoor temperature Outdoor temperature	20°C DB 7°C DB / 6°C WB

Running current is at rated conditions (AS3823) and does not include compressor start-up or variations in power supply and load conditions.

FEATURES EXPLANATION

ENERGY SAVINGS	
<b>INVERTER CONTROL</b> Varies the rotation speed of the compressor for higher energy savings.	<b>ECO MODE</b> More energy saving compared to the normal mode by automatically adjusting the set temperature by up to 2°C. It's ideal when you want to maintain room temperature for gentle cooling and heating.
COMFORT	
<b>IAUTO-X</b> Come home to ultra-fast cooling, and then enjoy continuous comfort. Slower Cooling that evenly distributes cool air.	<b>QUIET MODE</b> Enjoy the comfort of running your air conditioner at night and still have a relaxing sleep.
<b>MILD DRY COOLING</b> Fine control helps prevent a rapid decrease in room humidity while maintaining the set temperature.	<b>FAN MODE</b> Allows you to run the fan without any cooling or heating, thus giving just ventilation.
<b>POWERFUL MODE</b> Pressing the Powerful button cools or heats the room quickly. It provides fast comfort, with full power and a strong air flow. This is perfect for use immediately after coming home, or when unexpected guests arrive.	<b>SOFT DRY OPERATION MODE</b> Starts with cooling to dehumidify, then provides continuous breeze at a low frequency to keep a room dry without much change to the temperature.
	<b>HOT START CONTROL</b> On the start of the heating cycle and after the defrost cycle, the indoor fan will start up once the indoor heat exchanger is warm.
CLEAN & HEALTHY AIR	
<b>nanoe™ X</b> nanoe™ X deodorizes and inhibits the growth of bacteria and viruses, for a fresher and cleaner living space.	<b>ODOUR-REMOVING FUNCTION</b> With this function, there's no unpleasant odor when the unit starts up. That's because the fan remains off momentarily, while the source of the odor inside the air conditioner is suppressed.
	<b>REMOVABLE, WASHABLE PANEL</b> Gives you easy access to the filter as well making the unit easy to clean.
	The unit must be in cool or dry mode and the fan speed must be set to automatic.
CONVENIENCE	
<b>24-HOUR DUAL ON &amp; OFF REAL SETTING TIMER</b> This feature enables you to preset two different sets of start/stop operation timer (hour and minute) within a 24-hour time frame.	<b>3RD PARTY CONNECTIVITY</b> Allows limited control from an external source when wired to do so.
	<b>Wired Remote Control (Optional)</b> For use in commercial applications, or where users don't want a remote control.
<b>DEMAND RESPONSE ENABLING DEVICE (DRED)</b> Allows Electrical Utility Companies to regulate the power supply to the units if connected.	<b>LCD WIRELESS REMOTE CONTROL</b> Easy control of the unit from anywhere in the room.
	<b>WLAN Remote Control &amp; Voice Control (Optional)</b> Control air conditioners remotely by turning your mobile device into a remote controller using internet connection.
RELIABILITY	
<b>BLUE FIN CONDENSER</b> Extra protection from the elements with a longer lasting coil.	<b>LONG PIPING</b> Long piping offers more flexible installation options, *2m - CS-Z25VKR, CS-Z35VKR *3m - CS-Z42VKR, CS-Z50VKR, CS-Z60VKR, CS-Z71VKR, CS-Z80VKR
	<b>SELF-DIAGNOSTIC FUNCTION</b> Should a malfunction occur, the unit diagnoses the problem and shows the corresponding alphanumeric code. This allows for quicker servicing.
<b>RANDOM AUTO RESTART</b> When multiple units are connected and there is a power outage they will turn on at different times in order to not spike the power supply.	<b>TOP-PANEL MAINTENANCE ACCESS</b> Easy access for maintenance.

OUTDOOR



CS-Z25VKR  
CS-Z35VKR



CS-Z42VKR  
CS-Z50VKR  
CS-Z60VKR  
CS-Z71VKR



CS-Z80VKR