

BULKHEAD DUCTED



Bulkhead Ducted



Wired Remote
Controller
Included

Model No	CS-E9QD3RW	CS-E12QD3RW	CS-E18QD3RW
Capacity	2.5kW	3.4kW	5.0kW

- Market-leading Energy Efficiency
- Only 370mm Deep
- Easy Installation
- Built-in Drain Pump (200mm lift*)
- -15°C to +46°C Operating Range

*Refer to Technical Manual for more details



Specifications

 Cooling
 Heating

240V / 1 Phase / 50 Hz			Bulkhead Ducted		
			CS-E9QD3RW (CU-E9QD3R)	CS-E12QD3RW (CU-E12QD3R)	CS-E18QD3RW (CU-E18QD3R)
Cooling/Heating Capacity	kW	2.50(0.85-3.10) 3.20(0.85-4.40)	3.40(0.85-4.00) 4.00(0.85-5.10)	5.00(0.90-5.70) 6.10(0.90-7.10)	
AEER/EER ACOP/COP	W/W	3.66/3.85 3.51/3.64	3.47/3.58 3.30/3.39	3.18/3.25 3.24/3.30	
Electrical Data	Voltage	V	240 240	240 240	
	Running Current	A	3.0 3.9	4.1 5.1	
	Power Input	kW	0.65(0.23-0.88) 0.88(0.22-1.36)	0.95(0.23-1.18) 1.18(0.22-1.6)	1.54(0.29-1.84) 1.85(0.33-2.20)
Airflow (max @ 10 Pa) - Cooling	L/s	250	256	286	
Airflow (max @ 10 Pa) - Heating	L/s	259	263	294	
Adjustable Static Pressure	Pa	0-124	0-140	0-147	
Noise Indoor	dB-A (H/L/Q-Lo)	32/27/24 34/28/25	33/27/24 35/28/25	42/30/27 42/32/29	
	Power Level dB	48/43/40 50/44/41	49/43/40 51/44/41	48/46/43 48/48/45	
Noise Outdoor	dB-A (H/L/Q-Lo)	46/-/- 48/-/-	49/-/- 50/-/-	48/43 49/44	
	Power Level dB	61/-/- 63/-/-	64/-/- 65/-/-	62/57 63/58	
Dimensions	Height x Width x Depth	mm	235x750x370 (619x824x299)	235x750x370 (619x824x299)	285x750x370 (795x875x320)
Net Weight	kg	17(33)	17(33)	18(52)	
Refrigerant Pipe Diameter	Liquid Side	mm/(inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4)
	Gas Side	mm/(inch)	9.52 (3/8)	12.70 (1/2)	12.70 (1/2)
Power Supply		Outdoor	Outdoor	Outdoor	
Pipe Length	Min-Max (m)	3-15	3-15	3-30	
Pipe Length for Additional Gas	m	7.5	7.5	10	
Additional Gas Amount	g/m	20	20	20	
Operating Range (Outdoor)	Cooling	Degree (°C)	5-46	5-46	5-46
	Heating	Degree (°C)	-15 -24	-15 -24	-15 -24
Drain Pipe Size	mm	VP-20	VP-20	VP-20	

Outdoor


 CU-E9QD3R
 CU-E12QD3R


CU-E18QD3R

