

PRIME⁺ EDITION

WATER FILTER SPECIFICATIONS

| | |
|---|--|
| Applicable Models | NR-CW530JVSA, NR-CW530JVKA, NR-BW530JVSA |
| Capacity: | 1,136 litres |
| Usage Life: | 6 months |
| Flow Rate: | 1.9 litres per minute |
| Certification | NSF 42 NSF 53 |
| Operating Temp: | 1 - 38 degrees Celsius |
| Operating Pressure: | 30-125 psi [206-861 kPA] |
| Reduces these contaminants: (% filtered)* see full instructions for additional information | |
| Chlorine | 97.5% |
| Microplastics | 99.7% |
| Cysts (microorganisms) | →99.99% |
| Turbidity (cloudiness) | 99.1% |
| Product Dimensions (WxHxD)(mm) | 60 x 210 x 60 mm |
| Installation | 90° Rotate and Lock |
| Weight(grams) | 345 grams |
| Replacment for item for: | ARAHFA10510 |
| Origin | Korea |



USAGE CAPACITY: 1,136 L
 USAGE LIFE: APPROX. 6 MONTHS
 FLOW RATE: 1.9 LITRES PER MINUTE
 OPERATING TEMP: 1 ~ 38 DEGREES
 CELSIUS

NSF Certified Performance

TESTED ACCORDING TO NSF/ANSI 42, 53, 401 STANDARDS

PANASONIC WATER FILTERS ARE TESTED AND CERTIFIED BY NSF INTERNATIONAL, DEDICATED TO PUBLIC HEALTH, SAFETY, AND PROTECTION OF THE ENVIRONMENT.

NSF CERTIFICATION IS WIDELY RECOGNISED AROUND THE WORLD AS A SAFETY GUARANTEE IN WATER FILTRATION SYSTEMS.