Panasonic



EL-GUARD GROUNDING RECEPTACLE WITHOUT KNOB



FEATURES

- Rating 10A 220V
- Fit with weatherproof cover
- Indoor & Outdoor use:
 bathroom, patio, rooftop
 terrace, pool area with pump
- Quick connect terminal



BATHROOM RATIO POOL SIDE ROOFTOP TERRACE









CONNECTION METHOD

1 Strip back covering.




2 Insert the wire fully until it stops for secure fastening.



RATING & SPECIFICATION

Rating	10 A 220 V∼	
Rated frequency	50 / 60 Hz	
Residual operating current	15 mA	
Break time	100 ms or less	
Residual non-operating current	7.5 mA	
Opening / Closing operation	4,000 times (Opening 2,000 times / Closing 2,000 times)	
Installation	Indoor	
Operating voltage range	220 V 50 / 60 Hz	
Ambient temperature -10 °C ~ 40 °C		

INSTALLATION METHOD



APPLICABLE WIRE

Flexible	Rigid		
NO	ОК	∭ ок	
	Solid	Stranded	

 $2.0~\text{mm}^2~-~3.5~\text{mm}^2$ Use <u>rigid</u> copper wire only.

CAUTION



When connecting the device, be sure to fullly insert the wires into the wire slot. Poor connections may generate heat leading to fire or burn damage.

COMBINATION WITH PLATE







WEG8981K-PH

FIT FOR WEATHERPROOF COVER



E-mail: lifesolutions@ph.panasonic.com

Website : www.panasonic.com/ph

Facebook: www.facebook.com/PanasonicBusinessSolutionPhilippines

 $\hbox{E-Catalog: www.panasonic.com/ph/business/life-solutions-learn/life-solutions/wiring-devices.html} \\$

Catalog Download Page: http://www.panasonic.com/ph/business/life-solutions-learn.html

Panasonic

[PHILIPPINES OFFICE]

Panasonic Manufacturing Philippines Corporation

Life Solution Department

[FACTORY] Panasonic Manufacturing Ayuthaya Co., Ltd. Panasonic Corporation Life Solutions Company

All Rights Reserved © 2021 COPYRIGHT Panasonic Manufacturing Philippines Corporation