

Panasonic

BUSINESS



SQP1 Series

- Large-screen 4K Displays with OPS slot
- 4K Indoor Displays add powerful features for Pro Users in a lightweight and stylish design
- The SQP1 series of 4K LCD Displays employ 4K picture quality to render intricately detailed, large screen images
- Durable panel materials and quality components ensures dependable 24 hours operation seven days a week
- OPS allows for more cost-effective system design, less cabling, management of digital signage



EQP1 Series

- Large-screen 4K Displays with OPS slot
- 4K entry professional Display with unbeatable cost-to-performance and reliability
- The EQP1 Series of 4K LCD Displays employ 4K picture quality to render intricately detailed, large-screen images
- It supports Media Player
- OPS allows for more cost-effective system design, less cabling, management of digital signage

SQP1 Series



	TH-98SQP1
Screen Size	98-inch
Brightness	500 cd/m ²
Panel Type / Backlight	IPS / Direct LED
Resolution	3840 x 2160

EQP1 Series



	TH-86EQP1	TH-75EQP1
Screen Size	86-inch	75-inch
Brightness	500 cd/m ²	410 cd/m ²
Panel Type / Backlight	IPS/Direct LED	IPS/Edge LED
Resolution	3840 x 2160	

SPECIFICATIONS

		TH-98SQP1	TH-86EQP1	TH-75EQP1
Screen size (diagonal)		98-inch (2476.9 mm) / 16:9	86-inch (2174 mm) / 16:9	75-inch (1892 mm) / 16:9
Resolution		3840 x 2160		
Brightness (typ.)		500 cd/m ²		410 cd/m ²
Contrast ratio		1300:1	1200:1	1200:1
Viewing angle (CR>10)		178° (H) / 178° (V)		
Terminals	HDMI IN	HDMI TYPE A Connector x 4	HDMI TYPE A Connector(4K) x 2 HDMI TYPE A Connector(2K) x 2	
	HDMI OUT	-	HDMI TYPE A connector x 1 (Only HDMI IN2)	HDMI TYPE A connector x 1 (Only HDMI IN2)
	PC N	Mini D-sub 15-pin x1 (Female)		
	PC AUDIO	Stereo Mini Jack(M3) x 1	-	
	AV IN	Mini 3.5mm x 1 (Audio shared with COMPONENT IN)	-	
	AV OUT	Mini 3.5mm x 1		
	AUDIO IN	-	Stereo Mini Jack(M3) x 1	
	DVI IN	DVI-D 24-pin x 1		
	COMPONENT IN	Mini 3.5mm x 1 set	RCA x 1 set	
	AUDIO IN	-	RCA x 1/ x 1 (Shared with PC)(L/R)	
	VIDEO IN	-	RCA x 1	
	AUDIO IN	-	RCA x 1/ x 1 (L/R)	
	AUDIO OUT	Stereo Mini Jack(M3) x 1	RCA x 1/ x 1 (L/R)	
	COAXIAL	-	RCA x 1	
	SPDIF	x 1	-	
	EARPHONE IN	Stereo Mini Jack (M3) x 1		
	MIC	Stereo Mini Jack(M3) x 1	-	
	USB	USB Connector (Type A) 3.0 x 2 USB Connector (Type A) 2.0 x 2	USB Connector (Type A) 3.0 x 1 USB Connector (Type A) 2.0 x 1	
	OPS	JAE x 1		
RS232C IN/OUT	D-sub 9-pin x 1 / D-sub 9-pin x 1			
Built-in speaker		16W x 2	20W x 2	10W x 2
Power requirements		100V-240V AC, 50/60Hz		
Power consumption		500W	450W	260W
Standby condition		Approx. 0.5 W		
Dimensions (W x H x D)		2198.8 x 1253.8 x 109.5mm	1963 x 1136 x 101.4 mm	1716.7 x 994.9 x 60 mm
Bezel width		Even Bezel 20.3 mm	Even Bezel 33 mm	
Weight (Display only)		Approx. 107 kg	Approx. 53 kg	Approx. 64.9 kg
Wall-hanging pitch		800 x 600 mm VESA Compliant	700 x 400 mm VESA Compliant	600 x 400 mm VESA Compliant
Operating environment		Temperature 0 to 40 deg		
Orientation		Landscape/Portrait (Counter-Clockwise)	Landscape	
Longest use (hours/day)		24/7	18/7	

Panasonic

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. All other trademarks are the property of their respective trademark owners. © 2019 Panasonic Corporation. All rights reserved.

บริษัท พานาโซนิค อีวี เซลส์ (ประเทศไทย) จำกัด
 75 ถนนเสรีไทย แขวงรามอินทรา เขตคันนายาว กรุงเทพฯ 10230
 ลูกค้าสัมพันธ์ โทร. 0-2729-9000 กด 1 www.panasonic.com/th