

規格性能表

機種名稱	CU-N140HA2				CU-N140HA3				CU-L140HA2				CU-L140HA3				CU-L250HA3		CU-L250HA4			
	室外機	CS-N71UA2 CS-N71UA2	CS-N140UA2	CS-L71DA2 CS-L71DA2	CS-L140DA2	CS-N71UA2 CS-N71UA2	CS-N140UA2	CS-L71DA2 CS-L71DA2	CS-L140DA2	CS-L71UA2 CS-L71UA2	CS-L140UA2	CS-L71DA2 CS-L71DA2	CS-L140DA2	CS-L71UA2 CS-L71UA2	CS-L140UA2	CS-L71DA2 CS-L71DA2	CS-L140DA2	CS-L140DA2	CS-L140UA2 CS-L140UA2	CS-L140DA2 CS-L140DA2		
電源	室外機	單相220V 60Hz				三相220V 60Hz				單相220V 60Hz				三相220V 60Hz				三相220V 60Hz		三相380V 60Hz		
	室內機	單相220V 60Hz				單相220V 60Hz				單相220V 60Hz				單相220V 60Hz				單相220V 60Hz		單相220V 60Hz		
冷氣性能	冷氣能力	kW	14.0		14.0		14.0		14.0		14.0		14.0		14.0		25.0		25.0			
	運轉電流	A	19.2		21.1		11.1		12.2		18.6		10.7		24.0		24.0		13.9		13.9	
	消耗功率	kW	4.000		4.420		4.000		4.420		3.900		3.900		8.700		8.680		8.700		8.680	
	CSPF季節能效		5.80		5.10		5.80		5.10		5.07 (1級)		5.07 (1級)		5.10 (1級)		4.70		5.10		4.70	
暖氣性能	暖氣能力	kW	16.0		16.0		16.0		16.0		16.0		16.0		28.0		28.0		28.0			
	運轉電流	A	23.0		24.2		12.2		13.6		19.3		11.1		25.0		25.0		14.5		14.5	
	消耗功率	kW	4.750		4.900		4.750		4.900		4.050		4.050		8.800		8.800		8.800		8.800	
壓縮機	型式	雙汽缸迴轉式DC變頻				雙汽缸迴轉式DC變頻				雙汽缸迴轉式DC變頻				雙汽缸迴轉式DC變頻				雙汽缸迴轉式DC變頻		雙汽缸迴轉式DC變頻		
	馬達輸出功率	kW	2.2				2.2				3.0				3.0				4.6		4.6	
室外風扇馬達	型式	直流無刷式DC馬達x1				直流無刷式DC馬達x1				直流無刷式DC馬達x2				直流無刷式DC馬達x2				直流無刷式DC馬達x2		直流無刷式DC馬達x2		
	風量	m³/min	70				70				115				115				160		160	
	馬達(輸出功率)	kW	0.12				0.12				0.09x2				0.09x2				0.12x2		0.12x2	
室內風扇馬達 (標準規格)	型式	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	DC馬達	
	風量(高/中/低)	m³/min	17/14/11	21/18/15	23/20/17	48/43/38	17/14/11	21/18/15	23/20/17	48/43/38	17/14/11	21/18/15	23/20/17	48/43/38	17/14/11	21/18/15	23/20/17	48/43/38	21/18/15	48/43/38	21/18/15	48/43/38
	馬達輸出功率	kW	0.024	0.092	0.130	0.200	0.130	0.200	0.130	0.200	0.024	0.092	0.130	0.200	0.130	0.200	0.130	0.200	0.092	0.200	0.092	0.200
機外靜壓	Pa	--	--	10 (0-40)	50 (0-100)	--	--	10 (0-40)	50 (0-100)	--	--	10 (0-40)	50 (0-100)	--	--	10 (0-40)	50 (0-100)	--	50 (0-100)	--	50 (0-100)	
保護裝置	高壓壓力SW	●				●				●				●				●		●		
	壓縮機吐出溫	●				●				●				●				●		●		
	壓縮機吸入溫	●				●				●				●				●		●		
	冷凝溫度保護	●				●				●				●				●		●		
	過電流FUSE	●				●				●				●				●		●		
	最大運轉電流制限	●				●				●				●				●		●		
	風扇過負荷保護	●				●				●				●				●		●		
	風扇LOCK保護	●				●				●				●				●		●		
冷媒	種類	R410A				R410A				R410A				R410A				R410A		R410A		
	出廠時冷媒量	kg	3.300				3.300				3.750				3.750				6.400		6.400	
配管連接	氣管	mm	Ø15.88				Ø15.88				Ø15.88				Ø15.88				室內側Ø15.88, 室外側Ø25.4		室內側Ø15.88, 室外側Ø25.4	
	液管	mm	Ø9.52				Ø9.52				Ø9.52				Ø9.52				Ø12.7		Ø12.7	
	內機排水口配管	mm	VP-25	VP-25	MPT 3/4"	MPT 3/4"	VP-25	VP-25	MPT 3/4"	MPT 3/4"	VP-25	VP-25	MPT 3/4"	MPT 3/4"	VP-25	VP-25	MPT 3/4"	MPT 3/4"	VP-25	MPT 3/4"	VP-25	MPT 3/4"
外機排水口配管	mm	Ø18				Ø18				VP-25				VP-25				VP-25		VP-25		
本體尺寸	室內機(高x寬x深)	mm	256x840x840	319x840x840	260x1330x500	290x1630x545	256x840x840	319x840x840	260x1330x500	290x1630x545	256x840x840	319x840x840	260x1330x500	290x1630x545	256x840x840	319x840x840	260x1330x500	290x1630x545	319x840x840	290x1630x545	319x840x840	290x1630x545
	室外機(高x寬x深)	mm	955x1100x370				955x1100x370				1416x940x340				1416x940x340				1500x980x370		1500x980x370	
淨重	室外機	kg	85				85				107				107				136		136	
	室內機	kg	23	28	24	34	23	28	24	34	24	29	24	34	24	29	24	34	29	34	29	34
噪音值	室內機	dB(A)	39/33/30	47/40/37	39/36/33	40/37/33	39/33/30	47/40/37	39/36/33	40/37/33	39/33/30	47/40/37	39/36/33	40/37/33	39/33/30	47/40/37	39/36/33	40/37/33	47/40/37	40/37/33	47/40/37	40/37/33
	一般模式	dB(A)	55				55				52				52				61		61	
	靜音模式	dB(A)	45				45				45				45				48		48	