

# MINI CASSETTE

Model No.  
CS-PV18RB4P  
CS-PV24RB4P



## TECHNICAL FOCUS

- 4-Way Airflow System
- LCD Wireless Remote Controller
- Random Auto Restart
- Removable Washable Panel
- 24 Hours Real On Off Timer
- Dew Prevention Control
- Anti Freezing Control



## Accessories

### Panel



CZ-BT20H

### Remote Controller



A wireless remote controller is in the same package with the indoor unit.

Capacity ( Btu/h )		18,100	22,300
Power Source	V/Phase Hz	220 V, 1Ø Phase - 50 Hz	
Indoor		CS-PV18RB4P	CS-PV24RB4P
Outdoor		CU-PV18RB4P	CU-PV24RB4P
Panel		CZ-BT20HW	CZ-BT20HW
Cooling Capacity: Rated	kW	5.30	6.55
	Btu/h	18,100	22,300
Current	A	7.9	11.3
Power Input: Rated	kW	1.69	2.40
EER	W/W	3.14	2.73
	Btu/hW	10.71	9.29
<b>Indoor Unit</b>			
Air Volume	m <sup>3</sup> /min	13.3	13.3
Sound Pressure Level (Hi/Lo)	dB (A)	43 / 33	44 / 35
Dimension	Indoor (HxWxD)	mm	260 × 575 × 575
	Panel (HxWxD)	mm	51 × 700 × 700
Net Weight	Indoor	kg	19.0
	Panel	kg	2.5
<b>Outdoor Unit</b>			
Sound Pressure Level	dB (A)	52	55
Dimension	Outdoor (HxWxD)	mm	695 × 875 × 320
Net Weight		kg	47.0
Piping Connection	Gas Pipe	mm (inch)	12.70 [1/2"]
	Liquid Pipe	mm (inch)	6.35 [1/4"]
Pipe Length	Min-Max	m	3.0 - 25.0
Elevation Difference		m	20.0
Maximum Chargeless Length	Max	m	7.5
Additional Gas		g/m	20
Operating Range, Outdoor	Min-Max	°C	16 - 43