

# CEILING EXPOSED

- The slim design makes thickness only 235 mm.
- Compact Looking, Stylish, One-Motion Design.
- Comfortable, Long-Distance Airflow Distribution.



(Accessory)



(Optional Wired Remote Controller)



(Optional)  
If not use  
CZ-RTC6WBLW\*1\*3/6BLW\*3,  
the adaptor also  
can be used.

CZ-RTC6W\*1/6

CZ-RTC6WBL\*1\*2/6BL\*2

CZ-RTC6WBLW\*1\*3/6BLW\*3

CZ-RTC5B

CZ-RTC4

CZ-CAPWFC1

\*1 Scheduled release date of 4th Quarter in CY23. \*2 BL=BLE, \*3 BLW=BLE&WLAN

Capacity [Btu/h(Phase)]		17,100	20,500	24,200	29,000	34,100	42,700	42,700 (3)	45,500	45,500(3)
Power Source	V/Phase Hz	220-240V, 10 Phase - 50Hz								
Indoor		S-1821PT3H	S-1821PT3H	S-2430PT3H	S-2430PT3H	S-3448PT3H	S-3448PT3H	S-3448PT3H	S-3448PT3H	S-3448PT3H
Outdoor		U-18PR1H5	U-21PR1H5	U-24PR1H5	U-30PR1H5	U-34PR1H5	U-43PR1H5	U-43PR1H5	U-48PR1H5	U-48PR1H5
Cooling Capacity: Rated [Min-Max]	kW	5.00 [2.00-5.60]	6.00 [2.00-6.30]	7.10 [2.00-7.80]	8.50 [2.00-9.60]	10.00 [3.20-11.20]	12.50 [3.80-13.54]	12.50 [3.80-13.54]	13.33 [3.80-14.00]	13.33 [3.80-14.00]
	Btu/h	17,100 [6,820-19,100]	20,500 [6,820-21,500]	24,200 [6,820-26,600]	29,000 [6,820-32,800]	34,100 [10,900-38,200]	42,700 [13,000-46,200]	42,700 [13,000-46,200]	45,500 [13,000-47,800]	45,500 [13,000-47,800]
Current: Rated [Min-Max]	A	5.9-6.2	8.4-9.0	8.9-9.7	11.7-12.8	14.3-15.6	18.6-20.3	6.1-6.7	20.4-22.2	6.7-7.4
Power Input: Rated [Min-Max]	kW	1.33 [0.39-1.65]	1.92 [0.39-2.25]	2.00 [0.32-2.36]	2.75 [0.29-3.31]	3.36 [0.58-3.77]	4.10 [0.68-4.50]	4.10 [0.68-4.50]	4.50 [0.68-4.80]	4.50 [0.68-4.80]
CSPF		6.18	5.65	5.51	5.86	5.04	5.08	5.08	4.98	4.98
COP/EER	W/W	3.76	3.13	3.38	3.09	2.98	3.05	3.05	2.96	2.96
	Btu/hW	12.86	10.68	11.52	10.55	10.15	10.41	10.41	10.11	10.11
<b>Indoor Unit</b>										
Air Volume	m <sup>3</sup> /min	15.0	15.0	21.0	21.0	35.0	35.0	35.0	35.0	35.0
	cfm	530	530	740	740	1,235	1,235	1,235	1,235	1,235
Sound Pressure Level [Hi/L0]	dB [A]	38 / 29	38 / 29	40 / 32	40 / 32	46 / 38	46 / 38	46 / 38	46 / 38	46 / 38
Sound Power Level [Hi/L0]	dB	56 / 47	56 / 47	58 / 50	58 / 50	64 / 56	64 / 56	64 / 56	64 / 56	64 / 56
Dimension	Indoor (HxWxD)	mm	235 x 960 x 690	235 x 960 x 690	235 x 1,275 x 690	235 x 1,275 x 690	235 x 1,590 x 690	235 x 1,590 x 690	235 x 1,590 x 690	235 x 1,590 x 690
Net Weight	Indoor	kg	26	26	34	34	40	40	40	40
<b>Outdoor</b>										
Sound Pressure Level	dB [A]	50	51	51	53	55	57	57	58	58
Sound Power Level	dB	69	70	70	72	74	76	76	77	77
Dimension	Outdoor (HxWxD)	mm	619 x 824 x 299	619 x 824 x 299	619 x 824 x 299	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370
Net Weight		kg	29	29	33	39	48	68	67	67
Piping Connection	Gas Pipe	mm (inch)	12.70 (1/2)	12.70 (1/2)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)
	Liquid Pipe	mm (inch)	6.35 (1/4)	6.35 (1/4)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)
Pipe Length	Min-Max	m	5 - 30	5 - 30	5 - 30	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50
Elevation Difference		m	20	20	20	30	30	30	30	30
Maximum Chargeless Length	Max	m	15	15	15	25	25	25	25	25
Additional Gas		g/m	10	10	10	30	30	30	30	30
Operation Range, Outdoor	Min-Max	°C	16-46	16-46	16-46	16-46	16-46	16-46	16-46	16-46

\* Specifications are subject to change without notice. Please refer to technical documents for more details. \* The sound pressure level is measured in accordance with JIS C 9612 and JIS B 8616.