

4-WAY CASSETTE

- Industry-leading Powerful, 360° Wide & Comfortable Airflow.
- The drain pump can pump water up to a height of 850 mm, making drain pipe layout easy.



(Accessory)

(Optional Wired Remote Controller)



[Optional]
If not use
CZ-RTC6WBLW*1*/6BLW*3,
the adaptor also
can be used.

CZ-RTC6W*1/6
CZ-RTC6WBL*1*/2/6BL*2
CZ-RTC6WBLW*1*/3/6BLW*3
*1 Scheduled release date of 4th Quarter in CY23. *2 BL=BLE, *3 BLW=BLE&WLAN

Capacity [Btu/h(Phase)]		17,100	20,500	24,200	29,000	34,100	42,700	47,800	47,800(3)	
Power Source		220-240V, 10 Phase - 50Hz								
Indoor		380-415V, 30 Phase - 50Hz								
Outdoor		220-240V, 10 Phase - 50Hz								
Panel		380-415V, 30 Phase - 50Hz								
Indoor		S-1821PU3H	S-1821PU3H	S-2430PU3H	S-2430PU3H	S-3448PU3H	S-3448PU3H	S-3448PU3H	S-3448PU3H	
Outdoor		U-18PR1H5	U-21PR1H5	U-24PR1H5	U-30PR1H5	U-34PR1H5	U-43PR1H5	U-43PR1H5	U-48PR1H5	
Panel		CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	
Cooling Capacity: Rated [Min-Max]	kW	5.00 [2.00-5.60]	6.00 [2.00-6.30]	7.10 [2.10-8.00]	8.50 [2.10-10.00]	10.00 [3.20-11.20]	12.50 [3.80-14.00]	12.50 [3.80-14.00]	14.00 [3.80-14.71]	
	Btu/h	17,100 [6,820-19,100]	20,500 [6,820-21,500]	24,200 [7,170-27,300]	29,000 [7,170-34,100]	34,100 [10,900-38,200]	42,700 [13,000-47,800]	42,700 [13,000-47,800]	47,800 [13,000-50,200]	
Current: Rated [Min-Max]	A	5.2-5.5	7.5-8.0	8.5-9.2	10.7-11.7	13.7-15.0	16.9-18.5	5.6-6.1	21.9-23.9	
Power Input: Rated [Min-Max]	kW	1.14 [0.38-1.50]	1.71 [0.38-2.10]	1.99 [0.30-2.26]	2.52 [0.28-3.33]	3.23 [0.61-3.73]	3.74 [0.63-4.25]	3.74 [0.63-4.25]	4.83 [0.63-5.10]	
CSPF		6.27	5.89	6.08	5.97	5.89	5.80	5.80	5.23	
COP/EER	W/W	4.39	3.51	3.57	3.37	3.10	3.34	3.34	2.90	
	Btu/hW	15.00	11.99	12.16	11.51	10.56	11.42	11.42	9.90	
Indoor Unit										
Air Volume	m ³ /min	25.0	25.0	25.0	25.0	36.4	36.4	36.4	36.4	
	cfm	882	882	882	882	1,285	1,285	1,285	1,285	
Sound Pressure Level [Hi/Lo]	dB [A]	42 / 35	42 / 35	42 / 35	42 / 35	47 / 41	47 / 41	47 / 41	47 / 41	
Sound Power Level [Hi/Lo]	dB	57 / 50	57 / 50	57 / 50	57 / 50	62 / 56	62 / 56	62 / 56	62 / 56	
Dimension	Indoor (HxWxD)	mm	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	
	Panel (HxWxD)	mm	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	
Net Weight	Indoor	kg	21	21	21	21	24	24	24	
	Panel	kg	5	5	5	5	5	5	5	
Outdoor										
Sound Pressure Level	dB [A]	49	50	51	53	55	57	57	58	
Sound Power Level	dB	68	69	70	72	74	76	76	77	
Dimension	Outdoor (HxWxD)	mm	619 x 824 x 299	619 x 824 x 299	619 x 824 x 299	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	
Net Weight		kg	29	29	33	39	48	68	67	
Piping Connection	Gas Pipe	mm (inch)	12.70 [1/2]	12.70 [1/2]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	
	Liquid Pipe	mm (inch)	6.35 [1/4]	6.35 [1/4]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	
Pipe Length	Min-Max	m	5 - 30	5 - 30	5 - 30	5 - 50	5 - 50	5 - 50	5 - 50	
Elevation Difference		m	20	20	20	30	30	30	30	
Maximum Chargeless Length	Max	m	15	15	15	25	25	25	25	
Additional Gas		g/m	10	10	10	30	30	30	30	
Operation Range, Outdoor	Min-Max	°C	16-46	16-46	16-46	16-46	16-46	16-46	16-46	

* Specifications are subject to change without notice. Please refer to technical documents for more details. * The sound pressure level is measured in accordance with JIS C 9612 and JIS B 8616.