

4-WAY CASSETTE

- 4 discharge space provide comfort cooling to every corner of the room.

Panel



CZ-KPUB1H



A Wireless remote controller is in the same package with the indoor unit.

CZ-RWCB1H (Wireless)



(Optional)

CZ-RTCB1H (Wired)

NON-INVERTER



Capacity (Btu/h)			18,000	24,000	30,000	36,000	48,000	60,000
Power Source		V/Phase Hz	220-240V~, 1phase, 50Hz			380-415V~, 3phase, 50Hz		
Indoor			S-18PUB1H5B	S-24PUB1H5B	S-30PUB1H5B	S-36PUB1H5B	S-48PUB1H5B	S-60PUB1H5B
Outdoor			U-18PNB1H5	U-24PNB1H5	U-30PNB1H5	U-36PNB1H8	U-48PNB1H8	U-60PNB1H8
Panel			CZ-KPUB1H	CZ-KPUB1H	CZ-KPUB1H	CZ-KPUB1H	CZ-KPUB1H	CZ-KPUB1H
Cooling Capacity: Rated		kW	5.28	7.03	8.79	10.55	14.07	17.58
		Btu/h	18,000	24,000	30,000	36,000	48,000	60,000
Current		A	8.00	10.40	12.50	6.69	8.35	10.00
Power Input: Rated		kW	1.76	2.34	2.74	3.60	4.67	5.71
Efficiency Ratio	COP	W/W	3.00	3.00	3.21	2.93	3.01	3.08
	EER	(Btu/h)/W	10.24	10.24	10.95	10.00	10.28	10.51
Indoor Unit								
Air Volume (Hi/Mi/L0)		m³/min	20/16.6/13.3	23.3/20/17.5	30/24.1/20.8	30/24.1/20.8	31.6/26.6/23.3	31.6/26.6/23.3
		cfm	706/586/470	823/706/618	1,059/851/735	1,059/851/735	1,116/939/823	1,116/939/823
Sound Pressure Level (Hi/Mi/L0)		dB [A]	43/40/36	46/42/39	52/47/43	52/47/43	52/47/43	52/47/43
Sound Power Level (Hi/Mi/L0)		dB [A]	53/50/46	56/52/49	62/57/53	62/57/53	62/57/53	62/57/53
Dimension (H×W×D)	Indoor	mm	246×840×840	246×840×840	246×840×840	246×840×840	288×840×840	288×840×840
	Indoor Package	mm	310×910×910	310×910×910	310×910×910	310×910×910	350×910×910	350×910×910
	Panel	mm	55×950×950	55×950×950	55×950×950	55×950×950	55×950×950	55×950×950
	Pane Package	mm	100×1,000×1,000	100×1,000×1,000	100×1,000×1,000	100×1,000×1,000	100×1,000×1,000	100×1,000×1,000
Weight (Net/Gross)	Indoor	kg	24.0/28.0	25.0/29.0	26.0/30.0	26.0/30.0	29.0/33.0	29.0/33.0
	Panel	kg	5.30/7.80	5.30/7.80	5.30/7.80	5.30/7.80	5.30/7.80	5.30/7.80
Outdoor Unit								
Sound Pressure Level		dB [A]	53	54	56	56	57	58
Sound Power Level		dB [A]	64	65	66	66	67	68
Dimension (H×W×D)	Outdoor	mm	545×800×315	655×825×310	700×900×350	805×970×395	805×970×395	1,325×940×370
	Package	mm	620×920×400	725×945×435	770×1,020×430	890×1,105×495	890×1,105×495	1,440×1,080×430
Weight (Net/Gross)		kg	36.0/39.0	44.0/47.5	53.0/57.0	62.0/66.0	72.0/76.0	93.0/103.0
Piping Connection	Gas Pipe	mm [inch]	12.7 [1/2"]	15.88 [5/8"]	15.88 [5/8"]	15.88 [5/8"]	15.88 [5/8"]	19.05 [3/4"]
	Liquid Pipe	mm [inch]	6.35 [1/4"]	9.52 [3/8"]	9.52 [3/8"]	9.52 [3/8"]	9.52 [3/8"]	9.52 [3/8"]
Pipe Length (Max)		m	30	30	30	50	50	50
Elevation Difference		m	20	20	20	30	30	30
Maximum Chargeless Length (Max)		m	5	5	5	5	5	5
Additional Gas		g/m	30	50	50	50	50	50
Operating Range, Outdoor (Min-Max)		°C	17-49	17-49	17-49	17-49	17-49	17-49