

F3 TYPE MID STATIC DUCTED Dimensions

Type	A	B	C	D	E	F	Air intake port size
	mm	mm	mm	mm	mm	Q'ty	mm
22/28/36/45/56	867	800	450 (Pitch 150 × 3)	71	592	12	204 × 683
60/73/90	1,067	1,000	750 (Pitch 150 × 5)	21	792	16	204 × 883
112/140/160	1,467	1,400	1,050 (Pitch 150 × 7)	71	1,192	20	204 × 1,283

①	Refrigerant tubing joint (liquid tube) S-22/28/36/45/56MF3E5AN : Φ6.35 (flared) S-60/73/90/112/140/160MF3E5AN : Φ9.52 (flared)
②	Refrigerant tubing joint (gas tube) S-22/28/36/45/56MF3E5AN : Φ12.7 (flared) S-60/73/90/112/140/160MF3E5AN : Φ15.88 (flared)
③	Upper drain port VP20 (ø26 mm) 200 mm flexible hose supplied
④	Bottom drain port VP20 (ø26 mm)
⑤	Suspension lug (4 – 12 × 30 mm)
⑥	Power supply outlet
⑦	Fresh air intake port (ø100 mm) ^{*1}
⑧	Flange for flexible air outlet duct
⑨	Electrical component box

*1 Necessary to attach duct connecting flange (field supply).



Inspection access
(Field supply)
See "Required Minimum
Space for Installation and
Maintenance Services"
on page 4-5-23 to 4-5-24.

