

DELUXE 4-WAY CASSETTE

- With the further advanced air purification technology of nanoe™ X Generator Mark 3.
- Powerful industry-leading, 360° wide, comfortable airflow.
- The drain pump can pump water up to a height of 850 mm, making drain pipe layout easy.



nanoeX
Generator Mark3

Panel



CZ-KPU3H

(Accessory)



(Optional Wired Remote Controller)



CZ-RTC6W*1/6*2
CZ-RTC6WBL*1*3/6BL*2*3
CZ-RTC6WBL*1*4/6BLW*2*4

CZ-RTC5B CZ-RTC4

*1 W=White colour, *2 w/o W=Black colour,
*3 BL=BLE, *4 BLW=BLE&WLAN

DELUXE

Specifications of R32 DELUXE Series R32

Capacity [Btu/h(Phase)]		17,100	20,500	24,200	34,100	42,700	42,700[3]	47,800	47,800[3]
Power Source	V/Phase Hz	230V, 10 Phase - 60Hz			400V, 30 Phase - 60Hz		230V, 10 Phase - 60Hz		400V, 30 Phase - 60Hz
Indoor Unit		S-18PU3QA	S-21PU3QA	S-24PU3QA	S-34PU3QA	S-43PU3QA	S-3448PU3QA	S-48PU3QA	S-3448PU3QA
Outdoor Unit		U-18PRH1Q6	U-21PRH1Q6	U-24PRH1Q6	U-34PRH1Q6	U-43PRH1Q6	U-43PRH1Q9	U-48PRH1Q6	U-48PRH1Q9
Panel		CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H	CZ-KPU3H
Cooling Capacity: Rated [Min-Max]	kW	5.00 [2.00-6.00]	6.00 [2.00-6.30]	7.10 [2.10-8.00]	10.00 [3.80-11.20]	12.50 [3.80-14.00]	12.50 [3.80-14.00]	14.00 [5.30-15.50]	14.00 [5.30-15.50]
	Btu/h	17,100 [6,820-20,500]	20,500 [6,820-21,500]	24,200 [7,170-27,300]	34,100 [13,000-38,200]	42,700 [13,000-47,800]	42,700 [13,000-47,800]	47,800 [18,100-52,900]	47,800 [18,100-52,900]
Current: Rated [Max]	A	4.1 [9.1]	5.7 [11.0]	7.0 [12.0]	11.1 [25.5]	16.2 [26.0]	5.3 [10.5]	19.4 [28.0]	6.4 [11.5]
Power Input: Rated [Min-Max]	kW	0.90 [0.26-1.35]	1.27 [0.26-1.65]	1.57 [0.28-2.25]	2.35 [0.62-3.00]	3.42 [0.63-4.10]	3.42 [0.63-4.10]	4.10 [0.96-4.90]	4.10 [0.96-4.90]
CSPF		7.50	7.10	6.80	6.60	6.30	6.30	5.70	5.70
COP/EER	W/W	5.56	4.72	4.52	4.26	3.65	3.65	3.41	3.41
	Btu/hW	19.00	16.14	15.41	14.51	12.49	12.49	11.66	11.66
Indoor Unit									
Air Volume	m ³ /min	25.0	25.0	25.0	36.4	36.4	36.4	36.4	36.4
	cfm	882	882	882	1,285	1,285	1,285	1,285	1,285
Sound Pressure Level [Hi/L0]	dB [A]	42 / 35	42 / 35	42 / 35	47 / 41	47 / 41	47 / 41	47 / 41	47 / 41
Sound Power Level [Hi/L0]	dB [A]	57 / 50	57 / 50	57 / 50	62 / 56	62 / 56	62 / 56	62 / 56	62 / 56
Dimension	Indoor (HxWxD) mm	256 x 840 x 840	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840
	Panel (HxWxD) mm	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950	44 x 950 x 950
Net Weight	Indoor kg	21	21	21	24	24	24	24	24
	Panel kg	5	5	5	5	5	5	5	5
Outdoor Unit									
Sound Pressure Level	dB [A]	50	51	53	54	57	57	58	58
Sound Power Level	dB [A]	69	70	72	73	76	76	77	77
Dimension	Outdoor (HxWxD) mm	695 x 875 x 320	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370
Net Weight	kg	39	39	39	69	69	67	75	73
Piping Connection	Gas Pipe mm (inch)	12.70 [1/2]	12.70 [1/2]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]
	Liquid Pipe mm (inch)	6.35 [1/4]	6.35 [1/4]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]
Pipe Length	Min-Max m	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50
Elevation Difference	m	30	30	30	30	30	30	30	30
Maximum Chargeless Length	Max m	30	30	30	30	30	30	30	30
Additional Gas	g/m	15	15	25	25	25	25	25	25
Operation Range, Outdoor	Min-Max °C	16-52	16-52	16-52	16-52	16-52	16-52	16-52	16-52

* Specifications are subject to change without notice. Please refer to technical documents for more details. * The sound pressure level is measured in accordance with JIS C 9612 and JIS B 8616. * DELUXE series indoor units can only be connected to outdoor units of the same series.

DELUXE / STANDARD ADAPTIVE DUCTED

- Air intake from rear as standard. Industry-leading horizontal and vertical design.
- Powerful 150Pa ESP and space saving 250 mm height, filter included.
- Built-in Drain pump and selectable air inlet position (bottom and rear).



Selectable
Remote
Controller



CZ-RTC6W*1/6*2
CZ-RTC6WBL*1*3/6BL*2*3
CZ-RTC6WBLW*1*4/6BLW*2*4

CZ-RTC5B CZ-RTC4
*1 W=White colour, *2 w/o W=Black colour,
*3 BL=BLE, *4 BLW=BLE&WLAN

nanoeX™
Generator Mark2

DELUXE

Specifications of R32 DELUXE Series R32

Capacity [Btu/h(Phase)]		17,100	20,500	24,200	34,100	42,700	42,700[3]	47,800	47,800[3]	
Power Source	V/Phase Hz			230V, 10 Phase - 60Hz			400V, 30 Phase - 60Hz	230V, 10 Phase - 60Hz	400V, 30 Phase - 60Hz	
Indoor Unit		S-1821PF3Q	S-1821PF3Q	S-2430PF3Q	S-3448PF3Q	S-3448PF3Q	S-3448PF3Q	S-3448PF3Q	S-3448PF3Q	
Outdoor Unit		U-18PRH1Q6	U-21PRH1Q6	U-24PRH1Q6	U-34PRH1Q6	U-43PRH1Q6	U-43PRH1Q9	U-48PRH1Q6	U-48PRH1Q9	
Cooling Capacity: Rated [Min-Max]	kW	5.00 [1.60-6.00]	6.00 [1.60-6.30]	7.10 [1.80-8.00]	10.00 [3.80-11.20]	12.50 [3.80-14.00]	12.50 [3.80-14.00]	14.00 [5.30-15.50]	14.00 [5.30-15.50]	
	Btu/h	17,100 [5,460-20,500]	20,500 [5,460-21,500]	24,200 [6,140-27,300]	34,100 [13,000-38,200]	42,700 [13,000-47,800]	42,700 [13,000-47,800]	47,800 [18,100-52,900]	47,800 [18,100-52,900]	
Current: Rated [Max]	A	5.3 [9.1]	7.1 [11.0]	8.0 [12.0]	11.3 [25.5]	17.0 [26.0]	5.6 [10.5]	20.5 [28.0]	6.7 [11.5]	
Power Input: Rated [Min-Max]	kW	1.16 [0.24-1.55]	1.58 [0.24-1.80]	1.80 [0.30-2.35]	2.40 [0.65-3.08]	3.59 [0.65-4.35]	3.59 [0.65-4.35]	4.34 [0.96-5.15]	4.34 [0.96-5.15]	
CSPF		5.90	5.60	6.10	6.40	5.45	5.45	5.55	5.55	
COP/EER	W/W	4.31	3.80	3.94	4.17	3.48	3.48	3.23	3.23	
	Btu/hW	14.74	12.97	13.44	14.21	11.89	11.89	11.01	11.01	
Indoor Unit										
Air Volume	m ³ /min	16.0	16.0	21.0	36.0	36.0	36.0	36.0	36.0	
	cfm	565	565	740	1,270	1,270	1,270	1,270	1,270	
External static pressure	Pa	30 [10-150]	30 [10-150]	30 [10-150]	50 [10-150]	50 [10-150]	50 [10-150]	50 [10-150]	50 [10-150]	
Sound Pressure Level [Hi/L0]	dB [A]	35 / 29	35 / 29	35 / 29	40 / 30	40 / 30	40 / 30	40 / 30	40 / 30	
Sound Power Level [Hi/L0]	dB [A]	58 / 52	58 / 52	58 / 52	63 / 53	63 / 53	63 / 53	63 / 53	63 / 53	
Dimension	Indoor (HxWxD)	mm	250 x 800 x 730	250 x 800 x 730	250 x 1,000 x 730	250 x 1,400 x 730	250 x 1,400 x 730	250 x 1,400 x 730	250 x 1,400 x 730	
Net Weight	Indoor	kg	25	25	30	39	39	39	39	
Outdoor Unit										
Sound Pressure Level	dB [A]	50	51	53	54	57	57	58	58	
Sound Power Level	dB [A]	69	70	72	73	76	76	77	77	
Dimension	Outdoor (HxWxD)	mm	695 x 875 x 320	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	
Net Weight		kg	39	39	39	69	69	75	73	
Piping Connection	Gas Pipe	mm (inch)	12.70 [1/2]	12.70 [1/2]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	
	Liquid Pipe	mm (inch)	6.35 [1/4]	6.35 [1/4]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	
Pipe Length	Min-Max	m	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	
Elevation Difference		m	30	30	30	30	30	30	30	
Maximum Chargeless Length	Max	m	30	30	30	30	30	30	30	
Additional Gas		g/m	15	15	25	25	25	25	25	
Operation Range, Outdoor	Min-Max	°C	16-52	16-52	16-52	16-52	16-52	16-52	16-52	

* Specifications are subject to change without notice. Please refer to technical documents for more details. * The sound pressure level is measured in accordance with JIS C 9612 and JIS B 8616. * DELUXE series indoor units can only be connected to outdoor units of the same series.

DELUXE / STANDARD CEILING EXPOSED

- The slim design makes thickness only 235 mm.
- Compact looking, stylish, one-motion design.
- Comfortable, long-distance airflow distribution.



(Accessory)



(Optional Wired Remote Controller)



CZ-RTC6W*1/6*2
CZ-RTC6WBL*1*3/6BL*2*3
CZ-RTC6WBLW*1*4/6BLW*2*4



CZ-RTC5B



CZ-RTC4

*1 W=White colour, *2 w/o W=Black colour,
*3 BL=BLE, *4 BLW=BLE+WLAN

nanoeX™
Generator Mark2

DELUXE

Specifications of R32 DELUXE Series R32

Capacity [Btu/h(Phase)]		17,100	20,500	24,200	34,100	42,700	42,700[3]	47,800	47,800[3]
Power Source	V/Phase Hz	230V, 10 Phase - 60Hz			400V, 30 Phase - 60Hz		230V, 10 Phase - 60Hz		400V, 30 Phase - 60Hz
Indoor Unit		S-18PT30A	S-21PT30A	S-24PT30A	S-34PT30A	S-43PT30A	S-3448PT30A	S-48PT30A	S-3448PT30A
Outdoor Unit		U-18PRH1Q6	U-21PRH1Q6	U-24PRH1Q6	U-34PRH1Q6	U-43PRH1Q6	U-43PRH1Q9	U-48PRH1Q6	U-48PRH1Q9
Cooling Capacity: Rated [Min-Max]	kW	5.00 [1.80-6.00]	6.00 [1.80-6.30]	7.10 [1.80-8.00]	10.00 [3.80-11.20]	12.50 [3.80-14.00]	12.50 [3.80-14.00]	14.00 [5.30-15.50]	14.00 [5.30-15.50]
	Btu/h	17,100 [6,140-20,500]	20,500 [6,140-21,500]	24,200 [6,140-27,300]	34,100 [13,000-38,200]	42,700 [13,000-47,800]	42,700 [13,000-47,800]	47,800 [18,100-52,900]	47,800 [18,100-52,900]
Current: Rated [Max]	A	4.9 [9.1]	6.5 [11.0]	7.5 [12.0]	11.7 [25.5]	17.7 [26.0]	5.8 [10.5]	20.0 [28.0]	6.6 [11.5]
Power Input: Rated [Min-Max]	kW	1.08 [0.27-1.43]	1.44 [0.27-1.72]	1.70 [0.25-2.15]	2.47 [0.68-3.04]	3.75 [0.68-4.40]	3.75 [0.68-4.40]	4.24 [0.94-5.00]	4.24 [0.94-5.00]
CSPF		7.20	6.70	6.85	6.05	5.50	5.50	5.40	5.40
COP/EER	W/W	4.63	4.17	4.18	4.05	3.33	3.33	3.30	3.30
	Btu/hW	15.83	14.24	14.24	13.81	11.39	11.39	11.27	11.27
Indoor Unit									
Air Volume	m ³ /min	15.0	15.0	21.0	35.0	35.0	35.0	35.0	35.0
	cfm	530	530	740	1,235	1,235	1,235	1,235	1,235
Sound Pressure Level [Hi/L0]	dB [A]	38 / 29	38 / 29	40 / 32	46 / 38	46 / 38	46 / 38	46 / 38	46 / 38
Sound Power Level [Hi/L0]	dB [A]	56 / 47	56 / 47	58 / 50	64 / 56	64 / 56	64 / 56	64 / 56	64 / 56
Dimension	Indoor (HxWxD)	mm	235 x 960 x 690	235 x 960 x 690	235 x 1,275 x 690	235 x 1,590 x 690	235 x 1,590 x 690	235 x 1,590 x 690	235 x 1,590 x 690
Net Weight	Indoor	kg	26	26	34	40	40	40	40
Outdoor Unit									
Sound Pressure Level	dB [A]	50	51	53	54	57	57	58	58
Sound Power Level	dB [A]	69	70	72	73	76	76	77	77
Dimension	Outdoor (HxWxD)	mm	695 x 875 x 320	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370
Net Weight		kg	39	39	39	69	69	75	73
Piping Connection	Gas Pipe	mm (inch)	12.70 [1/2]	12.70 [1/2]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]	15.88 [5/8]
	Liquid Pipe	mm (inch)	6.35 [1/4]	6.35 [1/4]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]	9.52 [3/8]
Pipe Length	Min-Max	m	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50
Elevation Difference		m	30	30	30	30	30	30	30
Maximum Chargeless Length	Max	m	30	30	30	30	30	30	30
Additional Gas		g/m	15	15	25	25	25	25	25
Operation Range, Outdoor	Min-Max	°C	16-52	16-52	16-52	16-52	16-52	16-52	16-52

* Specifications are subject to change without notice. Please refer to technical documents for more details. * The sound pressure level is measured in accordance with JIS C 9612 and JIS B 8616. * DELUXE series indoor units can only be connected to outdoor units of the same series.