



S-73MZ1H4A

S-22MZ1H4A/ S-28MZ1H4A/ S-36MZ1H4A  
S-45MZ1H4A/ S-56MZ1H4A/ S-60MZ1H4A

## Optional accessory



CZ-RTC6W  
CZ-RTC6WBL



CZ-RTC6  
CZ-RTC6BL



CZ-CENS1



CZ-RTC5B



CZ-RWS3  
Remote controller



CZ-RWRC3  
Receiver

Model Name			S-22MZ1H4A	S-28MZ1H4A	S-36MZ1H4A	S-45MZ1H4A	S-56MZ1H4A	S-60MZ1H4A	S-73MZ1H4A	
Power source			220/230/240 V, 1 phase - 50/60 Hz							
Cooling capacity	kW		2.2	2.8	3.6	4.5	5.6	6.0	7.3	
	BTU/h		7,500	9,500	12,200	15,300	19,100	20,500	24,900	
Heating capacity	kW		2.5	3.2	4.2	5.1	6.4	7.1	8.0	
	BTU/h		8,500	10,900	14,300	17,400	21,800	24,200	27,300	
Power input	Cooling	kW	0.075/0.075/0.075	0.080/0.080/0.080	0.085/0.085/0.085	0.095/0.095/0.095	0.100/0.100/0.100	0.100/0.100/0.100	0.125/0.125/0.125	
	Heating	kW	0.075/0.075/0.075	0.080/0.080/0.080	0.085/0.085/0.085	0.095/0.095/0.095	0.100/0.100/0.100	0.100/0.100/0.100	0.125/0.125/0.125	
Running current	Cooling	A	0.50/0.47/0.45	0.55/0.52/0.50	0.60/0.57/0.55	0.70/0.68/0.65	0.75/0.72/0.70	0.75/0.72/0.70	0.80/0.78/0.75	
	Heating	A	0.50/0.47/0.45	0.55/0.52/0.50	0.60/0.57/0.55	0.70/0.68/0.65	0.75/0.72/0.70	0.75/0.72/0.70	0.80/0.78/0.75	
Fan	Type		Sirroco fan	Sirroco fan	Sirroco fan	Sirroco fan	Sirroco fan	Sirroco fan	Sirroco fan	
	Air flow rate (H/M/L)	m <sup>3</sup> /h	480/420/360	600/540/420	600/540/420	690/630/510	720/660/540	870/750/630	1,080/840/660	
		L/s	133/117/100	167/150/117	167/150/117	192/175/142	200/183/150	242/208/175	300/233/183	
	Motor output	kW	0.06	0.06	0.06	0.06	0.06	0.06	0.06	
	External static pressure	Pa	10-30	10-30	10-30	10-30	10-30	10-30	10-30	
Sound power level (H/M/L)		dB	50/49/47	52/51/49	54/52/50	56/54/52	57/55/53	60/57/55	62/60/58	
Sound pressure level (H/M/L)		dB(A)	28/27/25	30/29/27	32/30/28	34/32/30	35/33/31	38/35/33	40/38/36	
Dimensions	H x W x D		mm	200×830×500	200×830×500	200×830×500	200×830×500	200×830×500	200×1,050×550	
	Pipe connections	Liquid	mm (inches)	Ø6.35 (Ø1/4)	Ø6.35 (Ø1/4)	Ø6.35 (Ø1/4)	Ø6.35 (Ø1/4)	Ø6.35 (Ø1/4)	Ø9.52 (Ø3/8)	Ø9.52 (Ø3/8)
Gas		mm (inches)	Ø12.7 (Ø1/2)	Ø12.7 (Ø1/2)	Ø12.7 (Ø1/2)	Ø12.7 (Ø1/2)	Ø12.7 (Ø1/2)	Ø15.88 (Ø5/8)	Ø15.88 (Ø5/8)	
Drain piping			VP-25	VP-25	VP-25	VP-25	VP-25	VP-25	VP-25	
Net weight		kg	17	17	18	18	18	18	24	

GLOBAL REMARKS	Rated conditions:	Cooling	Heating
	Indoor air temperature	27°C DB / 19°C WB	20°C DB
	Outdoor air temperature	35°C DB / 24°C WB	7°C DB / 6°C WB

Specifications are subject to change without notice.